
MMM MMM OOOOOOOOO UUU UUU NNN NNN TTTTTTTTTTTTTTT
MMM MMM OOOOOOOOO UUU UUU NNN NNN TTTTTTTTTTTTTTT
MMM MMM OOOOOOOOO UUU UUU NNN NNN TTTTTTTTTTTTTTT
MMMMMM MMMMMM OOO OOO UUU UUU NNN NNN TTT
MMMMMM MMMMMM OOO OOO UUU UUU NNN NNN TTT
MMMMMM MMMMMM OOO OOO UUU UUU NNN NNN TTT
MMM MMM MMM OOO OOO UUU UUU NNNNNN NNN TTT
MMM MMM MMM OOO OOO UUU UUU NNNNNN NNN TTT
MMM MMM MMM OOO OOO UUU UUU NNNNNN NNN TTT
MMM MMM OOO OOO UUU UUU NNN NNN NNN TTT
MMM MMM OOO OOO UUU UUU NNN NNN NNN TTT
MMM MMM OOO OOO UUU UUU NNN NNN NNN TTT
MMM MMM OOO OOO UUU UUU NNN NNNNNN TTT
MMM MMM OOO OOO UUU UUU NNN NNNNNN TTT
MMM MMM OOO OOO UUU UUU NNN NNNNNN TTT
MMM MMM OOO OOO UUU UUU NNN NNN TTT
MMM MMM OOO OOO UUU UUU NNN NNN TTT
MMM MMM OOO OOO UUU UUU NNN NNN TTT
MMM MMM OOOOOOOOO UUUUUUUUUUUUUUU NNN NNN TTT
MMM MMM OOOOOOOOO UUUUUUUUUUUUUUU NNN NNN TTT
MMM MMM OOOOOOOOO UUUUUUUUUUUUUUU NNN NNN TTT

FILEID**ASSIST



```
;     1          0001  0 MODULE ASSIST   (
;     2          0002  0                  LANGUAGE (BLISS32),
;     3          0003  0                  IDENT = 'V04-001'
;     4          0004  0                 ) =
;     5          0005  0
;     6          0006  1 BEGIN
;     7          0007  1
;     8          0008  1 !*****************************************************************************
;     9          0009  1 !*                                                                           *
;    10          0010  1 !*  COPYRIGHT (c) 1978, 1980, 1982, 1984 BY                                  *
;    11          0011  1 !*  DIGITAL EQUIPMENT CORPORATION, MAYNARD, MASSACHUSETTS.                    *
;    12          0012  1 !*  ALL RIGHTS RESERVED.                                                      *
;    13          0013  1 !*                                                                           *
;    14          0014  1 !*  THIS SOFTWARE IS FURNISHED UNDER A LICENSE AND MAY BE USED AND COPIED     *
;    15          0015  1 !*  ONLY IN  ACCORDANCE WITH  THE  TERMS  OF  SUCH  LICENSE  AND WITH THE    *
;    16          0016  1 !*  INCLUSION OF THE ABOVE COPYRIGHT NOTICE. THIS SOFTWARE OR  ANY  OTHER     *
;    17          0017  1 !*  COPIES THEREOF MAY NOT BE PROVIDED OR OTHERWISE MADE AVAILABLE TO ANY     *
;    18          0018  1 !*  OTHER PERSON.  NO TITLE TO AND OWNERSHIP OF  THE  SOFTWARE IS  HEREBY     *
;    19          0019  1 !*  TRANSFERRED.                                                              *
;    20          0020  1 !*                                                                           *
;    21          0021  1 !*  THE INFORMATION IN THIS SOFTWARE IS  SUBJECT TO CHANGE WITHOUT NOTICE     *
;    22          0022  1 !*  AND  SHOULD  NOT  BE  CONSTRUED AS  A COMMITMENT BY DIGITAL EQUIPMENT     *
;    23          0023  1 !*  CORPORATION.                                                              *
;    24          0024  1 !*                                                                           *
;    25          0025  1 !*  DIGITAL ASSUMES NO RESPONSIBILITY FOR THE USE  OR  RELIABILITY OF ITS     *
;    26          0026  1 !*  SOFTWARE ON EQUIPMENT WHICH IS NOT SUPPLIED BY DIGITAL.                   *
;    27          0027  1 !*                                                                           *
;    28          0028  1 !*                                                                           *
;    29          0029  1 !*****************************************************************************
;    30          0030  1
;    31          0031  1 !++
;    32          0032  1 !
;    33          0033  1 ! FACILITY:
;    34          0034  1 !
;    35          0035  1 !       MOUNT
;    36          0036  1 !
;    37          0037  1 ! ABSTRACT:
;    38          0038  1 !
;    39          0039  1 !       This module contains the routines to
;    40          0040  1 !       implement operator assisted mount.
;    41          0041  1 !
;    42          0042  1 ! ENVIRONMENT:
;    43          0043  1 !
;    44          0044  1 !       VAX/VMS operating system.
;    45          0045  1 !
;    46          0046  1 ! AUTHOR:
;    47          0047  1 !
;    48          0048  1 !       Steven T. Jeffreys
;    49          0049  1 !
;    50          0050  1 ! CREATION DATE:
;    51          0051  1 !
;    52          0052  1 !       October 9, 1980
;    53          0053  1 !
;    54          0054  1 ! MODIFIED BY:
;    55          0055  1 !
;    56          0056  1 !       V04-001 HH0056          Hai Huang                   11-Sep-1984
;    57          0057  1 !               Do limited number of retries on VOLINV error.
```

```
;    58          0058  1 !
;    59          0059  1 !       V03-007 HH0041          Hai Huang                       24-Jul-1984
;    60          0060  1 !               Remove REQUIRE  'LIBD$:[VMSLIB.OBJ]MOUNTMSG.B32'.
;    61          0061  1 !
;    62          0062  1 !       V03-006 CWH3001         CW Hobbs                        30-Jul-1983
;    63          0063  1 !               Various and sundry things to make OPCOM distributed
;    64          0064  1 !               across the cluster.
;    65          0065  1 !
;    66          0066  1 !       V03-005 TCM0002         Trudy C. Matthews       28-Jul-1983
;    67          0067  1 !               Add DEV_ACQUIRED flag that indicates whether mount interlock
;    68          0068  1 !               has been taken out for this device.  Remove DEALLOCATE_DEVICE
;    69          0069  1 !               routine, since devices mounted /SHARE, /SYSTEM or /GROUP are
;    70          0070  1 !               no longer allocated.  Remove temporary change introduced in
;    71          0071  1 !               TCM0001.
;    72          0072  1 !
;    73          0073  1 !       V03-004 TCM0001         Trudy C. Matthews       18-Jul-1983
;    74          0074  1 !               Make SS$_NOTQUEUED status (received from the $ENQ system
;    75          0075  1 !               service when we cannot take out a cluster-wide allocation
;    76          0076  1 !               lock on this device) one of the status codes acted on by
;    77          0077  1 !               operator-assisted mount.
;    78          0078  1 !
;    79          0079  1 !       V03-003 STJ50311        Steven T. Jeffreys      10-Feb-1983
;    80          0080  1 !               - Make all uses of PHYS_NAME indexed by DEVICE_INDEX.
;    81          0081  1 !               - Reset PREVIOUS_STATUS after an operator reply arrives.
;    82          0082  1 !               - If the mount failed with an operator request outstanding,
;    83          0083  1 !                 signal MOUN$_OPRQSTCAN instead of MOUN$_RQSTDON.
;    84          0084  1 !               - Define and use routine $DALLOC_DEVS.
;    85          0085  1 !
;    86          0086  1 !       V03-002 STJ0244         Steven T. Jeffreys      04-Apr-1982
;    87          0087  1 !               - Use common I/O routines, and make the code more
;    88          0088  1 !                 tolerant to random event flag setting and clearing.
;    89          0089  1 !               - Issue the MOUN$_RQSTDON status if the mount completes
;    90          0090  1 !                 successfully while we have an operator request outstanding.
;    91          0091  1 !
;    92          0092  1 !       V03-001 BLS0160         Benn Schreiber          18-Mar-1982
;    93          0093  1 !               Get OPCDEFTMP from SHRLIB$.
;    94          0094  1 !
;    95          0095  1 !       V02-011 STJ0229         Steven T. Jeffreys      01-Mar-1982
;    96          0096  1 !               - Set the inhibit message bit in the exit status
;    97          0097  1 !                 code if the message output via $PUTMSG.
;    98          0098  1 !
;    99          0099  1 !       V02-010 STJ0218         Steven T. Jeffreys      16-Feb-1982
;   100          0100  1 !               - Cancel exit handler before declaring it.
;   101          0101  1 !               - Clear system service failure exception mode and
;   102          0102  1 !                 restore it on exit.
;   103          0103  1 !
;   104          0104  1 !       V02-009 STJ0214         Steven T. Jeffreys      11-Feb-1982
;   105          0105  1 !               Add support for the /COMMENT switch.
;   106          0106  1 !
;   107          0107  1 !       V02-008 STJ0206         Steven T. Jeffreys      08-Feb-1982
;   108          0108  1 !               Set mailbox access rights to allow SYSTEM and OWNER
;   109          0109  1 !               read and write privileges.
;   110          0110  1 !
;   111          0111  1 !       V02-007 STJ0189         Steven T. Jeffreys      02-Feb-1982
;   112          0112  1 !               Initalize GLOBAL storage at run time, and fix various bugs.
;   113          0113  1 !
;   114          0114  1 !       V02-006 STJ174          Steven T. Jeffreys      19-Jan-1982
```

```
;   115          0115  1 !                 Made most of the GLOBAL routines in to local routines.
;   116          0116  1 !
;   117          0117  1 !       V02-005 STJ162          Steven T. Jeffreys      04-Jan-1982
;   118          0118  1 !               Removed copy of INTERCEPT_SIGNAL.
;   119          0119  1 !
;   120          0120  1 !       V02-004 STJ0150         Steven T. Jeffreys
;   121          0121  1 !               Extensive rewrite to support the $MOUNT system service.
;   122          0122  1 !
;   123          0123  1 !       V02-003 STJ0112         Steven T. Jeffreys
;   124          0124  1 !               - Use general addressing mode for library routines.
;   125          0125  1 !               - Fixed SET_TARGET_MASK.
;   126          0126  1 !               - Fixed SUBMIT_REQUEST to calculate actual message size.
;   127          0127  1 !               - Added support for alternate cancellation message.
;   128          0128  1 !               - Handle REPLY/BLANK_TAPE and REPLY/INITIALIZE_TAPE operator replies.
;   129          0129  1 !
;   130          0130  1 !       V02-002 STJ0083         Steven T. Jeffreys
;   131          0131  1 !               - Changed $DELMBX call in CANCEL_REQUEST to $DASSGN to properly
;   132          0132  1 !                 delete the mailbox and free up the channel.
;   133          0133  1 !               - Changed error recovery handlers to use the physical device
;   134          0134  1 !                  name string when referring to the device.
;   135          0135  1 !               - Added logic to recover from an SS$_INCVOLLABEL error, which
;   136          0136  1 !                 occurs when the label of the volume present in the drive does
;   137          0137  1 !                 not match the volume label specified by the user.
;   138          0138  1 !
;   139          0139  1 !--
;   140          0140  1
;   141          0141  1 LIBRARY 'SYS$LIBRARY:LIB.L32';
;   142          0142  1 LIBRARY 'SYS$LIBRARY:TPAMAC';
;   143          0143  1 REQUIRE 'LIBD$:[VMSLIB.OBJ]INITMSG.REQ';
;   144          0275  1 REQUIRE 'SHRLIB$:OPCDEFTMP';     ! *** TEMPORARY
;   145          0516  1 REQUIRE 'SRC$:MOUDEF.B32';
;   146          1048  1
;   147          1049  1 FORWARD ROUTINE
;   148          1050  1
;   149          1051  1         SYS$MOUNT,                          ! Main entry point of $MOUNT
;   150          1052  1         INTERCEPT_SIGNAL,                   ! Main condition handler
;   151          1053  1         SUBMIT_REQUEST   : NOVALUE,         ! Send request to operator
;   152          1054  1         SET_TARGET_MASK  : NOVALUE,         ! Sets operator target mask
;   153          1055  1         POST_READ_TO_MBX: NOVALUE,          ! Post read to reply mailbox
;   154          1056  1         INTERACTIVE_JOB,                    ! Determines if we're a batch job
;   155          1057  1         PRINT_REPLY      : NOVALUE,         ! Print the operator reply
;   156          1058  1         PARSE_REPLY      : NOVALUE,         ! Parse the oprator's reply
;   157          1059  1         CANCEL_REQUEST   : NOVALUE,         ! Cancel the operator request
;   158          1060  1         CHECK_FOR_REPLY  : NOVALUE,         ! Check for operator response
;   159          1061  1         ALLOCFAIL_HNDLR  : NOVALUE,         ! Handle device allocation failures
;   160          1062  1         MEDOFL_HNDLR     : NOVALUE,         ! Handle SS$_MEDOFL condition
;   161          1063  1         WRONGVOL_HNDLR   : NOVALUE,         ! Handle SS$_INCVOLLABEL condition
;   162          1064  1         INVALID_COMMAND,                    ! Notify user/operator of invalid reply
;   163          1065  1         EXIT_HANDLER     : NOVALUE;         ! Exit handler
;   164          1066  1
;   165          1067  1 FORWARD
;   166          1068  1
;   167          1069  1         STATE_TABLE      : VECTOR [0],      ! TPARSE state table
;   168          1070  1         KEY_TABLE        : VECTOR [0];      ! TPARSE key table
;   169          1071  1
;   170          1072  1 STRUCTURE
;   171          1073  1
```

```
;  172          1074  1          EXTERNAL_CTRL_BLK [I ; N] =                     ! exit handler descriptor
;  173          1075  1              [(4+N)*4]                                   ! N = # of arguments ( N <= 1)
;  174          1076  1              (EXIT_CTRL_BLK+I*4)<0,32,0>;                ! the block is a longword array
;  175          1077  1
;  176          1078  1  MACRO
;  177          1079  1          !
;  178          1080  1          ! Abort the mount operation.
;  179          1081  1          !
;  180        M 1082  1          ABORT_MOUNT (CODE) =
;  181        M 1083  1                  SIGNAL_STOP     (%IF NOT %NULL (CODE) %THEN CODE %ELSE 0 %FI
;  182        M 1084  1                                   %IF NOT %NULL (%REMAINING) %THEN , %REMAINING %FI
;  183        M 1085  1                                  )%;
;  184          1086  1
;  185          1087  1  MACRO
;  186          1088  1          !
;  187          1089  1          ! Generate a static string descriptor
;  188          1090  1          !
;  189        M 1091  1          DESCRIP (STRING) =
;  190        M 1092  1                  BBLOCK  [DSC$K_S_BLN]
;  191        M 1093  1                  INITIAL (WORD (%CHARCOUNT (STRING)),
;  192        M 1094  1                           BYTE (DSC$K_DTYPE_T),
;  193        M 1095  1                           BYTE (DSC$K_CLASS_S),
;  194        M 1096  1                           LONG (UPLIT BYTE (STRING))
;  195        M 1097  1                          )%;
;  196          1098  1
;  197          1099  1  MACRO
;  198          1100  1          !
;  199          1101  1          ! 3 byte operator mask field definition.
;  200          1102  1          !
;  201          1103  1          TARGET_FIELD = $BYTEOFFSET(OPC$B_MS_TARGET), 0, 24, 0%;
;  202          1104  1
;  203          1105  1  MACRO
;  204          1106  1          !
;  205          1107  1          ! For documentation purposes, define a boolean variable
;  206          1108  1          ! that can only take on the values TRUE or FALSE.
;  207          1109  1          !
;  208          1110  1          BOOLEAN = LONG%;
;  209          1111  1
;  210          1112  1  LITERAL
;  211          1113  1          FAO_BUFFER_SIZE = 512,          ! Max length of FAO result string
;  212          1114  1          MAX_DEV_LENGTH  = 63,           ! Max length of device name
;  213          1115  1          !
;  214          1116  1          ! Create the reply mailbox protection mask.  Allow only
;  215          1117  1          ! OWNER(read) and SYSTEM(read,write) access.  See documentation
;  216          1118  1          ! of the $CREMBX system service for more info.
;  217          1119  1          !
;  218          1120  1          MAILBOX_PROTECTION = %X'FF00',
;  219          1121  1          !
;  220          1122  1          ! The following are boolean values that are used to make the
;  221          1123  1          ! code more readable.  They are used as input to CANCEL_REQUEST.
;  222          1124  1          !
;  223          1125  1          REQUEST_SATISFIED       = 1,    ! The request completed w/o opertor intervention
;  224          1126  1          REQUEST_NOT_SATISFIED   = 0,    ! The request is being cancled for some reason
;  225          1127  1          !
;  226          1128  1          ! The following are mask definitions used for retrieving specified
;  227          1129  1          ! portions of a message via the $GETMSG system service.
;  228          1130  1          !
```

```
;  229          1131  1          MSG_TEXT        = 1,            ! Include message text
;  230          1132  1          MSG_ID          = 2,            ! Include message identifier
;  231          1133  1          MSG_SEVERITY    = 4,            ! Include severity indicator
;  232          1134  1          MSG_FACILITY    = 8,            ! Include message facility name
;  233          1135  1          !
;  234          1136  1          ! The following are indexes into the Exit Handler Control Block
;  235          1137  1          !
;  236          1138  1          XHNDLR_ADDRESS  = 1,            ! exit handler address
;  237          1139  1          XHNDLR_ARGCNT   = 2,            ! exit handler argument count
;  238          1140  1          XHNDLR_STSADDR  = 3,            ! system exit status address
;  239          1141  1          !
;  240          1142  1          TRUE            = 1,            ! Boolean value
;  241          1143  1          FALSE           = 0,            ! Boolean value
;  242          1144  1          !
;  243          1145  1          WAIT            = 1,            ! Enable wait for reply
;  244          1146  1          NO_WAIT         = 0,            ! Disable wait for reply
;  245          1147  1          !
;  246          1148  1          REPLY_FLAG      = MOUNT_EFN,    ! A local event flag #
;  247          1149  1          TIMER_FLAG      = TIMER_EFN,    ! A local event flag #
;  248          1150  1          TIMER_ID        = 999,          ! Timer identification #
;  249          1151  1          !
;  250          1152  1          EXPECT_REPLY    = 1,            ! Indicates that we expect a reply
;  251          1153  1          NO_REPLY        = 0;            ! Indecates that we don't desire a reply
;  252          1154  1
;  253          1155  1  GLOBAL LITERAL
;  254          1156  1          VOLINV_LIMIT    = 20;           ! VOLINV retry limit
;  255          1157  1
;  256          1158  1  !
;  257          1159  1  ! Define the static storage used by this module.  Note that the
;  258          1160  1  ! virtual pages on which this data resides must be USER writable.
;  259          1161  1  ! It is important that this data start on a page boundary, so that
;  260          1162  1  ! the $SETPRT call does not make pages writable that were not meant
;  261          1163  1  ! to be.
;  262          1164  1  !
;  263          1165  1
;  264          1166  1  PSECT GLOBAL = $USER_DATA$ (WRITE, NOEXECUTE, NOSHARE, ALIGN (9));
;  265          1167  1
;  266          1168  1  GLOBAL
;  267          1169  1          VA_START        : VECTOR [0] ALIGN (9),         ! Start of 'user data'
;  268          1170  1          VOLINV_COUNT    : LONG,                 ! VOLINV retry counter
;  269          1171  1          !
;  270          1172  1          ! Declare boolean variables.
;  271          1173  1          !
;  272          1174  1          REPLY_PENDING   : BOOLEAN VOLATILE,     ! Determines if response outstanding
;  273          1175  1          MOUNT_FAILED    : BOOLEAN VOLATILE,     ! Used in conjunction with MOUNT_STATUS
;  274          1176  1          OPERATOR_PRESENT: BOOLEAN VOLATILE,     ! Determines operator presence
;  275          1177  1          RETRY_COUNTER   : LONG VOLATILE,        ! Number of retries
;  276          1178  1          SS_FAIL_MODE    : BOOLEAN,              ! System service failure mode
;  277          1179  1          !
;  278          1180  1          ! Declare condition context variables.
;  279          1181  1          !
;  280          1182  1          MOUNT_STATUS    : BBLOCK[4] VOLATILE,   ! Primary condition
;  281          1183  1          PREVIOUS_STATUS : BBLOCK[4] VOLATILE,   ! Previous primary condition
;  282          1184  1          PREVIOUS_DEV_IDX: LONG VOLATILE,        ! Previous device index #
;  283          1185  1          OPERATOR_MASK   : LONG VOLATILE,        ! Mask of operators to receive requests
;  284          1186  1          REQUEST_ID      : LONG VOLATILE,        ! Operator request #
;  285          1187  1          !
```

```
;  286     1188  1        ! Declare exit handler control block.
;  287     1189  1        !
;  288     1190  1        EXIT_HNDLR_DSC  : EXIT_CTRL_BLK [0],    ! Define exit handler descriptor
;  289     1191  1        !
;  290     1192  1        ! Declare storge related to the operator reply message.
;  291     1193  1        !
;  292     1194  1        REPLY_CHANNEL   : LONG VOLATILE,        ! Channel of reply mailbox
;  293     1195  1        REPLY_IOSB      : BBLOCK [8] VOLATILE,  ! IOSB  for operator reply read
;  294     1196  1        REPLY_BUFFER    : BBLOCK [OPC$S_MS_OTEXT+8] VOLATILE,
;  295     1197  1        REPLY_DESC      : BBLOCK [DSC$K_S_BLN] VOLATILE
;  296     1198  1                          INITIAL (WORD (OPC$S_MS_OTEXT+8),
;  297     1199  1                                   BYTE (DSC$K_DTYPE_T),
;  298     1200  1                                   BYTE (DSC$K_CLASS_S),
;  299     1201  1                                   LONG (REPLY_BUFFER)
;  300     1202  1                                  ),
;  301     1203  1
;  302     1204  1        !
;  303     1205  1        ! Define the TPARSE control block.
;  304     1206  1        !
;  305     1207  1        TPARSE_BLOCK    : BBLOCK [TPA$K_LENGTH0]
;  306     1208  1                          INITIAL (TPA$R_COUNT0,TPA$M_ABBREV),
;  307     1209  1
;  308     1210  1        !
;  309     1211  1        ! Define the device name descriptor that is used as an implicit
;  310     1212  1        ! output to a TPARSE action routine.
;  311     1213  1        !
;  312     1214  1        DEVICE_DESC     : BBLOCK [DSC$K_S_BLN]  ! Descriptor for device name
;  313     1215  1                          INITIAL (WORD (MAX_DEV_LENGTH),
;  314     1216  1                                   BYTE (DSC$K_DTYPE_T),
;  315     1217  1                                   BYTE (DSC$K_CLASS_S),
;  316     1218  1                                   LONG (0)
;  317     1219  1                                  ),
;  318     1220  1        !
;  319     1221  1        ! Declare storage for operator message and its descriptor.
;  320     1222  1        !
;  321     1223  1        OP_MSG_BUF      : BBLOCK [OPC$S_MS_OTEXT] ! Buffer for op. request ms
;  322     1224  1                          INITIAL (BYTE (OPC$_RQ_RQST)),
;  323     1225  1
;  324     1226  1        OP_MSG_DESC     : BBLOCK [DSC$K_S_BLN]  ! Descriptor for op. request
;  325     1227  1                          INITIAL (WORD (OPC$S_MS_OTEXT),
;  326     1228  1                                   BYTE (DSC$K_DTYPE_T),
;  327     1229  1                                   BYTE (DSC$K_CLASS_S),
;  328     1230  1                                   LONG (OP_MSG_BUF)
;  329     1231  1                                  ),
;  330     1232  1
;  331     1233  1        CANCEL_MSG_BUF  : BBLOCK [OPC$K_HDR_SIZE]               ! Cancel message
;  332     1234  1                          INITIAL (BYTE (OPC$_X_CANCEL),        ! Set cancellation code
;  333     1235  1                                   BYTE (OPC$K_UNSPEC)          ! Set SCOPE unspecified
;  334     1236  1                                  ),
;  335     1237  1
;  336     1238  1        CANCEL_MSG_DESC : BBLOCK [DSC$K_S_BLN]  ! Cancel message descriptor
;  337     1239  1                          INITIAL (WORD (OPC$K_HDR_SIZE),
;  338     1240  1                                   BYTE (DSC$K_DTYPE_T),
;  339     1241  1                                   BYTE (DSC$K_CLASS_S),
;  340     1242  1                                   LONG (CANCEL_MSG_BUF)
;  341     1243  1                                  ),
;  342     1244  1        !
```

```
;   343          1245  1          ! Declare storage for FAO resultant string buffer and descriptor.
;   344          1246  1          !
;   345          1247  1          FAO_BUFFER      : BBLOCK [FAO_BUFFER_SIZE],
;   346          1248  1          FAO_RESULT_DESC : BBLOCK [DSC$K_S_BLN]
;   347          1249  1                            INITIAL (WORD (LOG$C_NAMLENGTH),
;   348          1250  1                                     BYTE (DSC$K_DTYPE_T),
;   349          1251  1                                     BYTE (DSC$K_CLASS_S),
;   350          1252  1                                     LONG (FAO_BUFFER)
;   351          1253  1                                    ),
;   352          1254  1          !
;   353          1255  1          ! Define the INADR vector used in the $SETPRT call.
;   354          1256  1          ! Note that VA_RANGE is on the next virtual page after VA_END.
;   355          1257  1          !
;   356          1258  1          VA_END          : VECTOR [0],           ! End of 'user data'
;   357          1259  1          VA_RANGE        : VECTOR [2] INITIAL (VA_START, VA_END) ALIGN (9);
;   358          1260  1
;   359          1261  1
;   360          1262  1 BIND
;   361          1263  1          !
;   362          1264  1          ! This is the delta-time value for all timers used.
;   363          1265  1          ! The time is a quadword value, is currently set for 5 seconds.
;   364          1266  1          !
;   365          1267  1          DELTA_TIME      = UPLIT (-5 * 10000000, -1);
```

```
;   367     1268  1 GLOBAL ROUTINE SYS$MOUNT  (ITEM_LIST) =
;   368     1269  1 !++
;   369     1270  1 ! Functional description:
;   370     1271  1 !
;   371     1272  1 !       This routine is the main entry point of the $MOUNT system service,
;   372     1273  1 !       and executes in the access mode of the caller.  Usually this will
;   373     1274  1 !       be USER mode.  This routine others defined in this module implement
;   374     1275  1 !       the logic for "operator assisted mount".  This code must execute
;   375     1276  1 !       in  USER mode, to allow users to CTRL\Y out of a mount request.
;   376     1277  1 !
;   377     1278  1 ! Input:
;   378     1279  1 !
;   379     1280  1 !       ITEM_LIST       : Address of a $GETJPI-like item list
;   380     1281  1 !
;   381     1282  1 ! Output:
;   382     1283  1 !
;   383     1284  1 !       None.
;   384     1285  1 !
;   385     1286  1 ! Implicit Inputs:
;   386     1287  1 !
;   387     1288  1 !       The MOUNT data base.
;   388     1289  1 !
;   389     1290  1 ! Implicit Outputs:
;   390     1291  1 !
;   391     1292  1 !       The MOUNT data base may be altered as
;   392     1293  1 !       the result of operator intervention.
;   393     1294  1 !
;   394     1295  1 !--
;   395     1296  1
;   396     1297  2 BEGIN                                           ! Start of OPERATOR_ASSIST
;   397     1298  2
;   398     1299  2 BUILTIN
;   399     1300  2         FP,
;   400     1301  2         AP,
;   401     1302  2         CALLG;
;   402     1303  2
;   403     1304  2 LOCAL
;   404     1305  2         STATUS;
;   405     1306  2
;   406     1307  2 EXTERNAL
;   407     1308  2         MOUNT_OPTIONS   : BITVECTOR VOLATILE;   ! Mount options bit vector
;   408     1309  2
;   409     1310  2 EXTERNAL ROUTINE
;   410     1311  2         $DALLOC_DEVS$U  : ADDRESSING_MODE (GENERAL),    ! Address of transfer vector
;   411     1312  2         $CHANGE_PROT$U  : ADDRESSING_MODE (GENERAL),    ! Address of the transfer vector
;   412     1313  2         SYS$VMOONT$U    : ADDRESSING_MODE (GENERAL);    ! Address of the transfer vector
;   413     1314  2
;   414     1315  2 !
;   415     1316  2 ! Enable a condition handler that will force the primary
;   416     1317  2 ! condition code facility-code to the MOUNT facility.
;   417     1318  2 !
;   418     1319  2 ENABLE INTERCEPT_SIGNAL;
;   419     1320  2
;   420     1321  2 !
;   421     1322  2 ! Set the page protection of this module's data to allow user
;   422     1323  2 ! mode read/write access.  This must be done here, since this
;   423     1324  2 ! image is INSTALLed as a protected shareable image, which has
```

```
;  424     1325  2 ! the effect of setting the protection to be USER read, EXEC write.
;  425     1326  2 ! Note that the data sits in a specail PSECT, to avoid changing
;  426     1327  2 ! the page protection on adjacent pages.
;  427     1328  2 !
;  428     1329  3 IF NOT (MOUNT_STATUS = $CHANGE_PROT$U ())
;  429     1330  2 THEN
;  430     1331  2     RETURN (.MOUNT_STATUS);
;  431     1332  2 !
;  432     1333  2 ! Initialize the necessary variables.  Most of the
;  433     1334  2 ! descriptors are not significantly changed, and do
;  434     1335  2 ! not have to be initialized at run time.
;  435     1336  2 !
;  436     1337  2 REPLY_PENDING = FALSE;
;  437     1338  2 MOUNT_FAILED = TRUE;
;  438     1339  2 OPERATOR_PRESENT = TRUE;
;  439     1340  2 PREVIOUS_STATUS = -1;
;  440     1341  2 PREVIOUS_DEV_IDX = -1;
;  441     1342  2 RETRY_COUNTER = 0;
;  442     1343  2 SS_FAIL_MODE = 0;
;  443     1344  2
;  444     1345  2 !
;  445     1346  2 ! Clear the system service failure exception flag, but save it's state.
;  446     1347  2 !
;  447     1348  2 STATUS = $SETSFM (ENBFLG=0);
;  448     1349  3 IF (.STATUS EQL SS$_WASSET)
;  449     1350  2 THEN
;  450     1351  2     SS_FAIL_MODE = 1;
;  451     1352  2
;  452     1353  2 !
;  453     1354  2 ! Set up the exit handler descriptor and declare the handler.
;  454     1355  2 !
;  455     1356  2 EXIT_HNDLR_DSC[XHNDLR_ADDRESS] = EXIT_HANDLER;
;  456     1357  2 EXIT_HNDLR_DSC[XHNDLR_ARGCNT]  = 1;
;  457     1358  2 EXIT_HNDLR_DSC[XHNDLR_STSADDR] = MOUNT_STATUS;
;  458     1359  2 $CANEXH (DESBLK = EXIT_HNDLR_DSC);
;  459     1360  2 $DCLEXH (DESBLK=EXIT_HNDLR_DSC);
;  460     1361  2
;  461     1362  2 !
;  462     1363  2 ! Perform the mount request.  If it fails, attempt to recover
;  463     1364  2 ! via some operator assistance.  If that is not possible, or the
;  464     1365  2 ! operator or user aborts the mount, die gracefully and return the
;  465     1366  2 ! status to the user.
;  466     1367  2 !
;  467     1368  2 MOUNT_STATUS = 0;
;  468     1369  2 VOLINV_COUNT = 0;
;  469     1370  2 WHILE NOT .MOUNT_STATUS DO
;  470     1371  3     BEGIN
;  471     1372  4     IF NOT (MOUNT_STATUS = CALLG (.AP, SYS$VMOUNT$U))
;  472     1373  3     THEN
;  473     1374  3         IF NOT .MOUNT_OPTIONS [OPT_ASSIST]
;  474     1375  3         THEN
;  475     1376  3
;  476     1377  4             BEGIN
;  477     1378  4             !
;  478     1379  4             ! If the mount operation failed for some reason other than VOLINV,
;  479     1380  4             ! exit loop with the error status. Else, do a limited number of
;  480     1381  4             ! retries. This automatic retry is implemented due to a race
```

```
;  481     1382  4                ! between mount and mount-verification. If mount is in progress
;  482     1383  4                ! and some event (e.g. cluster state transition) triggers mount-
;  483     1384  4                ! verification, mount-verification will clear the volume-valid
;  484     1385  4                ! bit in the UCB, causing mount to fail with a VOLINV error.
;  485     1386  4                !
;  486     1387  4                ! Not that the VOLINV error message will be suppressed (in module
;  487     1388  4                ! VMOUNT) unless the last retry fails with a VOLINV error.
;  488     1389  4                !
;  489     1390  5                IF (.MOUNT_STATUS AND STS$M_MSG_NO) NEQ (SS$_VOLINV AND STS$M_MSG_NO)
;  490     1391  4                THEN
;  491     1392  4                    EXITLOOP;
;  492     1393  4                VOLINV_COUNT = .VOLINV_COUNT + 1;
;  493     1394  4                IF .VOLINV_COUNT GEQ VOLINV_LIMIT
;  494     1395  4                THEN
;  495     1396  4                    EXITLOOP;
;  496     1397  4                END
;  497     1398  4
;  498     1399  3            ELSE
;  499     1400  3
;  500     1401  4                BEGIN
;  501     1402  4                !
;  502     1403  4                ! SELECT an error recovery handler based on the mount status value.
;  503     1404  4                ! Use only the message number and the facility code in the comparisons.
;  504     1405  4                !
;  505     1406  4                SELECTONEU (.MOUNT_STATUS AND STS$M_MSG_NO) OF
;  506     1407  4                    SET
;  507     1408  4                    [SS$_DEVALLOC    AND STS$M_MSG_NO]      : ALLOCFAIL_HNDLR ();
;  508     1409  4                    [SS$_MEDOFL      AND STS$M_MSG_NO]      : MEDOFL_HNDLR ();
;  509     1410  4                    [SS$_VOLINV      AND STS$M_MSG_NO]      : MEDOFL_HNDLR ();
;  510     1411  4                    [SS$_NODEVAVL    AND STS$M_MSG_NO]      : ALLOCFAIL_HNDLR ();
;  511     1412  4                    [SS$_NOSUCHDEV   AND STS$M_MSG_NO]      : ALLOCFAIL_HNDLR ();
;  512     1413  4                    [SS$_INCVOLLABEL AND STS$M_MSG_NO]      : WRONGVOL_HNDLR ();
;  513     1414  4                    [OTHERWISE]                             : EXITLOOP;
;  514     1415  4                    TES;
;  515     1416  4
;  516     1417  4                !
;  517     1418  4                ! Check for a reply to the operator request.  If it has
;  518     1419  4                ! arrived, it will be processed.  If it hasn't, wait for
;  519     1420  4                ! a few seconds and try again.
;  520     1421  4                !
;  521     1422  4                CHECK_FOR_REPLY ();
;  522     1423  3                END;
;  523     1424  2            END;
;  524     1425  2
;  525     1426  2        !
;  526     1427  2        ! Attempt to deallocate devices that are not mounted and
;  527     1428  2        ! were not previously allocated.
;  528     1429  2        !
;  529     1430  2        ! If the mount interlock on this device is still in effect, dequeue it now.
;  530     1431  2        !
;  531     1432  2        ! Cancel the any outstanding requests and the exit handler.
;  532     1433  2        ! Also restore the system service failure exception flag to its
;  533     1434  2        ! original state, and disable the condition handler.
;  534     1435  2        !
;  535     1436  2        $DALLOC_DEVS$U (0);                                 ! Attempt to deallocate devices
;  536     1437  2        CANCEL_REQUEST (REQUEST_SATISFIED);
;  537     1438  2        $SETSFM (ENBFLG = .SS_FAIL_MODE);
```

```
;  538          1439  2 .FP = 0;
;  539          1440  2 $CANEXH (DESBLK = EXIT_HNDLR_DSC);
;  540          1441  2
;  541          1442  3 RETURN (.MOUNT_STATUS)                    ! Return the status code
;  542          1443  3
;  543          1444  1 END;                                      ! End of SYS$MOUNT


                                        .TITLE  ASSIST
                                        .IDENT  \V04-001\

                                        .PSECT  $USER_DATA$,NOEXE,9

                                00000 VA_START::
                                                .BLKB   0
                                00000 VOLINV_COUNT::
                                                .BLKB   4
                                00004 REPLY_PENDING::
                                                .BLKB   4
                                00008 MOUNT_FAILED::
                                                .BLKB   4
                                0000C OPERATOR_PRESENT::
                                                .BLKB   4
                                00010 RETRY_COUNTER::
                                                .BLKB   4
                                00014 SS_FAIL_MODE::
                                                .BLKB   4
                                00018 MOUNT_STATUS::
                                                .BLKB   4
                                0001C PREVIOUS_STATUS::
                                                .BLKB   4
                                00020 PREVIOUS_DEV_IDX::
                                                .BLKB   4
                                00024 OPERATOR_MASK::
                                                .BLKB   4
                                00028 REQUEST_ID::
                                                .BLKB   4
                                0002C EXIT_HNDLR_DSC::
                                                .BLKB   16
                                0003C REPLY_CHANNEL::
                                                .BLKB   4
                                00040 REPLY_IOSB::
                                                .BLKB   8
                                00048 REPLY_BUFFER::
                                                .BLKB   136
                          0088  000D0 REPLY_DESC::
                                                .WORD   136                     ;
                            0E  000D2           .BYTE   14                      ;
                            01  000D3           .BYTE   1                       ;
                  00000000'     000D4           .ADDRESS REPLY_BUFFER           ;
00000002          00000008      000D8 TPARSE_BLOCK::
                                                .LONG   8, 2                    ;
                                000E0           .BLKB   28
                          003F  000FC DEVICE_DESC::
                                                .WORD   63                      ;
                            0E  000FE           .BYTE   14                      ;
                            01  000FF           .BYTE   1                       ;
```

```
                                00000000  00100              .LONG   0                                                       ;
                                      03  00104 OP_MSG_BUF::
                                                             .BYTE   3                                                       ;
                                          00105              .BLKB   127
                                    0080  00184 OP_MSG_DESC::
                                                             .WORD   128                                                     ;
                                      0E  00186              .BYTE   14                                                      ;
                                      01  00187              .BYTE   1                                                       ;
                                00000000' 00188              .ADDRESS OP_MSG_BUF                                             ;
                                      0E  0018C CANCEL_MSG_BUF::
                                                             .BYTE   14                                                      ;
                                      04  0018D              .BYTE   4                                                       ;
                                          0018E              .BLKB   24
                                          001A6              .BLKB   2
                                    001A  001A8 CANCEL_MSG_DESC::
                                                             .WORD   26                                                      ;
                                      0E  001AA              .BYTE   14                                                      ;
                                      01  001AB              .BYTE   1                                                       ;
                                00000000' 001AC              .ADDRESS CANCEL_MSG_BUF                                         ;
                                          001B0 FAO_BUFFER::
                                                             .BLKB   512
                                    0040  003B0 FAO_RESULT_DESC::
                                                             .WORD   64                                                      ;
                                      0E  003B2              .BYTE   14                                                      ;
                                      01  003B3              .BYTE   1                                                       ;
                                00000000' 003B4              .ADDRESS FAO_BUFFER                                             ;
                                          003B8 VA_END::     .BLKB   0
                                          003B8              .BLKB   72
                    00000000' 00000000' 00400 VA_RANGE::
                                                             .ADDRESS VA_START, VA_END                                       ;

                                                             .PSECT  $PLIT$,NOWRT,NOEXE,2

                    FFFFFFFF  FD050F80  00000 P.AAA:         .LONG   -50000000, -1                                           ;

                                                VOLINV_LIMIT==       20
                                                DELTA_TIME=          P.AAA
                                                             .EXTRN  MOUNT_OPTIONS, $DALLOC_DEVS$U
                                                             .EXTRN  $CHANGE_PROT$U, SYS$VMOUNT$U
                                                             .EXTRN  SYS$SETSFM, SYS$CANEXH
                                                             .EXTRN  SYS$DCLEXH

                                                             .PSECT  $CODE$,NOWRT,2

                                                      003C 00000         .ENTRY  SYS$MOUNT, Save R2,R3,R4,R5                 ; 1268
                                          55 00000000G  00   9E 00002    MOVAB   SYS$CANEXH, R5                              ;
                                          54 00000000G  00   9E 00009    MOVAB   SYS$SETSFM, R4                              ;
                                          53      0000' CF   9E 00010    MOVAB   MOUNT_STATUS, R3                            ;
                                          6D      0108  CF   DE 00015    MOVAL   13$, (FP)                                   ; 1297
                                00000000G 00            00   FB 0001A    CALLS   #0, $CHANGE_PROT$U                          ; 1329
                                          63            50   D0 00021    MOVL    R0, MOUNT_STATUS                            ;
                                          03            50   E8 00024    BLBS    R0, 1$                                      ;
                                                     00F3   31 00027    BRW     12$                                         ;
                                                  EC   A3   D4 0002A 1$: CLRL    REPLY_PENDING                               ; 1337
                                             F0   A3        01   D0 0002D    MOVL    #1, MOUNT_FAILED                        ; 1338
                                             F4   A3        01   D0 00031    MOVL    #1, OPERATOR_PRESENT                    ; 1339
                                             04   A3        01   CE 00035    MNEGL   #1, PREVIOUS_STATUS                     ; 1340
```

```
                08   A3                 01   CE 00039          MNEGL   #1, PREVIOUS_DEV_IDX                    ; 1341
                                   F8   A3   D4 0003D          CLRL    RETRY_COUNTER                           ; 1342
                                   FC   A3   D4 00040          CLRL    SS_FAIL_MODE                            ; 1343
                                        7E   D4 00043          CLRL    -(SP)                                   ; 1348
                     64                 01   FB 00045          CALLS   #1, SYS$SETSFM
                     09                 50   D1 00048          CMPL    STATUS, #9                              ; 1349
                                        04   12 0004B          BNEQ    2$
                FC   A3                 01   D0 0004D          MOVL    #1, SS_FAIL_MODE                        ; 1351
                18   A3            0000V CF   9E 00051 2$:     MOVAB   EXIT_HANDLER, EXIT_HNDLR_DSC+4          ; 1356
                1C   A3                 01   D0 00057          MOVL    #1, EXIT_HNDLR_DSC+8                    ; 1357
                20   A3                 63   9E 0005B          MOVAB   MOUNT_STATUS, EXIT_HNDLR_DSC+12         ; 1358
                                   14   A3   9F 0005F          PUSHAB  EXIT_HNDLR_DSC                          ; 1359
                     65                 01   FB 00062          CALLS   #1, SYS$CANEXH
                                   14   A3   9F 00065          PUSHAB  EXIT_HNDLR_DSC                          ; 1360
         00000000G   00                 01   FB 00068          CALLS   #1, SYS$DCLEXH
                                        63   D4 0006F          CLRL    MOUNT_STATUS                            ; 1368
                                   E8   A3   D4 00071          CLRL    VOLINV_COUNT                            ; 1369
                     2D                 63   E8 00074 3$:      BLBS    MOUNT_STATUS, 4$                        ; 1370
         00000000G   00                 6C   FA 00077          CALLG   (AP), SYS$VMOUNT$U                      ; 1372
                     63                 50   D0 0007E          MOVL    R0, MOUNT_STATUS
                     F0                 50   E8 00081          BLBS    R0, 3$
   1C      0000G     CF                 02   E0 00084          BBS     #2, MOUNT_OPTIONS+6, 5$                 ; 1374
   50                63 FFFF0007        8F   CB 0008A          BICL3   #-65529, MOUNT_STATUS, R0               ; 1390
      00000250       8F                 50   D1 00092          CMPL    R0, #592
                                        64   12 00099          BNEQ    11$
                                   E8   A3   D6 0009B          INCL    VOLINV_COUNT                            ; 1393
                     14            E8   A3   D1 0009E          CMPL    VOLINV_COUNT, #20                       ; 1394
                                        D0   19 000A2          BLSS    3$
                                        59   11 000A4 4$:      BRB     11$                                     ; 1396
   52                63 FFFF0007        8F   CB 000A6 5$:      BICL3   #-65529, MOUNT_STATUS, R2               ; 1406
      00000840       8F                 52   D1 000AE          CMPL    R2, #2112                               ; 1408
                                        2B   13 000B5          BEQL    8$
      000001A0       8F                 52   D1 000B7          CMPL    R2, #416                                ; 1409
                                        09   13 000BE          BEQL    6$
      00000250       8F                 52   D1 000C0          CMPL    R2, #592                                ; 1410
                                        07   12 000C7          BNEQ    7$
           0000V     CF                 00   FB 000C9 6$:      CALLS   #0, MEDOFL_HNDLR
                                        27   11 000CE          BRB     10$
      00009B0       8F                 52   D1 000D0 7$:      CMPL    R2, #2480                               ; 1411
                                        09   13 000D7          BEQL    8$
      00000908      8F                 52   D1 000D9          CMPL    R2, #2312                               ; 1412
                                        07   12 000E0          BNEQ    9$
           0000V     CF                 00   FB 000E2 8$:      CALLS   #0, ALLOCFAIL_HNDLR
                                        0E   11 000E7          BRB     10$
      00000108       8F                 52   D1 000E9 9$:      CMPL    R2, #264                                ; 1413
                                        0D   12 000F0          BNEQ    11$
           0000V     CF                 00   FB 000F2          CALLS   #0, WRONGVOL_HNDLR
           0000V     CF                 00   FB 000F7 10$:     CALLS   #0, CHECK_FOR_REPLY                     ; 1422
                                   FF75 31   11 000FC          BRW     3$                                      ; 1374
                                        7E   D4 000FF 11$:     CLRL    -(SP)                                   ; 1436
         00000000G   00                 01   FB 00101          CALLS   #1, $DALLOC_DEVS$U
                                        01   DD 00108          PUSHL   #1                                      ; 1437
           0000V     CF                 01   FB 0010A          CALLS   #1, CANCEL_REQUEST
                                   FC   A3   DD 0010F          PUSHL   SS_FAIL_MODE                            ; 1438
                     64                 01   FB 00112          CALLS   #1, SYS$SETSFM
                                        6D   D4 00115          CLRL    (FP)                                    ; 1439
                                   14   A3   9F 00117          PUSHAB  EXIT_HNDLR_DSC                          ; 1440
```

```
                          65              01  FB 0011A                   CALLS   #1, SYS$CANEXH                                  ;
                          50              63  D0 0011D 12$:              MOVL    MOUNT_STATUS, R0                                ; 1442
                                              04 00120                   RET                                                     ; 1444
                                            0000 00121 13$:              .WORD   Save nothing                                    ; 1297
                                          7E  D4 00123                   CLRL    -(SP)                                           ;
                                          5E  DD 00125                   PUSHL   SP                                              ;
                          7E      04      AC  7D 00127                   MOVQ    4(AP), -(SP)                                    ;
                    0000V CF              03  FB 0012B                   CALLS   #3, INTERCEPT_SIGNAL                            ;
                                              04 00130                   RET                                                     ;

; Routine Size:  305 bytes,    Routine Base:  $CODE$ + 0000
```

```
;   545     1445  1 ROUTINE INTERCEPT_SIGNAL (SIGNAL, MECHANISM) =
;   546     1446  1
;   547     1447  1 !++
;   548     1448  1 ! Functional Description:
;   549     1449  1 !
;   550     1450  1 !       This routine is a conditon handler whose sole
;   551     1451  1 !       reason for existence is to force the primary
;   552     1452  1 !       conditon code's facility-code to that of the
;   553     1453  1 !       MOUNT facility.
;   554     1454  1 !
;   555     1455  1 ! Input:
;   556     1456  1 !
;   557     1457  1 !       SIGNAL    = Address of the signal array
;   558     1458  1 !       MECHANISM = Address of the mechanism array
;   559     1459  1 !
;   560     1460  1 ! Output:
;   561     1461  1 !
;   562     1462  1 !       The condition facility code is equal to MOUN$_FACILITY
;   563     1463  1 !--
;   564     1464  1
;   565     1465  2 BEGIN                                           ! Start of INTERCEPT_SIGNAL
;   566     1466  2
;   567     1467  2 MAP
;   568     1468  2
;   569     1469  2         SIGNAL          : REF BBLOCK,           ! Signal array
;   570     1470  2         MECHANISM       : REF BBLOCK;           ! Mechanism array
;   571     1471  2
;   572     1472  2 EXTERNAL
;   573     1473  2
;   574     1474  2         MOUNT_OPTIONS   : BITVECTOR VOLATILE,   ! parser option flags
;   575     1475  2         USER_STATUS     : VECTOR;               ! Status return of some routines
;   576     1476  2
;   577     1477  2
;   578     1478  2 IF .SIGNAL[CHF$L_SIG_NAME] NEQ SS$_UNWIND
;   579     1479  2 THEN
;   580     1480  3     BEGIN
;   581     1481  3     !
;   582     1482  3     ! Make the facility code MOUN$_FCILITY.
;   583     1483  3     !
;   584     1484  3     IF .BBLOCK [SIGNAL[CHF$L_SIG_NAME], STS$V_FAC_NO] EQL 0
;   585     1485  3     OR .BBLOCK [SIGNAL[CHF$L_SIG_NAME], STS$V_FAC_NO] EQL INIT$_FACILITY
;   586     1486  3     THEN
;   587     1487  3         BBLOCK [SIGNAL[CHF$L_SIG_NAME], STS$V_FAC_NO] = MOUN$_FACILITY;
;   588     1488  3
;   589     1489  3     IF .BBLOCK [SIGNAL[CHF$L_SIG_NAME], STS$V_MSG_NO] EQL 0
;   590     1490  3     THEN
;   591     1491  3         BBLOCK [SIGNAL[CHF$L_SIG_NAME], STS$V_MSG_NO] = .USER_STATUS [0] ^ (-$BITPOSITION (STS$V_MSG_NO));
;   592     1492  3
;   593     1493  3     !
;   594     1494  3     ! If the caller requested it, print the message text associated with the message code.
;   595     1495  3     !
;   596     1496  3     IF .MOUNT_OPTIONS [OPT_MESSAGE]
;   597     1497  3     THEN
;   598     1498  4         BEGIN
;   599     1499  4         SIGNAL [CHF$L_SIG_ARGS] = .SIGNAL [CHF$L_SIG_ARGS] - 2;
;   600     1500  4         $PUTMSG (MSGVEC = SIGNAL [CHF$L_SIG_ARGS], ACTRTN=0, FACNAM=0);
;   601     1501  4         SIGNAL [CHF$L_SIG_ARGS] = .SIGNAL [CHF$L_SIG_ARGS] + 2;
```

```
;   602          1502  4          BBLOCK [SIGNAL [CHF$L_SIG_NAME], STS$V_INHIB_MSG] = 1;
;   603          1503  4          END;
;   604          1504  4
;   605          1505  4      !
;   606          1506  4      ! If the condition severity code is SEVERE or ERROR, then unwind the
;   607          1507  4      ! stack back to the caller of the frame that established this handler.
;   608          1508  4      ! Return the condition code in R0.
;   609          1509  4      !
;   610          1510  4      IF .BBLOCK [SIGNAL [CHF$L_SIG_NAME], STS$V_SEVERITY] EQL STS$K_SEVERE
;   611          1511  4      OR .BBLOCK [SIGNAL [CHF$L_SIG_NAME], STS$V_SEVERITY] EQL STS$K_ERROR
;   612          1512  4      THEN
;   613          1513  4          BEGIN
;   614          1514  4          MECHANISM [CHF$L_MCH_SAVR0] = .SIGNAL [CHF$L_SIG_NAME];
;   615          1515  4          $UNWIND ();
;   616          1516  4          END;
;   617          1517  4      END;
;   618          1518  4
;   619          1519  4  !
;   620          1520  4  ! Attempt to continue the operation.
;   621          1521  4  !
;   622          1522  4  RETURN (SS$_CONTINUE);
;   623          1523  4
;   624          1524  1  END;                                    ! End of INTERCEPT_SIGNAL


                                                                .EXTRN  USER_STATUS, SYS$PUTMSG
                                                                .EXTRN  SYS$UNWIND

                                                    000C 00000 INTERCEPT_SIGNAL:
                                                                .WORD   Save R2,R3                      ;  1445
                                                    52      04 AC DO 00002      MOVL    SIGNAL, R2      ;  1478
                                                    53      04 A2 9E 00006      MOVAB   4(R2), R3       ;
                                          00000920  8F         63 D1 0000A      CMPL    (R3), #2336     ;
                                                               6D 13 00011      BEQL    6$              ;
                                              0FFF  8F      02 A3 B3 00013      BITW    2(R3), #4095    ;  1484
                                                               0C 13 00019      BEQL    1$              ;
00000075    8F        02    A3                  0C            00 ED 0001B      CMPZV   #0, #12, 2(R3), #117 ;  1485
                                                               0A 12 00025      BNEQ    2$              ;
      02    A3              0C                  00 00000072   8F F0 00027 1$:    INSV    #114, #0, #12, 2(R3) ;  1487
                                              FFF8  8F         63 B3 00031 2$:    BITW    (R3), #65528    ;  1489
                                                               0C 12 00036      BNEQ    3$              ;
                          50      0000G       CF      FD       8F 78 00038      ASHL    #-3, USER_STATUS, R0 ;  1491
                    63    0D                  03               50 F0 0003F      INSV    R0, #3, #T3, (R3)
                          17      0000G       CF               03 E1 00044 3$:  BBC     #3, MOUNT_OPTIONS+6, 4$ ;  1496
                                              62               02 C2 0004A      SUBL2   #2, (R2)        ;  1499
                                                               7E 7C 0004D      CLRQ    -(SP)           ;  1500
                                                               7E D4 0004F      CLRL    -(SP)           ;
                                                               52 DD 00051      PUSHL   R2              ;
                                  00000000G   00               04 FB 00053      CALLS   #4, SYS$PUTMSG  ;
                                              62               02 C0 0005A      ADDL2   #2, (R2)        ;  1501
                                        03    A3               10 88 0005D      BISB2   #16, 3(R3)      ;  1502
                    04                63    03               00 ED 00061 4$:  CMPZV   #0, #3, (R3), #4 ;  1510
                                                               07 13 00066      BEQL    5$              ;
                    02                63          03         00 ED 00068      CMPZV   #0, #3, (R3), #2 ;  1511
                                                               11 12 0006D      BNEQ    6$              ;
                                                    50      08 AC DO 0006F 5$:  MOVL    MECHANISM, R0   ;  1514
```

```
                          0C   A0          63  D0 00073          MOVL    (R3), 12(R0)                                ;
                                           7E  7C 00077          CLRQ    -(SP)                                       ; 1515
                00000000G 00               02  FB 00079          CALLS   #2, SYS$UNWIND                              ;
                          50               01  D0 00080 6$:      MOVL    #1, R0                                      ; 1522
                                               04 00083          RET                                                 ; 1524

; Routine Size:  132 bytes,    Routine Base:  $CODE$ + 0131
```

```
;  626     1525  1 ROUTINE POST_READ_TO_MBX (MBX_CHANNEL) : NOVALUE =
;  627     1526  1
;  628     1527  1 !++
;  629     1528  1 ! Functional description:
;  630     1529  1 !
;  631     1530  1 !       This routine will post a read to the reply mailbox.
;  632     1531  1 !       Instead of waiting for the I/O to complete, request
;  633     1532  1 !       that an event flag be set when the I/O is finally done.
;  634     1533  1 !
;  635     1534  1 ! Input:
;  636     1535  1 !
;  637     1536  1 !       None.
;  638     1537  1 !
;  639     1538  1 ! Implicit Input:
;  640     1539  1 !
;  641     1540  1 !       REPLY_CHANNEL   : Channel # of channel to the reply mailbox.
;  642     1541  1 !
;  643     1542  1 ! Output:
;  644     1543  1 !
;  645     1544  1 !       None.
;  646     1545  1 !
;  647     1546  1 ! Implict output:
;  648     1547  1 !
;  649     1548  1 !       REPLY_IOSB      : Address of an I/O status block to receive the status of the I/O.
;  650     1549  1 !       REPLY_BUFFER    : Address of buffer to receive the operator's reply.
;  651     1550  1 !
;  652     1551  1 ! Side effects:
;  653     1552  1 !
;  654     1553  1 !       If the $QIO fails, the user will be notified
;  655     1554  1 !       of the failure and the mount will be aborted.
;  656     1555  1 !
;  657     1556  1 ! Routine value:
;  658     1557  1 !
;  659     1558  1 !       None.
;  660     1559  1 !--
;  661     1560  1
;  662     1561  2 BEGIN                                           ! Start of POST_READ_TO_MBX
;  663     1562  2
;  664     1563  2 LOCAL
;  665     1564  2         STATUS          : LONG;                 ! Hold status of $QIO call
;  666     1565  2
;  667   P 1566  3 IF NOT (STATUS = $QIO    (FUNC = IO$_READVBLK,
;  668   P 1567  3                           EFN  = REPLY_FLAG,
;  669   P 1568  3                           CHAN = .REPLY_CHANNEL,
;  670   P 1569  3                           IOSB = REPLY_IOSB,
;  671   P 1570  3                           P1   = REPLY_BUFFER,
;  672   P 1571  3                           P2   = ($BYTEOFFSET (OPC$S_MS_OTEXT) + $BYTEOFFSET (OPC$L_MS_TEXT))
;  673     1572  3                          ))
;  674     1573  2 THEN
;  675     1574  2     ABORT_MOUNT (MOUN$_MBXRDERR, 0, .STATUS);
;  676     1575  2
;  677     1576  1 END;                                            ! End of POST_READ_TO_MBX


                                                                    .EXTRN  SYS$QIO
```

```
                                                0000 00000 POST_READ_TO_MBX:
                                                                  .WORD   Save nothing                          ; 1525
                                            7E  7C 00002          CLRQ    -(SP)                                 ; 1572
                                            7E  7C 00004          CLRQ    -(SP)
                         7E         88      8F  9A 00006          MOVZBL  #136, -(SP)
                                 0000'      CF  9F 0000A          PUSHAB  REPLY_BUFFER
                                            7E  7C 0000E          CLRQ    -(SP)
                                 0000'      CF  9F 00010          PUSHAB  REPLY_IOSB
                                            31  DD 00014          PUSHL   #49
                                 0000'      CF  DD 00016          PUSHL   REPLY_CHANNEL
                                            1A  DD 0001A          PUSHL   #26
              00000000G  00                 0C  FB 0001C          CALLS   #12, SYS$QIO
                         11                 50  E8 00023          BLBS    STATUS, 1$
                                            50  DD 00026          PUSHL   STATUS                                ; 1574
                                            7E  D4 00028          CLRL    -(SP)
                              007281DC      8F  DD 0002A          PUSHL   #7504348
              00000000G  00                 03  FB 00030          CALLS   #3, LIB$STOP
                                                04 00037 1$:      RET                                           ; 1576

; Routine Size:  56 bytes,    Routine Base:  $CODE$ + 01B5
```

```
;  679     1577  1 ROUTINE INTERACTIVE_JOB =
;  680     1578  1
;  681     1579  1 !++
;  682     1580  1 ! Functional Description:
;  683     1581  1 !
;  684     1582  1 !       This routine will determine if the current process is an
;  685     1583  1 !       interactive process, and return that information to the
;  686     1584  1 !       caller.  By definition, a process is interactive if it
;  687     1585  1 !       has a terminal associated with it.
;  688     1586  1 !
;  689     1587  1 ! Input:
;  690     1588  1 !
;  691     1589  1 !       None.
;  692     1590  1 !
;  693     1591  1 ! Output:
;  694     1592  1 !
;  695     1593  1 !       None.
;  696     1594  1 !
;  697     1595  1 ! Routine Value:
;  698     1596  1 !
;  699     1597  1 !       1 if current process is an interactive process
;  700     1598  1 !       0 if current process is not an interactive process
;  701     1599  1 !--
;  702     1600  1
;  703     1601  2 BEGIN                                           ! Start of INTERACTIVE_JOB
;  704     1602  2
;  705     1603  2 LOCAL
;  706     1604  2         ITEM_LIST       : BBLOCK [16],          ! Item list for $GETJPI
;  707     1605  2         DEVICE_NAME     : BBLOCK [16],          ! Device name buffer
;  708     1606  2         NAME_LENGTH     : LONG;                 ! Cell for device name length
;  709     1607  2
;  710     1608  2 !
;  711     1609  2 ! Build the $GETJPI item list and get the terminal name.
;  712     1610  2 !
;  713     1611  2 NAME_LENGTH = 0;                                ! Zero the output cell
;  714     1612  2 ITEM_LIST [0, 0, 16, 0] = 16;                   ! Set buffer length
;  715     1613  2 ITEM_LIST [2, 0, 16, 0] = JPI$_TERMINAL;        ! Set item code
;  716     1614  2 ITEM_LIST [4, 0, 32, 0] = DEVICE_NAME;          ! Set buffer address
;  717     1615  2 ITEM_LIST [8, 0, 32, 0] = NAME_LENGTH;          ! Set result length address
;  718     1616  2 ITEM_LIST [12,0, 32, 0] = 0;                    ! Set list terminator
;  719     1617  2 $GETJPI (ITMLST = ITEM_LIST);
;  720     1618  2
;  721     1619  2 !
;  722     1620  2 ! If a terminal is associated with the process, the terminal name
;  723     1621  2 ! length should be nonzero.
;  724     1622  2 !
;  725     1623  2 IF .NAME_LENGTH NEQ 0
;  726     1624  2 THEN
;  727     1625  2     1                                           ! Return TRUE
;  728     1626  2 ELSE
;  729     1627  2     0                                           ! Return FALSE
;  730     1628  2
;  731     1629  1 END;                                           ! End of INTERACTIVE_JOB


                                                .EXTRN  SYS$GETJPI
```

```
                                        0000 00000 INTERACTIVE_JOB:
                                                           .WORD   Save nothing                                    ; 1577
                                5E              20  C2 00002           SUBL2   #32, SP                                 ;
                                                7E  D4 00005           CLRL    NAME_LENGTH                             ; 1611
                          14    AE 031D0010       8F  D0 00007           MOVL    #52232208, ITEM_LIST                    ; 1612
                          18    AE        04      AE  9E 0000F           MOVAB   DEVICE_NAME, ITEM_LIST+4                ; 1614
                          1C    AE                6E  9E 00014           MOVAB   NAME_LENGTH, ITEM_LIST+8                ; 1615
                                        20      AE  D4 00018           CLRL    ITEM_LIST+12                            ; 1616
                                                7E  7C 0001B           CLRQ    -(SP)                                   ; 1617
                                                7E  D4 0001D           CLRL    -(SP)                                   ;
                                        20      AE  9F 0001F           PUSHAB  ITEM_LIST                               ;
                                                7E  7C 00022           CLRQ    -(SP)                                   ;
                                                7E  D4 00024           CLRL    -(SP)                                   ;
                    00000000G   00              07  FB 00026           CALLS   #7, SYS$GETJPI                          ;
                                                6E  D5 0002D           TSTL    NAME_LENGTH                             ; 1623
                                                04  13 0002F           BEQL    1$                                      ;
                                50              01  D0 00031           MOVL    #1, R0                                  ;
                                                    04 00034           RET                                             ;
                                                50  D4 00035 1$:       CLRL    R0                                      ;
                                                    04 00037           RET                                             ; 1629

; Routine Size:  56 bytes,    Routine Base:  $CODE$ + 01ED

;  732          1630  1
```

```
;  734     1631  1 ROUTINE SUBMIT_REQUEST (MSG_DESC,REPLY_EXPECTED) : NOVALUE =
;  735     1632  1
;  736     1633  1 !++
;  737     1634  1 ! Functional Description:
;  738     1635  1 !
;  739     1636  1 !       This routine will send a request to all operators enabled
;  740     1637  1 !       to receive disk and tape messages.  All requests that are
;  741     1638  1 !       issued to the operator are echoed to the user.  Also, the
;  742     1639  1 !       request context is saved so that when the operator replies
;  743     1640  1 !       we can parse the reply in the context of the request.
;  744     1641  1 !
;  745     1642  1 ! Input:
;  746     1643  1 !
;  747     1644  1 !       MSG_DESC        = Address of a quadword string descriptor.
;  748     1645  1 !                         The string is the operator request.
;  749     1646  1 !
;  750     1647  1 !       REPLY_EXPECTED  = Boolean value.  If true then an operator
;  751     1648  1 !                         response is expected.
;  752     1649  1 !
;  753     1650  1 ! Output:
;  754     1651  1 !
;  755     1652  1 !       None.
;  756     1653  1 !
;  757     1654  1 ! Implicit Inputs:
;  758     1655  1 !
;  759     1656  1 !       MOUNT_STATUS    = status from current mount attempt
;  760     1657  1 !
;  761     1658  1 ! Implicit Outputs:
;  762     1659  1 !
;  763     1660  1 !       The request context is saved, the request is made.
;  764     1661  1 !--
;  765     1662  1
;  766     1663  2 BEGIN                                           ! Start of SUBMIT_REQUEST
;  767     1664  2
;  768     1665  2 MAP
;  769     1666  2
;  770     1667  2         MSG_DESC        : REF BBLOCK;           ! Address of request descriptor
;  771     1668  2
;  772     1669  2 EXTERNAL
;  773     1670  2
;  774     1671  2         DEVICE_INDEX    : LONG VOLATILE;        ! Index into device list
;  775     1672  2
;  776     1673  2 LITERAL
;  777     1674  2
;  778     1675  2         BLANK           = %ASCII ' ',           ! Fill character
;  779     1676  2         ZERO            = 0;                    ! Handy literal
;  780     1677  2
;  781     1678  2 LOCAL
;  782     1679  2
;  783     1680  2         STATUS          : LONG,                 ! Return status
;  784     1681  2         MBX_CHAN        : LONG;                 ! Operator reply mailbox channel
;  785     1682  2
;  786     1683  2
;  787     1684  2 !
;  788     1685  2 ! If no mailbox exists, create one.
;  789     1686  2 !
;  790     1687  2 IF .REPLY_CHANNEL EQL ZERO
```

```
;   791          1688  2 THEN
;   792          1689  3     IF NOT (STATUS = $CREMBX (CHAN = REPLY_CHANNEL, PROMSK = MAILBOX_PROTECTION))
;   793          1690  2     THEN
;   794          1691  2         ABORT_MOUNT (MOUN$_MBXCRERR, 0, .STATUS);
;   795          1692  2
;   796          1693  2 !
;   797          1694  2 ! Fill in the necessary fields in the request string.
;   798          1695  2 ! Copy the message string to the operator message buffer.
;   799          1696  2 !
;   800          1697  2 REQUEST_ID = .REQUEST_ID + 1;                    ! Inc reqeust #
;   801          1698  2 OP_MSG_BUF[OPC$L_MS_RQSTID]= .REQUEST_ID;        ! Set request #
;   802          1699  2 !
;   803          1700  2 CH$COPY (.MSG_DESC[DSC$W_LENGTH],                ! Source length
;   804          1701  2           .MSG_DESC[DSC$A_POINTER],              ! Source pointer
;   805          1702  2           BLANK,                                 ! Fill character
;   806          1703  2           OPC$S_MS_OTEXT-$BYTEOFFSET(OPC$L_MS_TEXT),! Destination length
;   807          1704  2           OP_MSG_BUF+$BYTEOFFSET(OPC$L_MS_TEXT)  ! Destination pointer
;   808          1705  2          );
;   809          1706  2 OP_MSG_DESC[DSC$W_LENGTH] = .MSG_DESC[DSC$W_LENGTH]+$BYTEOFFSET(OPC$L_MS_TEXT);
;   810          1707  2
;   811          1708  2 IF .REPLY_EXPECTED
;   812          1709  2 THEN
;   813          1710  3     BEGIN
;   814          1711  3     !
;   815          1712  3     ! An operator reply is expected.  Save the condition
;   816          1713  3     ! context and set up the reply mailbox channel.
;   817          1714  3     !
;   818          1715  3     PREVIOUS_STATUS  = .MOUNT_STATUS;
;   819          1716  3     PREVIOUS_DEV_IDX = .DEVICE_INDEX;
;   820          1717  3     REPLY_PENDING    =  TRUE;
;   821          1718  3     MBX_CHAN         = .REPLY_CHANNEL;
;   822          1719  3     END
;   823          1720  2 ELSE
;   824          1721  2     !
;   825          1722  2     ! An operator reply is not expected.
;   826          1723  2     ! Indicate this to OPCOM by specifying a mailbox channel of zero.
;   827          1724  2     !
;   828          1725  2     MBX_CHAN = ZERO;
;   829          1726  2
;   830          1727  2 !
;   831          1728  2 ! Set the operator target mask.
;   832          1729  2 !
;   833          1730  2 SET_TARGET_MASK ();
;   834          1731  2 OP_MSG_BUF[TARGET_FIELD] = .OPERATOR_MASK;
;   835          1732  2 !
;   836          1733  2 ! Send the request to the operator.
;   837          1734  2 !
;   838          1735  3 IF NOT (STATUS = $SNDOPR (MSGBUF=OP_MSG_DESC, CHAN=.MBX_CHAN))
;   839          1736  2 THEN
;   840          1737  2     ABORT_MOUNT (MOUN$_OPRSNDERR, 0, .STATUS);
;   841          1738  2 !
;   842          1739  2 ! Echo the operator request to the user.  If no operator is
;   843          1740  2 ! present, do not echo the request.  This interlock is necessary
;   844          1741  2 ! to prevent repeatedly issuing the request if no OPCOM process
;   845          1742  2 ! is present.
;   846          1743  2 !
;   847          1744  2 IF .OPERATOR_PRESENT
```

```
;  848     1745  2 THEN
;  849     1746  2     SIGNAL (MOUN$_OPRQST, 1, .MSG_DESC);
;  850     1747  2 !
;  851     1748  2 ! An alternate request status returned by $SNDOPR is SS$_NOPERATOR,
;  852     1749  2 ! which indicates that there is no operator present to service the
;  853     1750  2 ! request.  Taken in this context, it means that there is no OPCOM
;  854     1751  2 ! process present on the system.
;  855     1752  2 !
;  856     1753  2 IF .STATUS EQL OPC$_NOPERATOR
;  857     1754  2 THEN
;  858     1755  3     BEGIN
;  859     1756  3     REPLY_PENDING = FALSE;
;  860     1757  3     IF NOT INTERACTIVE_JOB ()
;  861     1758  3     THEN
;  862     1759  3         !
;  863     1760  3         ! Abort the mount, as no one can service the request.
;  864     1761  3         !
;  865     1762  3         ABORT_MOUNT (MOUN$_BATCHNOOPR)
;  866     1763  3     ELSE
;  867     1764  4         BEGIN
;  868     1765  4         !
;  869     1766  4         ! Inform the user that no operator is available to service
;  870     1767  4         ! the request.  The user then has three courses of action:
;  871     1768  4         !   - Abort the mount via CTRL-C
;  872     1769  4         !   - Wait for an operator to enable himself to service the request
;  873     1770  4         !   - Service the request himself.  (Hands-on environment)
;  874     1771  4         !
;  875     1772  4         ! Since the problem may go away in time, wait a short while after
;  876     1773  4         ! informing the user before continuing the MOUNT operation.
;  877     1774  4         !
;  878     1775  4         IF .OPERATOR_PRESENT
;  879     1776  4         THEN
;  880     1777  4             SIGNAL (MOUN$_NOOPR);
;  881     1778  4         OPERATOR_PRESENT = FALSE;
;  882     1779  5         IF NOT (STATUS = $SETIMR (EFN=TIMER_FLAG, REQIDT=TIMER_ID, DAYTIM=DELTA_TIME))
;  883     1780  4         THEN
;  884     1781  4             ABORT_MOUNT (.STATUS);
;  885     1782  4         $WAITFR (EFN = TIMER_FLAG);
;  886     1783  4         $CANTIM (REQIDT = TIMER_ID);
;  887     1784  4         $SETEF  (EFN = TIMER_FLAG);
;  888     1785  3         END;
;  889     1786  2     END;
;  890     1787  2 !
;  891     1788  2 ! If an operator reply is expected, then issue a read to the reply mailbox.
;  892     1789  2 !
;  893     1790  2 REPLY_IOSB = 0;
;  894     1791  2 IF .REPLY_PENDING
;  895     1792  2 THEN
;  896     1793  2     POST_READ_TO_MBX ();
;  897     1794  2
;  898     1795  1 END;                                   ! End of SUBMIT_REQUEST


                                                        .EXTRN  DEVICE_INDEX, SYS$CREMBX
                                                        .EXTRN  SYS$SNDOPR, SYS$SETIMR
                                                        .EXTRN  SYS$WAITFR, SYS$CANTIM
```

```
                                                                .EXTRN  SYS$SETEF

                                                        07FC 00000 SUBMIT_REQUEST:
                                                                .WORD   Save R2,R3,R4,R5,R6,R7,R8,R9,R10                ; 1631
                                                5A 00000000G    00  9E 00002       MOVAB   LIB$SIGNAL, R10
                                                59 00000000G    00  9E 00009       MOVAB   LIB$STOP, R9
                                                58      0000'   CF  9E 00010       MOVAB   REPLY_CHANNEL, R8
                                                                68  D5 00015       TSTL    REPLY_CHANNEL                   ; 1687
                                                                27  12 00017       BNEQ    1$
                                                                7E  7C 00019       CLRQ    -(SP)                           ; 1689
                                                7E      FF00    8F  3C 0001B       MOVZWL  #65280, -(SP)
                                                                7E  7C 00020       CLRQ    -(SP)
                                                                58  DD 00022       PUSHL   R8
                                                                7E  D4 00024       CLRL    -(SP)
                                        00000000G   00          07  FB 00026       CALLS   #7, SYS$CREMBX
                                                57              50  D0 0002D       MOVL    R0, STATUS
                                                0D              57  E8 00030       BLBS    STATUS, 1$
                                                                57  DD 00033       PUSHL   STATUS                          ; 1691
                                                                7E  D4 00035       CLRL    -(SP)
                                                    007281D4    8F  DD 00037       PUSHL   #7504340
                                                69              03  FB 0003D       CALLS   #3, LIB$STOP
                                                          EC    A8  D6 00040 1$:    INCL    REQUEST_ID                      ; 1697
                                            00CC        C8      EC  A8  D0 00043    MOVL    REQUEST_ID, OP_MSG_BUF+4        ; 1698
                                                56          04  AC  D0 00049       MOVL    MSG_DESC, R6                    ; 1700
0078    8F              20      04      B6                      66  2C 0004D       MOVC5   (R6), @4(R6), #32, #120, OP_MSG_BUF+8   ; 1704
                                                    00D0        C8  00055
                0148    C8              66                      08  A1 00058       ADDW3   #8, (R6), OP_MSG_DESC           ; 1706
                                                14          08  AC  E9 0005E       BLBC    REPLY_EXPECTED, 2$              ; 1708
                                        E0      A8          DC  A8  D0 00062       MOVL    MOUNT_STATUS, PREVIOUS_STATUS   ; 1715
                                        E4      A8      0000G   CF  D0 00067       MOVL    DEVICE_INDEX, PREVIOUS_DEV_IDX  ; 1716
                                        C8      A8              01  D0 0006D       MOVL    #1, REPLY_PENDING               ; 1717
                                                52              68  D0 00071       MOVL    REPLY_CHANNEL, MBX_CHAN         ; 1718
                                                                02  11 00074       BRB     3$                              ; 1708
                                                                52  D4 00076 2$:    CLRL    MBX_CHAN                        ; 1725
                                            0000V       CF      00  FB 00078 3$:    CALLS   #0, SET_TARGET_MASK             ; 1730
00C9    C8              18                  00          E8  A8  F0 0007D       INSV    OPERATOR_MASK, #0, #24, OP_MSG_BUF+1    ; 1731
                                                                52  DD 00085       PUSHL   MBX_CHAN                        ; 1735
                                                    0148        C8  9F 00087       PUSHAB  OP_MSG_DESC
                                        00000000G   00          02  FB 0008B       CALLS   #2, SYS$SNDOPR
                                                57              50  D0 00092       MOVL    R0, STATUS
                                                0D              57  E8 00095       BLBS    STATUS, 4$
                                                                57  DD 00098       PUSHL   STATUS                          ; 1737
                                                                7E  D4 0009A       CLRL    -(SP)
                                                    007281EC    8F  DD 0009C       PUSHL   #7504364
                                                69              03  FB 000A2       CALLS   #3, LIB$STOP
                                                0D          D0  A8  E9 000A5 4$:    BLBC    OPERATOR_PRESENT, 5$            ; 1744
                                                                56  DD 000A9       PUSHL   R6                              ; 1746
                                                                01  DD 000AB       PUSHL   #1
                                                    0072A023    8F  DD 000AD       PUSHL   #7512099
                                                6A              03  FB 000B3       CALLS   #3, LIB$SIGNAL
                                        00058061    8F          57  D1 000B6 5$:    CMPL    STATUS, #360545                 ; 1753
                                                                65  12 000BD       BNEQ    9$
                                                          C8    A8  D4 000BF       CLRL    REPLY_PENDING                   ; 1756
                                            FF01        CF      00  FB 000C2       CALLS   #0, INTERACTIVE_JOB             ; 1757
                                                0B              50  E8 000C7       BLBS    R0, 6$
                                                    007281FC    8F  DD 000CA       PUSHL   #7504380                        ; 1762
                                                69              01  FB 000D0       CALLS   #1, LIB$STOP
```

```
                                4F   11 000D3          BRB     9$                              ;
              09          D0    A8   E9 000D5 6$:      BLBC    OPERATOR_PRESENT, 7$            ; 1775
                   0072A03B     8F   DD 000D9          PUSHL   #7512123                        ; 1777
              6A                01   FB 000DF          CALLS   #1, LIB$SIGNAL                  ;
                          D0    A8   D4 000E2 7$:      CLRL    OPERATOR_PRESENT                ; 1778
              7E        03E7    8F   3C 000E5          MOVZWL  #999, -(SP)                     ; 1779
                                7E   D4 000EA          CLRL    -(SP)                           ;
                        0000'   CF   9F 000EC          PUSHAB  DELTA_TIME                      ;
                                19   DD 000F0          PUSHL   #25                             ;
   00000000G  00                04   FB 000F2          CALLS   #4, SYS$SETIMR                  ;
              57                50   D0 000F9          MOVL    R0, STATUS                      ;
              05                57   E8 000FC          BLBS    STATUS, 8$                      ;
                                57   DD 000FF          PUSHL   STATUS                          ; 1781
              69                01   FB 00101          CALLS   #1, LIB$STOP                    ;
                                19   DD 00104 8$:      PUSHL   #25                             ; 1782
   00000000G  00                01   FB 00106          CALLS   #1, SYS$WAITFR                  ;
                                7E   D4 0010D          CLRL    -(SP)                           ; 1783
              7E        03E7    8F   3C 0010F          MOVZWL  #999, -(SP)                     ;
   00000000G  00                02   FB 00114          CALLS   #2, SYS$CANTIM                  ;
                                19   DD 0011B          PUSHL   #25                             ; 1784
   00000000G  00                01   FB 0011D          CALLS   #1, SYS$SETEF                   ;
                          04    A8   D4 00124 9$:      CLRL    REPLY_IOSB                      ; 1790
              05          C8    A8   E9 00127          BLBC    REPLY_PENDING, 10$              ; 1791
        FE60  CF                00   FB 0012B          CALLS   #0, POST_READ_TO_MBX            ; 1793
                                     04 00130 10$:     RET                                     ; 1795

; Routine Size:  305 bytes,    Routine Base:  $CODE$ + 0225

;  899          1796  1
```

```
;  901     1797  1 ROUTINE SET_TARGET_MASK : NOVALUE =
;  902     1798  1
;  903     1799  1 !++
;  904     1800  1 ! Functional description:
;  905     1801  1 !
;  906     1802  1 !       Get the device characteristics and figure out which class
;  907     1803  1 !       of operator is to receive the request.  If the device is a
;  908     1804  1 !       tape, send the request to tape class operators.  If the
;  909     1805  1 !       device is a disk, send the request to disk class operators.
;  910     1806  1 !       If the device is neither tape or disk (ie. the user screwed
;  911     1807  1 !       up the device name on the command line) then send the
;  912     1808  1 !       request to both disk and tape class operators.  We remember
;  913     1809  1 !       the operator class mask in case we later have to cancel
;  914     1810  1 !       the request.
;  915     1811  1 !
;  916     1812  1 ! Input:
;  917     1813  1 !
;  918     1814  1 !       None.
;  919     1815  1 !
;  920     1816  1 ! Output:
;  921     1817  1 !
;  922     1818  1 !       None.
;  923     1819  1 !
;  924     1820  1 ! Implicit Input:
;  925     1821  1 !
;  926     1822  1 !       The MOUNT data base.  Note that:
;  927     1823  1 !       DEVICE_STRING[.DEVICE_INDEX*2] = the address of string descriptor
;  928     1824  1 !                                        of the device currently being mounted.
;  929     1825  1 !
;  930     1826  1 ! Implicit Output:
;  931     1827  1 !
;  932     1828  1 !       OPERATOR_MASK = mask of target operators.  Only
;  933     1829  1 !                       the low 3 bytes are significant.
;  934     1830  1 !
;  935     1831  1 !--
;  936     1832  1
;  937     1833  2 BEGIN                                           ! Start of SET_TARGET_MASK
;  938     1834  2
;  939     1835  2 EXTERNAL
;  940     1836  2         DEVICE_INDEX    : LONG VOLATILE,        ! Index into aforementioned vector
;  941     1837  2         PHYS_NAME       : VECTOR VOLATILE;      ! Vector of device descriptors
;  942     1838  2
;  943     1839  2 LOCAL
;  944     1840  2         DEVICE_CHAR     : BBLOCK [DIB$K_LENGTH],! Primary characteristics buffer
;  945     1841  2         DEVICE_CHAR2    : BBLOCK [DIB$K_LENGTH],! Secondary characteristics buffer
;  946     1842  2         DEVCHAR_DESC    : BBLOCK [DSC$K_S_BLN], ! Descriptor of primary char. buffer
;  947     1843  2         DEVCHAR_DESC2   : BBLOCK [DSC$K_S_BLN], ! Descriptor of secondary char. buffer
;  948     1844  2         STATUS          : LONG;
;  949     1845  2
;  950     1846  2 !
;  951     1847  2 ! Set up the device characteristic buffer descriptors.
;  952     1848  2 !
;  953     1849  2 DEVCHAR_DESC [DSC$W_LENGTH]  = DIB$K_LENGTH;
;  954     1850  2 DEVCHAR_DESC [DSC$B_DTYPE]   = DSC$K_DTYPE_T;
;  955     1851  2 DEVCHAR_DESC [DSC$B_CLASS]   = DSC$K_CLASS_S;
;  956     1852  2 DEVCHAR_DESC [DSC$A_POINTER] = DEVICE_CHAR;
;  957     1853  2 DEVCHAR_DESC2 [DSC$W_LENGTH]  = DIB$K_LENGTH;
```

```
;  958          1854  2 DEVCHAR_DESC2 [DSC$B_DTYPE]   = DSC$K_DTYPE_T;
;  959          1855  2 DEVCHAR_DESC2 [DSC$B_CLASS]   = DSC$K_CLASS_S;
;  960          1856  2 DEVCHAR_DESC2 [DSC$A_POINTER] = DEVICE_CHAR2;
;  961          1857  2 OPERATOR_MASK = 0;                          ! Zero the operator targt mask.
;  962          1858  2 !
;  963          1859  2 ! Get the device characteristics and perform some sanity checking.
;  964          1860  2 ! If this device is not mountable, don't worry, the operator will be
;  965          1861  2 ! notified and he'll think of something.
;  966          1862  2 !
;  967        P 1863  2 STATUS = $GETDEV (DEVNAM = PHYS_NAME [.DEVICE_INDEX *2],
;  968        P 1864  2                   PRIBUF=DEVCHAR_DESC,
;  969        P 1865  2                   SCDBUF = DEVCHAR_DESC2
;  970          1866  2                  );
;  971          1867  2 IF (NOT .DEVICE_CHAR[DEV$V_FOD]) OR  (.STATUS EQL SS$_NOSUCHDEV)
;  972          1868  2 THEN
;  973          1869  2     OPERATOR_MASK = (OPC$M_NM_DISKS OR OPC$M_NM_TAPES)  ! Send to tape and disk operators
;  974          1870  2 ELSE
;  975          1871  2     !
;  976          1872  2     ! Set the operator mask according to device class.  That is, tape
;  977          1873  2     ! requests go to TAPE operators, disk requests go to DISK operators.
;  978          1874  2     !
;  979          1875  2     OPERATOR_MASK = (IF .DEVICE_CHAR[DEV$V_SQD]
;  980          1876  2                      THEN
;  981          1877  2                          OPC$M_NM_TAPES
;  982          1878  2                      ELSE
;  983          1879  2                          OPC$M_NM_DISKS);
;  984          1880  1 END;                                        ! End of SET_TARGET_MASK

                                                .EXTRN  PHYS_NAME, SYS$GETDEV

                                0004 00000 SET_TARGET_MASK:
                                           .WORD   Save R2                                  ;  1797
                        52      0000'  CF  9E 00002        MOVAB   OPERATOR_MASK, R2
                        5E      FF0C   CE  9E 00007        MOVAB   -244(SP), SP
                    04  AE  010E0074     8F  D0 0000C        MOVL    #17694836, DEVCHAR_DESC          ;  1849
                    08  AE        8C     AD  9E 00014        MOVAB   DEVICE_CHAR, DEVCHAR_DESC+4      ;  1852
                            010E0074     8F  DD 00019        PUSHL   #17694836                        ;  1853
                    04  AE        10     AE  9E 0001F        MOVAB   DEVICE_CHAR2, DEVCHAR_DESC2+4    ;  1856
                                           62  D4 00024        CLRL    OPERATOR_MASK                    ;  1857
                                           5E  DD 00026        PUSHL   SP                               ;  1866
                                           7E  D4 00028        CLRL    -(SP)
                                10         AE  9F 0002A        PUSHAB  DEVCHAR_DESC
                                           7E  D4 0002D        CLRL    -(SP)
                50      0000G   CF             01  78 0002F        ASHL    #1, DEVICE_INDEX, R0
                                        0000GCF40  DF 00035        PUSHAL  PHYS_NAME[R0]
                    00000000G   00             05  FB 0003A        CALLS   #5, SYS$GETDEV
                09        8D    AD             06  E1 00041        BBC     #6, DEVICE_CHAR+1, 1$    ;  1867
                    00000908    8F             50  D1 00046        CMPL    STATUS, #2312
                                               04  12 0004D        BNEQ    2$
                                62             0C  D0 0004F 1$:     MOVL    #12, OPERATOR_MASK       ;  1869
                                               04  00052        RET
                05        8C    AD             05  E1 00053 2$:     BBC     #5, DEVICE_CHAR, 3$      ;  1875
                                50             04  D0 00058        MOVL    #4, R0
                                               03  11 0005B        BRB     4$
                                50             08  D0 0005D 3$:     MOVL    #8, R0                   ;
```

```
                        62          50  D0 00060 4$:    MOVL    R0, OPERATOR_MASK                       ;
                                        04 00063        RET                                             ; 1880

; Routine Size:  100 bytes,    Routine Base:  $CODE$ + 0356
```

```
;  986          1881  1 ROUTINE CANCEL_REQUEST (REQUEST_STATUS) : NOVALUE =
;  987          1882  1
;  988          1883  1 !++
;  989          1884  1 ! Functional Description:
;  990          1885  1 !
;  991          1886  1 !       This routine will cancel an outstanding operator request.
;  992          1887  1 !       The reply mailbox is deleted after the cancelation message
;  993          1888  1 !       is sent so there will be no stale messages lying around to
;  994          1889  1 !       confuse things later on.  The user is notified of the cancelation.
;  995          1890  1 !
;  996          1891  1 ! Input:
;  997          1892  1 !
;  998          1893  1 !       REQUEST_STATUS  : A boolean value that describes the status of the
;  999          1894  1 !                         operator request.  A value of 1 indicates the request
; 1000          1895  1 !                         has been successfully completed without  operator
; 1001          1896  1 !                         intervention, and the reason for the request no
; 1002          1897  1 !                         longer exists.  A value of 0 indicates that the
; 1003          1898  1 !                         request has not been satisfied, but is being canceled
; 1004          1899  1 !                         for some reason.
; 1005          1900  1 !
; 1006          1901  1 ! Output:
; 1007          1902  1 !
; 1008          1903  1 !       None.
; 1009          1904  1 !
; 1010          1905  1 ! Implicit Input:
; 1011          1906  1 !
; 1012          1907  1 !       REPLY_PENDING = TRUE if there is an outstanding operater request.
; 1013          1908  1 !
; 1014          1909  1 ! Implicit Outputs:
; 1015          1910  1 !
; 1016          1911  1 !       REPLY_PENDING = FALSE
; 1017          1912  1 !--
; 1018          1913  1
; 1019          1914  2 BEGIN                                           ! Start of CANCEL_REQUEST
; 1020          1915  2
; 1021          1916  2
; 1022          1917  2 IF .REPLY_PENDING
; 1023          1918  2 THEN
; 1024          1919  2     BEGIN
; 1025          1920  2     !
; 1026          1921  2     ! Send cancelation notice to operator
; 1027          1922  2     !
; 1028          1923  2     BBLOCK [CANCEL_MSG_BUF [OPC$L_RQ_OPTIONS], OPC$V_RQSTDONE] = .REQUEST_STATUS;
; 1029          1924  2     CANCEL_MSG_BUF[OPC$L_RQSTID] = .REQUEST_ID;
; 1030          1925  2     CANCEL_MSG_BUF[OPC$L_ATTNMASK1] = .OPERATOR_MASK;
; 1031          1926  2     $SNDOPR (MSGBUF=CANCEL_MSG_DESC, CHAN=.REPLY_CHANNEL);
; 1032          1927  2     !
; 1033          1928  2     ! Deassign the channel to the reply mailbox.  Since it
; 1034          1929  2     ! is a temporary mailbox, it will be deleted.
; 1035          1930  2     !
; 1036          1931  2     $DASSGN (CHAN = .REPLY_CHANNEL);
; 1037          1932  2     REPLY_CHANNEL = 0;
; 1038          1933  2     REPLY_PENDING = FALSE;
; 1039          1934  2     !
; 1040          1935  2     ! Clear the reply event flag.
; 1041          1936  2     !
; 1042          1937  3     $CLREF (EFN=REPLY_FLAG);
```

```
; 1043        1938 3      !
; 1044        1939 3      ! Notify the user of the cancelation.
; 1045        1940 3      !
; 1046        1941 4      IF .REQUEST_STATUS AND (NOT .MOUNT_FAILED)
; 1047        1942 3      THEN
; 1048        1943 3          SIGNAL (MOUN$_RQSTDON)
; 1049        1944 3      ELSE
; 1050        1945 3          SIGNAL (MOUN$_OPRQSTCAN);
; 1051        1946 2      END;
; 1052        1947 2
; 1053        1948 1 END;                                             ! End of CANCEL_REQUEST


                                                                .EXTRN  SYS$DASSGN, SYS$CLREF

                                          0004 00000 CANCEL_REQUEST:
                                                                .WORD   Save R2                                       ; 1881
                             52      0000'  CF  9E 00002        MOVAB   REPLY_CHANNEL, R2
                             55        C8   A2  E9 00007        BLBC    REPLY_PENDING, 3$                             ; 1917
  0156  C2         01        00        04   AC  F0 0000B        INSV    REQUEST_STATUS, #0, #1, CANCEL_MSG_BUF+6      ; 1923
                      0162   C2        EC   A2  D0 00013        MOVL    REQUEST_ID, CANCEL_MSG_BUF+18                 ; 1924
                      015A   C2        E8   A2  D0 00019        MOVL    OPERATOR_MASK, CANCEL_MSG_BUF+10              ; 1925
                                            62  DD 0001F        PUSHL   REPLY_CHANNEL                                 ; 1926
                                     016C   C2  9F 00021        PUSHAB  CANCEL_MSG_DESC
                  00000000G  00             02  FB 00025        CALLS   #2, SYS$SNDOPR
                                            62  DD 0002C        PUSHL   REPLY_CHANNEL                                 ; 1931
                  00000000G  00             01  FB 0002E        CALLS   #1, SYS$DASSGN
                                            62  D4 00035        CLRL    REPLY_CHANNEL                                 ; 1932
                                       C8   A2  D4 00037        CLRL    REPLY_PENDING                                 ; 1933
                                            1A  DD 0003A        PUSHL   #26                                           ; 1937
                  00000000G  00             01  FB 0003C        CALLS   #1, SYS$CLREF
                             0C        04   AC  E9 00043        BLBC    REQUEST_STATUS, 1$                            ; 1941
                             08        CC   A2  E8 00047        BLBS    MOUNT_FAILED, 1$
                               0072A073     8F  DD 0004B        PUSHL   #7512179                                      ; 1943
                                            06  11 00051        BRB     2$
                               0072A033     8F  DD 00053 1$:    PUSHL   #7512115                                      ; 1945
                  00000000G  00             01  FB 00059 2$:    CALLS   #1, LIB$SIGNAL
                                                04 00060 3$:    RET                                           ; 1948

; Routine Size:  97 bytes,    Routine Base:  $CODE$ + 03BA
```

```
;  1055     1949  1 ROUTINE CHECK_FOR_REPLY : NOVALUE =
;  1056     1950  1
;  1057     1951  1 !++
;  1058     1952  1 ! Functional Description:
;  1059     1953  1 !
;  1060     1954  1 !       This routine will check to see if the operator
;  1061     1955  1 !       replied to a request after DELTA_TIME expired.
;  1062     1956  1 !       If so, the response must be parsed and acted upon.
;  1063     1957  1 !       Note that this might require undoing a successful mount.
;  1064     1958  1 !       If the request is still outstanding and the mount
;  1065     1959  1 !       completed successfully, then cancel the request.
;  1066     1960  1 !
;  1067     1961  1 ! Input:
;  1068     1962  1 !
;  1069     1963  1 !       WAIT_ENABLED = TRUE if we are to wait, FALSE if not.
;  1070     1964  1 !
;  1071     1965  1 ! Output:
;  1072     1966  1 !
;  1073     1967  1 !       None.
;  1074     1968  1 !
;  1075     1969  1 ! Implicit Inputs:
;  1076     1970  1 !
;  1077     1971  1 !       REPLY_PENDING = 1 if there is an outstanding request.
;  1078     1972  1 !       REPLY_DESC = string descriptor of the operator's reply.
;  1079     1973  1 !       REPLY_BUFFER = buffer holding the operator's reply.
;  1080     1974  1 !       MOUNT data base.
;  1081     1975  1 !
;  1082     1976  1 ! Implicit Outputs:
;  1083     1977  1 !
;  1084     1978  1 !       The MOUNT data base may be updated as a result of the operator's reply.
;  1085     1979  1 !--
;  1086     1980  1
;  1087     1981  2 BEGIN                                           ! Start of CHECK_FOR_REPLY
;  1088     1982  2
;  1089     1983  2 LOCAL
;  1090     1984  2
;  1091     1985  2         EF_STATE        : LONG,                 ! State of Event flags
;  1092     1986  2         STATUS          : LONG;
;  1093     1987  2
;  1094     1988  2 IF NOT .MOUNT_FAILED
;  1095     1989  2 THEN
;  1096     1990  2     !
;  1097     1991  2     ! The mount succeeded.  Operator intervention is
;  1098     1992  2     ! no longer necessary, so cancel the request.
;  1099     1993  2     !
;  1100     1994  2     CANCEL_REQUEST (REQUEST_SATISFIED)
;  1101     1995  2 ELSE
;  1102     1996  2     BEGIN
;  1103     1997  2     !
;  1104     1998  2     ! The mount failed (again).
;  1105     1999  2     !
;  1106     2000  2     ! If a reply was pending, wait for either the timer to go off or
;  1107     2001  2     ! for the reply to arrive, whichever comes first.  If no reply is
;  1108     2002  2     ! pending, then simply wait for the timer to go off.  Cancel the
;  1109     2003  2     ! timer on the way out, just to be thourough.
;  1110     2004  2     !
;  1111     2005  3     ! If no operator is present, only attempt to read the reply mailbox
```

```
;  1112          2006  3      ! every tenth time through this routine.  This is necessaray to prevent
;  1113          2007  3      ! prevent mount from looping rapidly through this code.
;  1114          2008  3      !
;  1115          2009  3      IF NOT (STATUS = $SETIMR (EFN=TIMER_FLAG, REQIDT=TIMER_ID, DAYTIM=DELTA_TIME))
;  1116          2010  3      THEN
;  1117          2011  3          ABORT_MOUNT (.STATUS, 0, .MOUNT_STATUS);
;  1118          2012  3
;  1119          2013  3      IF (.REPLY_PENDING AND .OPERATOR_PRESENT)
;  1120          2014  3      OR ((NOT .OPERATOR_PRESENT) AND (.RETRY_COUNTER/10) GEQ 1)
;  1121          2015  3      THEN
;  1122          2016  4          BEGIN
;  1123          2017  4          RETRY_COUNTER = 0;
;  1124          2018  5          IF (.REPLY_IOSB [0,0,16,0] NEQ 0)
;  1125          2019  4          THEN
;  1126          2020  4              PARSE_REPLY ()
;  1127          2021  4          ELSE
;  1128          2022  4              $WAITFR (EFN = TIMER_FLAG);
;  1129          2023  4          END
;  1130          2024  3      ELSE
;  1131          2025  3          $WAITFR (EFN = TIMER_FLAG);
;  1132          2026  3
;  1133          2027  3      $CANTIM (REQIDT = TIMER_ID);                    ! Cancel the timer
;  1134          2028  3      $SETEF (EFN = TIMER_FLAG);                      ! Set timer flag
;  1135          2029  2      END;
;  1136          2030  2  RETRY_COUNTER = .RETRY_COUNTER + 1;
;  1137          2031  1  END;                                                ! End of CHECK_FOR_REPLY


                                0004 00000 CHECK_FOR_REPLY:
                                           .WORD   Save R2                                          ;  1949
                     52   0000'  CF  9E 00002      MOVAB   RETRY_COUNTER, R2
                     08     F8   A2  E8 00007      BLBS    MOUNT_FAILED, 1$                         ;  1988
                                 01  DD 0000B      PUSHL   #1                                       ;  1994
                8E   AF          01  FB 0000D      CALLS   #1, CANCEL_REQUEST
                                 65  11 00011      BRB     7$
                     7E   03E7   8F  3C 00013  1$:  MOVZWL  #999, -(SP)                             ;  2009
                                 7E  D4 00018      CLRL    -(SP)
                          0000'  CF  9F 0001A      PUSHAB  DELTA_TIME
                                 19  DD 0001E      PUSHL   #25
          00000000G              04  FB 00020      CALLS   #4, SYS$SETIMR
                                 0E  50 E8 00027   BLBS    STATUS, 2$
                           08    A2  DD 0002A      PUSHL   MOUNT_STATUS                             ;  2011
                                 7E  D4 0002D      CLRL    -(SP)
                                 50  DD 0002F      PUSHL   STATUS
          00000000G              03  FB 00031      CALLS   #3, LIB$STOP
                     04     F4   A2  E9 00038  2$:  BLBC    REPLY_PENDING, 3$                        ;  2013
                     0A     FC   A2  E8 0003C      BLBS    OPERATOR_PRESENT, 4$
                     14     FC   A2  E8 00040  3$:  BLBS    OPERATOR_PRESENT, 5$                     ;  2014
          50         62         0A  C7 00044      DIVL3   #10, RETRY_COUNTER, R0
                                 0E  15 00048      BLEQ    5$
                                 62  D4 0004A  4$:  CLRL    RETRY_COUNTER                            ;  2017
                           30    A2  B5 0004C      TSTW    REPLY_IOSB                               ;  2018
                                 07  13 0004F      BEQL    5$
                0000V    CF         00  FB 00051      CALLS   #0, PARSE_REPLY                      ;  2020
```

```
                                        09  11 00056              BRB     6$                                      ;
                                        19  DD 00058 5$:          PUSHL   #25                                     ; 2025
                    00000000G   00      01  FB 0005A              CALLS   #1, SYS$WAITFR                          ;
                                        7E  D4 00061 6$:          CLRL    -(SP)                                   ; 2027
                          7E    03E7    8F  3C 00063              MOVZWL  #999, -(SP)                             ;
                    00000000G   00      02  FB 00068              CALLS   #2, SYS$CANTIM                          ;
                                        19  DD 0006F              PUSHL   #25                                     ; 2028
                    00000000G   00      01  FB 00071              CALLS   #1, SYS$SETEF                           ;
                                        62  D6 00078 7$:          INCL    RETRY_COUNTER                           ; 2030
                                            04 0007A              RET                                             ; 2031

; Routine Size:  123 bytes,    Routine Base:  $CODE$ + 041B
```

```
;  1139          2032  1 ROUTINE ALLOCFAIL_HNDLR : NOVALUE =
;  1140          2033  1
;  1141          2034  1 !++
;  1142          2035  1 ! Functional Description:
;  1143          2036  1 !
;  1144          2037  1 !       This routine will attempt to recover from a device
;  1145          2038  1 !       allocation failure.  This means that the device
;  1146          2039  1 !       specified by the user (or operator) cannot be
;  1147          2040  1 !       successfully allocated.  Notify the operator and
;  1148          2041  1 !       try again.  Current allocation failures handled are:
;  1149          2042  1 !
;  1150          2043  1 !               SS$_DEVALLOC    - device allocated to another user
;  1151          2044  1 !               SS$_NODEVAVL    - no devices of generic type are available
;  1152          2045  1 !               SS$_NOSUCHDEV   - incorrect device specifier
;  1153          2046  1 !
;  1154          2047  1 ! Input:
;  1155          2048  1 !
;  1156          2049  1 !       None.
;  1157          2050  1 !
;  1158          2051  1 ! Output:
;  1159          2052  1 !
;  1160          2053  1 !       None.
;  1161          2054  1 !
;  1162          2055  1 ! Implicit Input:
;  1163          2056  1 !
;  1164          2057  1 !       MOUNT_STATUS  = status of current mount attempt
;  1165          2058  1 !       REPLY_PENDING = TRUE if an operator request is outstanding
;  1166          2059  1 !       The MOUNT data base.
;  1167          2060  1 !
;  1168          2061  1 ! Implict Output:
;  1169          2062  1 !
;  1170          2063  1 !       The MOUNT data base may be changed as
;  1171          2064  1 !       the result of operator intervention.
;  1172          2065  1 !--
;  1173          2066  1
;  1174          2067  2 BEGIN                                           ! Start of ALLOCFAIL_HNDLR
;  1175          2068  2
;  1176          2069  2 EXTERNAL
;  1177          2070  2
;  1178          2071  2         COMMENT_STRING  : BBLOCK,              ! User comment string
;  1179          2072  2         DEVICE_INDEX    : LONG VOLATILE,       ! Index into device name vector
;  1180          2073  2         PHYS_NAME       : VECTOR VOLATILE;     ! Physical device name descriptor
;  1181          2074  2 LITERAL
;  1182          2075  2
;  1183          2076  2         FAO_CTRL_SIZ    = FAO_BUFFER_SIZE/2;   ! Maximum size for FAO control string
;  1184          2077  2
;  1185          2078  2 LOCAL
;  1186          2079  2
;  1187          2080  2         ALLOCFAIL_FAO   : BBLOCK [DSC$K_S_BLN], ! FAO control string descriptor
;  1188          2081  2         FAO_CTRL_BUF    : BBLOCK [FAO_CTRL_SIZ],! Buffer for FAO control string
;  1189          2082  2         STATUS          : LONG;
;  1190          2083  2
;  1191          2084  2
;  1192          2085  2 !
;  1193          2086  2 ! If this condition is different from the one signaled previously,
;  1194          2087  2 ! cancel any outstanding requests before handling this condition.
;  1195          2088  2 ! Otherwise do nothing.
```

```
; 1196        2089  2 !
; 1197        2090  3 IF (.MOUNT_STATUS NEQ .PREVIOUS_STATUS)
; 1198        2091  3 OR (.DEVICE_INDEX NEQ .PREVIOUS_DEV_IDX)
; 1199        2092  2 THEN
; 1200        2093  3     BEGIN
; 1201        2094  3     CANCEL_REQUEST (REQUEST_NOT_SATISFIED);
; 1202        2095  3     OPERATOR_PRESENT = TRUE;                        ! Assume operator present
; 1203        2096  3     !
; 1204        2097  3     ! Set up the output descriptor and get the FAO control string.
; 1205        2098  3     !
; 1206        2099  3     ALLOCFAIL_FAO [DSC$W_LENGTH]  = FAO_CTRL_SIZ;
; 1207        2100  3     ALLOCFAIL_FAO [DSC$B_DTYPE]   = DSC$K_DTYPE_T;
; 1208        2101  3     ALLOCFAIL_FAO [DSC$B_CLASS]   = DSC$K_CLASS_S;
; 1209        2102  3     ALLOCFAIL_FAO [DSC$A_POINTER] = FAO_CTRL_BUF;
; 1210      P 2103  4     IF NOT (STATUS = $GETMSG    (MSGID  = MOUN$_NODEVAVL,
; 1211      P 2104  4                                  MSGLEN = ALLOCFAIL_FAO [DSC$W_LENGTH],
; 1212      P 2105  4                                  BUFADR = ALLOCFAIL_FAO,
; 1213      P 2106  4                                  FLAGS  = MSG_TEXT
; 1214        2107  4                                 ))
; 1215        2108  3     THEN
; 1216        2109  3         ABORT_MOUNT (.STATUS, 0, .MOUNT_STATUS);
; 1217        2110  3     !
; 1218        2111  3     ! Set up the output descriptor and format the operator request.
; 1219        2112  3     !
; 1220        2113  3     FAO_RESULT_DESC[DSC$A_POINTER] = FAO_BUFFER;
; 1221        2114  3     FAO_RESULT_DESC[DSC$W_LENGTH]  = FAO_BUFFER_SIZE;
; 1222      P 2115  3     $FAO (ALLOCFAIL_FAO,
; 1223      P 2116  3           FAO_RESULT_DESC [DSC$W_LENGTH],
; 1224      P 2117  3           FAO_RESULT_DESC,
; 1225      P 2118  3           PHYS_NAME [.DEVICE_INDEX*2],
; 1226      P 2119  3           COMMENT_STRING
; 1227        2120  3          );
; 1228        2121  3     !
; 1229        2122  3     ! Send the request to the operator.
; 1230        2123  3     !
; 1231        2124  3     SUBMIT_REQUEST (FAO_RESULT_DESC,EXPECT_REPLY);
; 1232        2125  2     END;
; 1233        2126  2
; 1234        2127  1 END;                                                ! End of ALLOCFAIL_HNDLR


                                                        .EXTRN  COMMENT_STRING, SYS$GETMSG
                                                        .EXTRN  SYS$FAO

                                   0004 00000 ALLOCFAIL_HNDLR:
                                                        .WORD   Save R2                               ; 2032
                   52      0000'   CF  9E 00002         MOVAB   FAO_RESULT_DESC, R2                   ;
                   5E      FEF8    CE  9E 00007         MOVAB   -264(SP), SP                          ;
          FC6C     C2      FC68    C2  D1 0000C         CMPL    MOUNT_STATUS, PREVIOUS_STATUS         ; 2090
                                   09  12 00013         BNEQ    1$                                    ;
          FC70     C2      0000G   CF  D1 00015         CMPL    DEVICE_INDEX, PREVIOUS_DEV_IDX        ; 2091
                                   71  13 0001C         BEQL    3$                                    ;
                                   7E  D4 0001E  1$:    CLRL    -(SP)                                 ; 2094
          FEFF     CF              01  FB 00020         CALLS   #1, CANCEL_REQUEST                    ;
          FC5C     C2              01  D0 00025         MOVL    #1, OPERATOR_PRESENT                  ; 2095
            F8     AD 010E0100     8F  D0 0002A         MOVL    #17694976, ALLOCFAIL_FAO              ; 2099
```

```
                        FC    AD              6E  9E 00032          MOVAB   FAO_CTRL_BUF, ALLOCFAIL_FAO+4          ; 2102
                              7E              01  7D 00036          MOVQ    #1, -(SP)                              ; 2107
                                        FB    AD  9F 00039          PUSHAB  ALLOCFAIL_FAO
                                        F8    AD  9F 0003C          PUSHAB  ALLOCFAIL_FAO
                                  0072A05B    8F  DD 0003F          PUSHL   #7512155
                  00000000G     00              05  FB 00045          CALLS   #5, SYS$GETMSG
                                0F              50  E8 0004C          BLBS    STATUS, 2$
                                          FC68  C2  DD 0004F          PUSHL   MOUNT_STATUS                           ; 2109
                                                7E  D4 00053          CLRL    -(SP)
                                                50  DD 00055          PUSHL   STATUS
                  00000000G     00              03  FB 00057          CALLS   #3, LIB$STOP
                          04    A2        FE00  C2  9E 0005E  2$:     MOVAB   FAO_BUFFER, FAO_RESULT_DESC+4          ; 2113
                                62        0200  8F  B0 00064          MOVW    #512, FAO_RESULT_DESC                  ; 2114
                                          0000G CF  9F 00069          PUSHAB  COMMENT_STRING                         ; 2120
                    50          0000G     CF      01  78 0006D          ASHL    #1, DEVICE_INDEX, R0
                                          0000GCF40  DF 00073          PUSHAL  PHYS_NAME[R0]
                                                52  DD 00078          PUSHL   R2
                                                52  DD 0007A          PUSHL   R2
                                                F8  AD  9F 0007C          PUSHAB  ALLOCFAIL_FAO
                  00000000G     00              05  FB 0007F          CALLS   #5, SYS$FAO
                                                01  DD 00086          PUSHL   #1                                     ; 2124
                                                52  DD 00088          PUSHL   R2
                              FD00    CF        02  FB 0008A          CALLS   #2, SUBMIT_REQUEST
                                                04  0008F  3$:     RET                                            ; 2127

; Routine Size:  144 bytes,    Routine Base:  $CODE$ + 0496
```

```
;  1236     2128  1 ROUTINE MEDOFL_HNDLR : NOVALUE =
;  1237     2129  1
;  1238     2130  1 !++
;  1239     2131  1 ! Functional Description:
;  1240     2132  1 !
;  1241     2133  1 !       This routine will attempt to recover from a medium
;  1242     2134  1 !       offline condition.  This usually means that the disk is
;  1243     2135  1 !       not spun up.  Notify the operator that the device
;  1244     2136  1 !       needs to be put online.
;  1245     2137  1 !
;  1246     2138  1 ! Input:
;  1247     2139  1 !
;  1248     2140  1 !       None.
;  1249     2141  1 !
;  1250     2142  1 ! Output:
;  1251     2143  1 !
;  1252     2144  1 !       None.
;  1253     2145  1 !
;  1254     2146  1 ! Implicit Input:
;  1255     2147  1 !
;  1256     2148  1 !       MOUNT_STATUS  = status of the current mount attempt
;  1257     2149  1 !       REPLY_PENDING = TRUE if an operator request is outstanding
;  1258     2150  1 !       The MOUNT data base.
;  1259     2151  1 !
;  1260     2152  1 ! Implict Output:
;  1261     2153  1 !
;  1262     2154  1 !       The MOUNT data base may be changed as
;  1263     2155  1 !       the result of operator intervention.
;  1264     2156  1 !--
;  1265     2157  1
;  1266     2158  2 BEGIN                                           ! Start of MEDOFL_HNDLR
;  1267     2159  2
;  1268     2160  2 EXTERNAL
;  1269     2161  2
;  1270     2162  2         COMMENT_STRING  : BBLOCK,               ! User comment string
;  1271     2163  2         LABEL_STRING    : VECTOR VOLATILE,      ! Vector of label descriptors
;  1272     2164  2         PHYS_NAME       : VECTOR VOLATILE,      ! Physical device name descriptor
;  1273     2165  2         DEVICE_INDEX    : LONG VOLATILE;        ! Index into DEVICE_STRING vector
;  1274     2166  2
;  1275     2167  2 LITERAL
;  1276     2168  2
;  1277     2169  2         FAO_CTRL_SIZ    = FAO_BUFFER_SIZE/2;    ! FAO control string size
;  1278     2170  2
;  1279     2171  2 LOCAL
;  1280     2172  2
;  1281     2173  2         MEDOFL_FAO      : BBLOCK [DSC$K_S_BLN],
;  1282     2174  2         MEDOFL_BUF      : BBLOCK [FAO_CTR[_SIZ],
;  1283     2175  2         VOLUME_FAO      : BBLOCK [DSC$K_S_BLN],
;  1284     2176  2         VOLUME_BUF      : BBLOCK [FAO_CTR[_SIZ],
;  1285     2177  2         VOLUME_DESC     : BBLOCK [DSC$K_S_BLN],
;  1286     2178  2         VOLUME_BUFFER   : BBLOCK [FAO_CTR[_SIZ],
;  1287     2179  2         STATUS          : LONG;
;  1288     2180  2
;  1289     2181  2
;  1290     2182  2
;  1291     2183  2 !
;  1292     2184  2 ! If this condition is different from the one signaled previously,
```

```
;  1293          2185  2 ! cancel any outstanding requests before handling this condition.
;  1294          2186  2 ! Note that if the previous condition was SS$_INCVOLLABEL, we do
;  1295          2187  2 ! not cancel the request and issue another one.  This is to give
;  1296          2188  2 ! the operator a chance to remove the incorrect volume from the drive
;  1297          2189  2 ! and to (hopefully) insert the correct volume.
;  1298          2190  2 !
;  1299          2191  2 IF  ((.MOUNT_STATUS AND STS$M_COND_ID) NEQ (SS$_INCVOLLABEL AND STS$M_COND_ID))
;  1300          2192  2 AND ((.PREVIOUS_STATUS AND STS$M_COND_ID) EQL (SS$_INCVOLLABEL AND STS$M_COND_ID))
;  1301          2193  2 AND (.DEVICE_INDEX  EQL .PREVIOUS_DEV_IDX)
;  1302          2194  2 THEN
;  1303          2195  2     BEGIN
;  1304          2196  2     PREVIOUS_STATUS = .MOUNT_STATUS;
;  1305          2197  2     END;
;  1306          2198  2
;  1307          2199  2 IF (.DEVICE_INDEX NEQ .PREVIOUS_DEV_IDX)
;  1308          2200  2 OR (.MOUNT_STATUS NEQ .PREVIOUS_STATUS)
;  1309          2201  2 THEN
;  1310          2202  2     BEGIN
;  1311          2203  2     CANCEL_REQUEST (REQUEST_NOT_SATISFIED);
;  1312          2204  2     OPERATOR_PRESENT = TRUE;                    ! Assume operator present
;  1313          2205  2     END;
;  1314          2206  2 !
;  1315          2207  2 ! If there is no outstanding request, then submit a request.
;  1316          2208  2 !
;  1317          2209  2 IF NOT .REPLY_PENDING
;  1318          2210  2 THEN
;  1319          2211  3     BEGIN
;  1320          2212  3     !
;  1321          2213  3     ! Set up the output descriptor and format the volume label string.
;  1322          2214  3     !
;  1323          2215  3     VOLUME_DESC [DSC$W_LENGTH]  = FAO_CTRL_SIZ;
;  1324          2216  3     VOLUME_DESC [DSC$B_DTYPE]   = DSC$K_DTYPE_T;
;  1325          2217  3     VOLUME_DESC [DSC$B_CLASS]   = DSC$K_CLASS_S;
;  1326          2218  3     VOLUME_DESC [DSC$A_POINTER] = VOLUME_BUFFER;
;  1327          2219  3     IF .LABEL_STRING[.DEVICE_INDEX*2] GTR 0
;  1328          2220  3     THEN
;  1329          2221  4         BEGIN
;  1330          2222  4         !
;  1331          2223  4         ! Set up the output descriptor and get the FAO control string.
;  1332          2224  4         !
;  1333          2225  4         VOLUME_FAO [DSC$W_LENGTH] = FAO_CTRL_SIZ;
;  1334          2226  4         VOLUME_FAO [DSC$B_DTYPE]  = DSC$K_DTYPE_T;
;  1335          2227  4         VOLUME_FAO [DSC$B_CLASS]  = DSC$K_CLASS_S;
;  1336          2228  4         VOLUME_FAO [DSC$A_POINTER] = VOLUME_BUF;
;  1337        P 2229  5         IF NOT (STATUS = $GETMSG (MSGID  = MOUN$_VOLNAME,
;  1338        P 2230  5                                 MSGLEN = VOLUME_FAO [DSC$W_LENGTH],
;  1339        P 2231  5                                 BUFADR = VOLUME_FAO,
;  1340        P 2232  5                                 FLAGS  = MSG_TEXT
;  1341          2233  5                                ))
;  1342          2234  4         THEN
;  1343          2235  4             ABORT_MOUNT (.STATUS, 0, .MOUNT_STATUS);
;  1344          2236  4         !
;  1345          2237  4         ! Format the volume label string.
;  1346          2238  4         !
;  1347        P 2239  4         $FAO    (VOLUME_FAO,
;  1348        P 2240  4                  VOLUME_DESC [DSC$W_LENGTH],
;  1349        P 2241  4                  VOLUME_DESC,
```

```
;  1350        P 2242  4                    LABEL_STRING [.DEVICE_INDEX*2]
;  1351          2243  4                   );
;  1352          2244  4            END
;  1353          2245  3        ELSE
;  1354          2246  3            VOLUME_DESC [DSC$W_LENGTH] = 0;          ! Set volume name null
;  1355          2247  3        !
;  1356          2248  3        ! Set up the desctiptors and get the FAO control string for the message.
;  1357          2249  3        !
;  1358          2250  3        MEDOFL_FAO [DSC$W_LENGTH]   = FAO_CTRL_SIZ;
;  1359          2251  3        MEDOFL_FAO [DSC$B_DTYPE]    = DSC$K_DTYPE_T;
;  1360          2252  3        MEDOFL_FAO [DSC$B_CLASS]    = DSC$K_CLASS_S;
;  1361          2253  3        MEDOFL_FAO [DSC$A_POINTER]  = MEDOFL_BUF;
;  1362        P 2254  3        $GETMSG     (MSGID  = MOUN$_MOUNTDEV,
;  1363        P 2255  3                    MSGLEN = MEDOFL_FAO [DSC$W_LENGTH],
;  1364        P 2256  3                    BUFADR = MEDOFL_FAO,
;  1365        P 2257  3                    FLAGS  = MSG_TEXT
;  1366          2258  3                   );
;  1367          2259  3        !
;  1368          2260  3        ! Set up the output descriptor and format the operator request.
;  1369          2261  3        !
;  1370          2262  3        FAO_RESULT_DESC [DSC$W_LENGTH]  = FAO_BUFFER_SIZE;
;  1371          2263  3        FAO_RESULT_DESC [DSC$A_POINTER] = FAO_BUFFER;
;  1372        P 2264  3        $FAO (MEDOFL_FAO,
;  1373        P 2265  3              FAO_RESULT_DESC[DSC$W_LENGTH],
;  1374        P 2266  3              FAO_RESULT_DESC,
;  1375        P 2267  3              VOLUME_DESC,
;  1376        P 2268  3              PHYS_NAME [.DEVICE_INDEX*2],
;  1377        P 2269  3              COMMENT_STRING
;  1378          2270  3             );
;  1379          2271  3        !
;  1380          2272  3        ! Send the request to the operator.
;  1381          2273  3        !
;  1382          2274  3        SUBMIT_REQUEST (FAO_RESULT_DESC,EXPECT_REPLY);
;  1383          2275  2        END;
;  1384          2276  2
;  1385          2277  1 END;                                          ! End of MEDOFL_HNDLR


                                                        .EXTRN  LABEL_STRING

                                        003C 00000 MEDOFL_HNDLR:
                                                        .WORD   Save R2,R3,R4,R5                        ; 2128
                        55 00000000G    00   9E 00002        MOVAB   SYS$FAO, R5
                        54 00000000G    00   9E 00009        MOVAB   SYS$GETMSG, R4
                        53     0000G    CF   9E 00010        MOVAB   DEVICE_INDEX, R3
                        52     0000'    CF   9E 00015        MOVAB   MOUNT_STATUS, R2
                        5E     FCE8     CE   9E 0001A        MOVAB   -792(SP), SP
                50      62 F0000007     8F   CB 0001F        BICL3   #-268435449, MOUNT_STATUS, R0       ; 2191
                   00000108     8F              50   D1 00027        CMPL    R0, #264
                                                1C   13 0002E        BEQL    1$
                50        04    A2 F0000007     8F   CB 00030        BICL3   #-268435449, PREVIOUS_STATUS, R0    ; 2192
                   00000108     8F              50   D1 00039        CMPL    R0, #264
                                                0A   12 00040        BNEQ    1$
                          08    A2              63   D1 00042        CMPL    DEVICE_INDEX, PREVIOUS_DEV_IDX  ; 2193
                                                04   12 00046        BNEQ    1$
                          04    A2              62   D0 00048        MOVL    MOUNT_STATUS, PREVIOUS_STATUS   ; 2196
```

```
                08   A2              63   D1 0004C 1$:    CMPL    DEVICE_INDEX, PREVIOUS_DEV_IDX          ; 2199
                                     06   12 00050        BNEQ    2$
                04   A2              62   D1 00052        CMPL    MOUNT_STATUS, PREVIOUS_STATUS           ; 2200
                                     0B   13 00056        BEQL    3$
                                     7E   D4 00058 2$:     CLRL    -(SP)                                   ; 2203
              FE35   CF              01   FB 0005A        CALLS   #1, CANCEL_REQUEST
                F4   A2              01   D0 0005F        MOVL    #1, OPERATOR_PRESENT                    ; 2204
                     01        EC    A2   E9 00063 3$:     BLBC    REPLY_PENDING, 4$                       ; 2209
                                     04   00067           RET
              0100   CE  010E0100    8F   D0 00068 4$:     MOVL    #17694976, VOLUME_DESC                  ; 2215
              0104   CE              6E   9E 00071        MOVAB   VOLUME_BUFFER, VOLUME_DESC+4            ; 2218
        50          63              01   78 00076        ASHL    #1, DEVICE_INDEX, R0                    ; 2219
                          0000GCF40   D5   0007A          TSTL    LABEL_STRING[R0]
                                     4E   15 0007F        BLEQ    6$
              FEF0   CD  010E0100    8F   D0 00081        MOVL    #17694976, VOLUME_FAO                   ; 2225
              FEF4   CD       0108   CE   9E 0008A        MOVAB   VOLUME_BUF, VOLUME_FAO+4                ; 2228
                     7E              01   7D 00091        MOVQ    #1, -(SP)                               ; 2233
                          FEF0   CD   9F 00094        PUSHAB  VOLUME_FAO
                          FEF0   CD   9F 00098        PUSHAB  VOLUME_FAO
                    0072A053     8F   DD 0009C        PUSHL   #7512147
                     64              05   FB 000A2        CALLS   #5, SYS$GETMSG
                     0D              50   E8 000A5        BLBS    STATUS, 5$
                                     62   DD 000A8        PUSHL   MOUNT_STATUS                            ; 2235
                                     7E   D4 000AA        CLRL    -(SP)
                                     50   DD 000AC        PUSHL   STATUS
    00000000G        00              03   FB 000AE        CALLS   #3, LIB$STOP
        50          63              01   78 000B5 5$:     ASHL    #1, DEVICE_INDEX, R0                    ; 2243
                          0000GCF40   DF   000B9          PUSHAL  LABEL_STRING[R0]
                          0104   CE   9F 000BE        PUSHAB  VOLUME_DESC
                          0108   CE   9F 000C2        PUSHAB  VOLUME_DESC
                          FEF0   CD   9F 000C6        PUSHAB  VOLUME_FAO
                     65              04   FB 000CA        CALLS   #4, SYS$FAO
                                     04   11 000CD        BRB     7$                                      ; 2219
                          0100   CE   B4 000CF 6$:     CLRW    VOLUME_DESC                             ; 2246
              F8   AD  010E0100    8F   D0 000D3 7$:     MOVL    #17694976, MEDOFL_FAO                   ; 2250
              FC   AD       FEF8   CD   9E 000DB        MOVAB   MEDOFL_BUF, MEDOFL_FAO+4                ; 2253
                     7E              01   7D 000E1        MOVQ    #1, -(SP)                               ; 2258
                               F8   AD   9F 000E4        PUSHAB  MEDOFL_FAO
                               F8   AD   9F 000E7        PUSHAB  MEDOFL_FAO
                         0072A04B     8F   DD 000EA        PUSHL   #7512139
                     64              05   FB 000F0        CALLS   #5, SYS$GETMSG
            0398   C2        0200     8F   B0 000F3        MOVW    #512, FAO_RESULT_DESC                   ; 2262
            039C   C2        0198     C2   9E 000FA        MOVAB   FAO_BUFFER, FAO_RESULT_DESC+4           ; 2263
                          0000G   CF   9F 00101        PUSHAB  COMMENT_STRING                          ; 2270
        50          63              01   78 00105        ASHL    #1, DEVICE_INDEX, R0
                          0000GCF40   DF   00109          PUSHAL  PHYS_NAME[R0]
                          0108   CE   9F 0010E        PUSHAB  VOLUME_DESC
                          0398   C2   9F 00112        PUSHAB  FAO_RESULT_DESC
                          0398   C2   9F 00116        PUSHAB  FAO_RESULT_DESC
                            F8   AD   9F 0011A        PUSHAB  MEDOFL_FAO
                     65              06   FB 0011D        CALLS   #6, SYS$FAO
                                     01   DD 00120        PUSHL   #1                                      ; 2274
                          0398   C2   9F 00122        PUSHAB  FAO_RESULT_DESC
              FBD4   CF              02   FB 00126        CALLS   #2, SUBMIT_REQUEST                      ;
                                     04   00012B          RET                                             ; 2277

; Routine Size:  300 bytes,    Routine Base:  $CODE$ + 0526
```

```
;  1387          2278  1 ROUTINE WRONGVOL_HNDLR : NOVALUE =
;  1388          2279  1
;  1389          2280  1 !++
;  1390          2281  1 ! Functional Description:
;  1391          2282  1 !
;  1392          2283  1 !       This routine will attempt to recover from an SS$_INCVOLLABEL
;  1393          2284  1 !       condition, which implies that the label of the volume presently
;  1394          2285  1 !       in the drive does not match the volume label specified by the user.
;  1395          2286  1 !
;  1396          2287  1 ! Input:
;  1397          2288  1 !
;  1398          2289  1 !       None.
;  1399          2290  1 !
;  1400          2291  1 ! Output:
;  1401          2292  1 !
;  1402          2293  1 !       None.
;  1403          2294  1 !
;  1404          2295  1 ! Implicit Input:
;  1405          2296  1 !
;  1406          2297  1 !       MOUNT_STATUS  = status of the current mount attempt
;  1407          2298  1 !       REPLY_PENDING = TRUE if an operator request is outstanding
;  1408          2299  1 !       The MOUNT data base.
;  1409          2300  1 !
;  1410          2301  1 ! Implict Output:
;  1411          2302  1 !
;  1412          2303  1 !       The MOUNT data base may be changed as
;  1413          2304  1 !       the result of operator intervention.
;  1414          2305  1 !--
;  1415          2306  1
;  1416          2307  2 BEGIN                                             ! Start of WRONGVOL_HNDLR
;  1417          2308  2
;  1418          2309  2 EXTERNAL
;  1419          2310  2
;  1420          2311  2         PHYS_NAME       : VECTOR VOLATILE,        ! Physical device name descriptor
;  1421          2312  2         DEVICE_INDEX    : LONG VOLATILE,          ! Index into DEVICE_STRING vector
;  1422          2313  2         LABEL_STRING    : VECTOR VOLATILE;        ! Vector of volume labels
;  1423          2314  2
;  1424          2315  2 LITERAL
;  1425          2316  2
;  1426          2317  2         FAO_CTRL_SIZ    = FAO_BUFFER_SIZE/2;      ! FAO control string size
;  1427          2318  2
;  1428          2319  2 LOCAL
;  1429          2320  2
;  1430          2321  2         WRONGVOL_FAO    : BBLOCK [DSC$K_S_BLN],
;  1431          2322  2         WRONGVOL_BUF    : BBLOCK [FAO_CTRL_SIZ],
;  1432          2323  2         STATUS          : LONG;
;  1433          2324  2
;  1434          2325  2
;  1435          2326  2 !
;  1436          2327  2 ! If this condition is different from the one signaled previously,
;  1437          2328  2 ! cancel any outstanding requests before handling this condition.
;  1438          2329  2 ! Otherwise do nothing.
;  1439          2330  2 !
;  1440          2331  3 IF (.MOUNT_STATUS NEQ .PREVIOUS_STATUS)
;  1441          2332  3 OR (.DEVICE_INDEX NEQ .PREVIOUS_DEV_IDX)
;  1442          2333  2 THEN
;  1443          2334  3     BEGIN
```

```
  3       CANCEL_REQUEST (REQUEST_NOT_SATISFIED);
  3       OPERATOR_PRESENT = TRUE;                      ! Assume operator present
  3       !
  3       ! Set up the output descriptor and get the FAO control string.
  3       !
  3       WRONGVOL_FAO [DSC$W_LENGTH]  = FAO_CTRL_SIZ;
  3       WRONGVOL_FAO [DSC$B_DTYPE]   = DSC$K_DTYPE_T;
  3       WRONGVOL_FAO [DSC$B_CLASS]   = DSC$K_CLASS_S;
  3       WRONGVOL_FAO [DSC$A_POINTER] = WRONGVOL_BUF;
P 4       IF NOT (STATUS = $GETMSG     (MSGID  = MOUN$_WRONGVOL,
P 4                                     MSGLEN = WRONGVOL_FAO [DSC$W_LENGTH],
P 4                                     BUFADR = WRONGVOL_FAO,
P 4                                     FLAGS  = MSG_TEXT
  4                                    ))
  3       THEN
  3           ABORT_MOUNT (.STATUS, 0, .MOUNT_STATUS);
  3       !
  3       ! Set up the output descriptor and format the operator request.
  3       !
  3       FAO_RESULT_DESC[DSC$A_POINTER] = FAO_BUFFER;
  3       FAO_RESULT_DESC[DSC$W_LENGTH]  = FAO_BUFFER_SIZE;
P 3       $FAO (WRONGVOL_FAO,
P 3             FAO_RESULT_DESC [DSC$W_LENGTH],
P 3             FAO_RESULT_DESC,
P 3             PHYS_NAME [.DEVICE_INDEX*2]
  3            );
  3       !
  3       ! Inform the user and all interested operators that the drive contains
  3       ! the wrong volume.  Note that this is just a message, and that no
  3       ! reply is expected.
  3       !
  3       SUBMIT_REQUEST (FAO_RESULT_DESC,NO_REPLY);
  3       !
  3       ! Call the medium offline handler to request that the correct volume
  3       ! be mounted in the specified drive.  The previous condition context
  3       ! must be reset manually, as SUBMIT_REQUEST will not do so when sending
  3       ! messages (instead of requests).
  3       !
  3       PREVIOUS_STATUS = .MOUNT_STATUS;
  3       MEDOFL_HNDLR ();
  2       END;
  2
  1 END;                                                ! End of WRONGVOL_HNDLR


                                   0004 00000 WRONGVOL_HNDLR:
                                                     .WORD    Save R2                                   ; 2278
               52      0000'  CF   9E 00002          MOVAB    FAO_RESULT_DESC, R2                       ;
               5E      FEF8   CE   9E 00007          MOVAB    -264(SP), SP                              ;
       FC6C    C2      FC68   C2   D1 0000C          CMPL     MOUNT_STATUS, PREVIOUS_STATUS             ; 2331
                              09   12 00013          BNEQ     1$                                        ;
       FC70    C2      0000G  CF   D1 00015          CMPL     DEVICE_INDEX, PREVIOUS_DEV_IDX            ; 2332
                              79   13 0001C          BEQL     3$                                        ;
                              7E   D4 0001E  1$:     CLRL     -(SP)                                     ; 2335
```

```
                    FD43   CF                  01   FB 00020                CALLS   #1, CANCEL_REQUEST                      ;
                    FC5C   C2                  01   D0 00025                MOVL    #1, OPERATOR_PRESENT                    ; 2336
                      F8   AD 010E0100         8F   D0 0002A                MOVL    #17694976, WRONGVOL_FAO                 ; 2340
                      FC   AD                  6E   9E 00032                MOVAB   WRONGVOL_BUF, WRONGVOL_FAO+4            ; 2343
                           7E                  01   7D 00036                MOVQ    #1, -(SP)                               ; 2348
                                         F8    AD   9F 00039                PUSHAB  WRONGVOL_FAO                            ;
                                         F8    AD   9F 0003C                PUSHAB  WRONGVOL_FAO                            ;
                                    0072A06B   8F   DD 0003F                PUSHL   #7512171                                ;
                00000000G           00         05   FB 00045                CALLS   #5, SYS$GETMSG                          ;
                                    0F         50   E8 0004C                BLBC    STATUS, 2$                              ;
                                         FC68  C2   DD 0004F                PUSHL   MOUNT_STATUS                            ; 2350
                                               7E   D4 00053                CLRL    -(SP)                                   ;
                                               50   DD 00055                PUSHL   STATUS                                  ;
                00000000G           00         03   FB 00057                CALLS   #3, LIB$STOP                            ;
                      04            A2   FE00  C2   9E 0005E 2$:            MOVAB   FAO_BUFFER, FAO_RESULT_DESC+4           ; 2354
                                    62   0200  8F   B0 00064                MOVW    #512, FAO_RESULT_DESC                   ; 2355
              50      0000G         CF         01   78 00069                ASHL    #1, DEVICE_INDEX, R0                    ; 2360
                                         0000GCF40   DF 0006F                PUSHAL  PHYS_NAME[R0]                           ;
                                               52   DD 00074                PUSHL   R2                                      ;
                                               52   DD 00076                PUSHL   R2                                      ;
                                         F8    AD   9F 00078                PUSHAB  WRONGVOL_FAO                            ;
                00000000G           00         04   FB 0007B                CALLS   #4, SYS$FAO                             ;
                                               7E   D4 00082                CLRL    -(SP)                                   ; 2366
                                               52   DD 00084                PUSHL   R2                                      ;
                    FB48   CF                  02   FB 00086                CALLS   #2, SUBMIT_REQUEST                      ;
                    FC6C   C2           FC68   C2   D0 0008B                MOVL    MOUNT_STATUS, PREVIOUS_STATUS           ; 2373
                    FE3D   CF                  00   FB 00092                CALLS   #0, MEDOFL_HNDLR                        ; 2374
                                               04   00097 3$:               RET                                             ; 2377

; Routine Size:  152 bytes,    Routine Base:  $CODE$ + 0652
```

```
;  1488          2378  1 ROUTINE PRINT_REPLY : NOVALUE =
;  1489          2379  1
;  1490          2380  1 !++
;  1491          2381  1 ! Funtional description:
;  1492          2382  1 !
;  1493          2383  1 !       This routine is a local utility routine used by PARSE_REPLY
;  1494          2384  1 !       to output the operator reply the user (SYS$OUTPUT).
;  1495          2385  1 !
;  1496          2386  1 ! Input:
;  1497          2387  1 !
;  1498          2388  1 !       None.
;  1499          2389  1 !
;  1500          2390  1 ! Outputs:
;  1501          2391  1 !
;  1502          2392  1 !       None.
;  1503          2393  1 !
;  1504          2394  1 ! Implicit input:
;  1505          2395  1 !
;  1506          2396  1 !       None.
;  1507          2397  1 !
;  1508          2398  1 ! Implicit output:
;  1509          2399  1 !
;  1510          2400  1 !       The operator reply, if any, is written to SYS$OUTPUT.
;  1511          2401  1 !
;  1512          2402  1 ! Side effects:
;  1513          2403  1 !
;  1514          2404  1 !       None.
;  1515          2405  1 !
;  1516          2406  1 ! Routine value:
;  1517          2407  1 !
;  1518          2408  1 !       None.
;  1519          2409  1 !
;  1520          2410  1 !--
;  1521          2411  1
;  1522          2412  2 BEGIN                                           ! Start of PRINT_REPLY
;  1523          2413  2
;  1524          2414  2 LOCAL
;  1525          2415  2         TEXT_DESC       : BBLOCK [DSC$K_S_BLN]; ! String descriptor
;  1526          2416  2
;  1527          2417  2 !
;  1528          2418  2 ! If the operator reply is greater than 8 bytes, then
;  1529          2419  2 ! it had some text to it.  If this is the case, inform
;  1530          2420  2 ! the user of the operator reply.  Note that the 8 bytes
;  1531          2421  2 ! of message overhead are not printed.  A temporary string
;  1532          2422  2 ! descriptor must be used so that $FAO will not replace
;  1533          2423  2 ! the any nonprinting ASCII characters with blanks.
;  1534          2424  2 !
;  1535          2425  2 IF .REPLY_IOSB[2,0,16,0] GTR $BYTEOFFSET (OPC$L_MS_TEXT)
;  1536          2426  2 THEN
;  1537          2427  3     BEGIN
;  1538          2428  3     TEXT_DESC [DSC$W_LENGTH]    = .REPLY_IOSB [2,0,16,0] - $BYTEOFFSET (OPC$L_MS_TEXT);
;  1539          2429  3     TEXT_DESC [DSC$B_DTYPE]     = DSC$K_DTYPE_T;
;  1540          2430  3     TEXT_DESC [DSC$B_CLASS]     = DSC$K_CLASS_S;
;  1541          2431  3     TEXT_DESC [DSC$A_POINTER]   = .REPLY_DESC [DSC$A_POINTER] + $BYTEOFFSET (OPC$L_MS_TEXT);
;  1542          2432  3     SIGNAL (MOUN$_OPREPLY, 1, TEXT_DESC);
;  1543          2433  3     END;
;  1544          2434  2
```

```
; 1545          2435  1 END;                                    ! End of PRINT_REPLY



                                                0000 00000 PRINT_REPLY:
                                                           .WORD   Save nothing                                    ; 2378
                                          5E            08  C2 00002          SUBL2   #8, SP                      ;
                                          08      0000' CF  B1 00005          CMPW    REPLY_IOSB+2, #8            ; 2425
                                                        24  1B 0000A          BLEQU   1$                          ;
                                    6E    0000' CF        08  A3 0000C          SUBW3   #8, REPLY_IOSB+2, TEXT_DESC ; 2428
                                      02  AE      010E    8F  B0 00012          MOVW    #270, TEXT_DESC+2           ; 2429
                                04    AE    0000' CF        08  C1 00018          ADDL3   #8, REPLY_DESC+4, TEXT_DESC+4 ; 2431
                                                        5E  DD 0001F          PUSHL   SP                          ; 2432
                                                        01  DD 00021          PUSHL   #1                          ;
                                              0072A02B  8F  DD 00023          PUSHL   #7512107                    ;
                                00000000G     00            03  FB 00029          CALLS   #3, LIB$SIGNAL          ;
                                                                04  00030 1$:      RET                             ; 2435

; Routine Size:  49 bytes,    Routine Base:  $CODE$ + 06EA
```

```
;  1547          2436  1 ROUTINE PARSE_REPLY : NOVALUE =
;  1548          2437  1
;  1549          2438  1 !++
;  1550          2439  1 ! Functional Description:
;  1551          2440  1 !
;  1552          2441  1 !       This routine will parse the operator reply in the context
;  1553          2442  1 !       of the conditon that spawned it, and then do the appropriate
;  1554          2443  1 !       thing, based on the operator's reply.
;  1555          2444  1 !
;  1556          2445  1 ! Input:
;  1557          2446  1 !
;  1558          2447  1 !       None.
;  1559          2448  1 !
;  1560          2449  1 ! Output:
;  1561          2450  1 !
;  1562          2451  1 !       None.
;  1563          2452  1 !
;  1564          2453  1 ! Implicit Inputs:
;  1565          2454  1 !
;  1566          2455  1 !       REPLY_DESC = string descriptor of the operator's reply.
;  1567          2456  1 !       REPLY_BUFFER = buffer holding the operator's reply.
;  1568          2457  1 !       MOUNT data base.
;  1569          2458  1 !
;  1570          2459  1 ! Implicit Outputs:
;  1571          2460  1 !
;  1572          2461  1 !       The MOUNT data base may be updated as a result of the operator's reply.
;  1573          2462  1 !--
;  1574          2463  1
;  1575          2464  2 BEGIN                                           ! Start of PARSE_REPLY
;  1576          2465  2
;  1577          2466  2 EXTERNAL ROUTINE
;  1578          2467  2
;  1579          2468  2         LIB$TPARSE      : ADDRESSING_MODE (GENERAL);    ! Used to parse operator reply
;  1580          2469  2
;  1581          2470  2 PSECT   GLOBAL = $GLOBAL$;
;  1582          2471  2 GLOBAL
;  1583          2472  2         NEWLINE         : DESCRIP (%CHAR (13,10));      ! Descriptor for newline string
;  1584          2473  2
;  1585          2474  2 BIND
;  1586          2475  2         !
;  1587          2476  2         ! Create the character translation table that will be used by the
;  1588          2477  2         ! CH$TRANSLATE function.  he table is st up so that all lower-cag
;  1589          2478  2         ! alphabetic characters are translated to their upper-case equivalent.
;  1590          2479  2         !
;  1591          2480  2         TRANS_TABLE     = CH$TRANSTABLE
;  1592          2481  2                           (0,1,2,3,4,5,6,7,8,9,10,11,12,13,14,15,16,17,18,19,
;  1593          2482  2                            20,21,22,23,24,25,26,27,28,29,30,31,32,33,34,35,36,
;  1594          2483  2                            37,38,39,40,41,42,43,44,45,46,47,48,49,50,51,52,53,
;  1595          2484  2                            54,55,56,57,58,59,60,61,62,63,64,65,66,67,68,69,70,
;  1596          2485  2                            71,72,73,74,75,76,77,78,79,80,81,82,83,84,85,86,87,
;  1597          2486  2                            88,89,90,91,92,93,94,95,96,65,66,67,68,69,70,71,72,
;  1598          2487  2                            73,74,75,76,77,78,79,80,81,82,83,84,85,86,87,88,89,
;  1599          2488  2                            90,123,124,125,126,127
;  1600          2489  2                           );
;  1601          2490  2
;  1602          2491  2 LOCAL
;  1603          2492  2
```

```
;  1604     2493  2          PTR             : LONG,                         ! Character pointer
;  1605     2494  2          STATUS          : LONG;
;  1606     2495  2
;  1607     2496  2      !
;  1608     2497  2      ! Check the status of the mailbox read.  If
;  1609     2498  2      ! not successful, then abort the mount.
;  1610     2499  2      !
;  1611     2500  2      IF NOT .REPLY_IOSB[0,0,16,0]
;  1612     2501  2      THEN
;  1613     2502  3          BEGIN
;  1614     2503  3          REPLY_PENDING = FALSE;
;  1615     2504  3          ABORT_MOUNT (MOUN$_MBXRDERR, 0, .REPLY_IOSB[0,0,16,0]);
;  1616     2505  2          END;
;  1617     2506  2
;  1618     2507  2      !
;  1619     2508  2      ! Decide what to do based on the type of operator reply.
;  1620     2509  2      ! The OPC$_xxxxx status codes are longer than a word, so
;  1621     2510  2      ! they are masked off to word size befor comparing them
;  1622     2511  2      ! to the reply status.
;  1623     2512  2      !
;  1624     2513  2      SELECTONEU .REPLY_BUFFER[OPC$W_MS_STATUS] OF
;  1625     2514  2          SET
;  1626     2515  3          [(OPC$_NOPERATOR AND %X'0FFFF')]    : BEGIN
;  1627     2516  3                                                !
;  1628     2517  3                                                ! No operator was enabled to receive the request.
;  1629     2518  3                                                !
;  1630     2519  3                                                REPLY_PENDING = FALSE;
;  1631     2520  3                                                IF NOT INTERACTIVE_JOB ()
;  1632     2521  3                                                THEN
;  1633     2522  3                                                    !
;  1634     2523  3                                                    ! Abort the mount, as no one is can service the request.
;  1635     2524  3                                                    !
;  1636     2525  3                                                ABORT_MOUNT (MOUN$_BATCHNOOPR)
;  1637     2526  3                                            ELSE
;  1638     2527  4                                                BEGIN
;  1639     2528  4                                                !
;  1640     2529  4                                                ! If this is the first time through this code for this conditi
;  1641     2530  4                                                ! for this device, then inform the user that no operator is en
;  1642     2531  4                                                ! to receive the request.
;  1643     2532  4                                                !
;  1644     2533  4                                                IF .OPERATOR_PRESENT
;  1645     2534  4                                                THEN
;  1646     2535  4                                                    SIGNAL (MOUN$_NOOPR);
;  1647     2536  4                                                OPERATOR_PRESENT = FALSE;
;  1648     2537  4                                                !
;  1649     2538  4                                                ! Re-issue the request, in the hope that an operator will even
;  1650     2539  4                                                ! be enabled to receive and service the request.
;  1651     2540  4                                                !
;  1652     2541  5                                                IF NOT (STATUS = $SNDOPR (MSGBUF=OP_MSG_DESC, CHAN=.REPLY_CHAN
;  1653     2542  4                                                THEN
;  1654     2543  4                                                    ABORT_MOUNT (MOUN$_OPRSNDERR, 0, .STATUS);
;  1655     2544  4                                                !
;  1656     2545  4                                                ! If the request was sent, re-issue a read to the reply mailbo
;  1657     2546  4                                                !
;  1658     2547  4                                                IF .STATUS NEQ OPC$_NOPERATOR
;  1659     2548  4                                                THEN
;  1660     2549  5                                                    BEGIN
```

```
                                                    POST_READ_TO_MBX ();
                                                    REPLY_PENDING = TRUE;
                                                    END;
                                                END;
                                            END;

        [(OPC$_RQSTCMPLTE AND %X'0FFFF')]   : BEGIN
                                            !
                                            ! The operator replied to our request.
                                            !
                                            PRINT_REPLY ();
                                            PREVIOUS_STATUS = -1;
                                            REPLY_PENDING = FALSE;
                                            OPERATOR_PRESENT = TRUE;
                                            !
                                            ! If there is no operator reply text, .nen return.
                                            !
                                            IF (.REPLY_IOSB [2,0,16,0] EQL $BYTEOFFSET (OPC$L_MS_TEXT))
                                            THEN
                                                RETURN;
                                            !
                                            ! Create a string descriptor for the operator reply text.
                                            !
                                            TPARSE_BLOCK [TPA$L_STRINGCNT] = .REPLY_IOSB [2,0,16,0] - $BYTEOFF
                                            TPARSE_BLOCK [TPA$L_STRINGPTR] = .REPLY_DESC [DSC$A_POINTER]+$BYTE
                                            !
                                            ! The reply text may contain a NEWLINE character.  If so, the inte
                                            ! is BEFORE  the NEWLINE character.  Note that the NEWLINE charact
                                            ! two characters, a carriage-return followed by a line-feed (<cr><
                                            !
                                            PTR   = CH$FIND_SUB    (.TPARSE_BLOCK [TPA$L_STRINGCNT],
                                                                    .TPARSE_BLOCK [TPA$L_STRINGPTR],
                                                                    .NEWLINE [DSC$W_LENGTH],
                                                                    .NEWLINE [DSC$A_POINTER]
                                                                   );
                                            !
                                            ! If a NEWLINE was found, set the string descriptor
                                            ! so that the text BEFORE the NEWLINE is parsed.
                                            !
                                            IF NOT CH$FAIL (.PTR)
                                            THEN
                                                TPARSE_BLOCK [TPA$L_STRINGCNT] = .PTR - .TPARSE_BLOCK [TPA$L_S
                                            !
                                            ! If there is no text before the NEWLINE, then there is no operato
                                            !
                                            IF .TPARSE_BLOCK [TPA$L_STRINGCNT] EQL 0
                                            THEN
                                                RETURN;
                                            !
                                            ! Convert the reply to upper case, so TPARSE will work correctly.
                                            !
                                            CH$TRANSLATE  (TRANS_TABLE,
                                                          .TPARSE_BLOCK [TPA$L_STRINGCNT],
                                                          .TPARSE_BLOCK [TPA$L_STRINGPTR],
                                                          0,
                                                          .TPARSE_BLOCK [TPA$L_STRINGCNT],
                                                          .TPARSE_BLOCK [TPA$L_STRINGPTR]
```

```
                                                 );
                                         !
                                         ! Parse the operator response and perform whatever action is neces
                                         !
                                         IF NOT (STATUS = LIB$TPARSE (TPARSE_BLOCK, STATE_TABLE, KEY_TABLE)
                                         THEN
                                             ABORT_MOUNT (.STATUS, 0, .MOUNT_STATUS);
                                         END;

        [(OPC$_RQSTPEND AND %X'OFFFF')]      : BEGIN
                                         !
                                         ! The operator did a REPLY/PENDING.  The orginal
                                         ! request is still active, so issue another read
                                         ! to the reply mailbox.
                                         !
                                         PRINT_REPLY ();
                                         OPERATOR_PRESENT = TRUE;
                                         POST_READ_TO_MBX ();
                                         END;

        [(OPC$_RQSTABORT AND %X'OFFFF')]     : BEGIN
                                         !
                                         ! The operator has aborted the mount request.
                                         !
                                         PRINT_REPLY ();
                                         REPLY_PENDING = FALSE;
                                         OPERATOR_PRESENT = TRUE;
                                         ABORT_MOUNT (MOUN$_OPRABORT);
                                         END;

        [(OPC$_RQSTCAN  AND %X'OFFFF'),
         (OPC$_RQSTDONE AND %X'OFFFF')]      : BEGIN
                                         !
                                         ! The user has canceled the requst, and
                                         ! the operator is acknowledging it.
                                         !
                                         PREVIOUS_STATUS = -1;
                                         REPLY_PENDING = FALSE;
                                         OPERATOR_PRESENT = TRUE;
                                         END;

        [(OPC$_BLANKTAPE AND %X'OFFFF'),
         (OPC$_INITAPE   AND %X'OFFFF')]     : BEGIN
                                         !
                                         ! These messages may be sent by mistake.  Notify
                                         ! the interested parties, and let MOUNT try again.
                                         !
                                         PREVIOUS_STATUS = -1;
                                         REPLY_PENDING = FALSE;
                                         OPERATOR_PRESENT = TRUE;
                                         INVALID_COMMAND ();
                                         END;

        [OTHERWISE]                          : BEGIN
                                         !
                                         ! This is an unknown response type.
                                         ! Abort the mount and print the bad message.
```

```
; 1775           2664  3                              !
; 1776           2665  3                              REPLY_PENDING = FALSE;
; 1777           2666  3                              OPERATOR_PRESENT = TRUE;
; 1778         P 2667  3                              ABORT_MOUNT    (MOUN$_BADREPLY,                 ! Error code
; 1779         P 2668  3                                              5,                               ! FAO count
; 1780         P 2669  3                                              .REPLY_BUFFER[OPC$B_MS_TYPE],    ! Message type
; 1781         P 2670  3                                              .REPLY_BUFFER[OPC$W_MS_STATUS],  ! Message status
; 1782         P 2671  3                                              .REPLY_BUFFER[OPC$L_MS_RPLYID],  ! Message Ident
; 1783         P 2672  3                                              .REPLY_DESC[DSC$W_LENGTH]  - $BYTEOFFSET (OPC$L_MS_
; 1784         P 2673  3                                              .REPLY_DESC[DSC$A_POINTER] + $BYTEOFFSET (OPC$L_MS_
; 1785           2674  3                                              );
; 1786           2675  2                              END;
; 1787           2676  2      TES;
; 1788           2677  2
; 1789           2678  1 END;                                         ! End of PARSE_REPLY



                                                              .PSECT  $PLIT$,NOWRT,NOEXE,2

                                       0A 0D  00008 P.AAB:   .ASCII  <13><10>                                    ;
                                              0000A          .BLKB   2
0E 0D 0C 0B 0A 09 08 07 06 05 04 03 02 01 00  0000C P.AAC:   .BYTE   0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, - ;
1D 1C 1B 1A 19 18 17 16 15 14 13 12 11 10 0F  0001B                  13, 14, 15, 16, 17, 18, 19, 20, 21, 22, -   ;
2C 2B 2A 29 28 27 26 25 24 23 22 21 20 1F 1E  0002A                  23, 24, 25, 26, 27, 28, 29, 30, 31, 32, -   ;
3B 3A 39 38 37 36 35 34 33 32 31 30 2F 2E 2D  00039                  33, 34, 35, 36, 37, 38, 39, 40, 41, 42, -   ;
4A 49 48 47 46 45 44 43 42 41 40 3F 3E 3D 3C  00048                  43, 44, 45, 46, 47, 48, 49, 50, 51, 52, -   ;
59 58 57 56 55 54 53 52 51 50 4F 4E 4D 4C 4B  00057                  53, 54, 55, 56, 57, 58, 59, 60, 61, 62, -   ;
48 47 46 45 44 43 42 41 60 5F 5E 5D 5C 5B 5A  00066                  63, 64, 65, 66, 67, 68, 69, 70, 71, 72, -   ;
57 56 55 54 53 52 51 50 4F 4E 4D 4C 4B 4A 49  00075                  73, 74, 75, 76, 77, 78, 79, 80, 81, 82, -   ;
                     7F 7E 7D 7C 7B 5A 59 58  00084                  83, 84, 85, 86, 87, 88, 89, 90, 91, 92, -   ;
                                                                     93, 94, 95, 96, 65, 66, 67, 68, 69, 70, -   ;
                                                                     71, 72, 73, 74, 75, 76, 77, 78, 79, 80, -   ;
                                                                     81, 82, 83, 84, 85, 86, 87, 88, 89, 90, -   ;
                                                                     123, 124, 125, 126, 127                     ;

                                                              .PSECT  $GLOBAL$,NOEXE,2

                                     0002  00000 NEWLINE::
                                                             .WORD   2                                           ;
                                       0E  00002             .BYTE   14                                          ;
                                       01  00003             .BYTE   1                                           ;
                                00000000'  00004             .ADDRESS P.AAB                                      ;

                                                    TRANS_TABLE=        P.AAC
                                                             .EXTRN  LIB$TPARSE

                                                             .PSECT  $CODE$,NOWRT,2

                                     03FC  00000 PARSE_REPLY:
                                                             .WORD   Save R2,R3,R4,R5,R6,R7,R8,R9                ; 2436
                  59          CA  AF  9E  00002              MOVAB   PRINT_REPLY, R9                             ;
                  58   00000000G  00  9E  00006              MOVAB   LIB$STOP, R8                                ;
                  57       0000'  CF  9E  0000D              MOVAB   REPLY_PENDING, R7                           ;
                  11          3C  A7  E8  00012              BLBS    REPLY_IOSB, 1$                              ; 2500
                                  67  D4  00016              CLRL    REPLY_PENDING                               ; 2503
                  7E          3C  A7  3C  00018              MOVZWL  REPLY_IOSB, -(SP)                           ; 2504
```

```
                                 7E  D4 0001C          CLRL    -(SP)
                      007281DC   8F  DD 0001E          PUSHL   #7504348
                             68  03  FB 00024          CALLS   #3, LIB$STOP
                             52      46  A7  3C 00027 1$:     MOVZWL  REPLY_BUFFER+2, R2                      ;2513
                           8061  8F      52  B1 0002B          CMPW    R2, #32865                              ;2515
                                         5A  12 00030          BNEQ    5$
                                         67  D4 00032          CLRL    REPLY_PENDING                           ;2519
                           FB03  C9      00  FB 00034          CALLS   #0, INTERACTIVE_JOB                     ;2520
                                 09      50  E8 00039          BLBS    R0, 2$
                                      007281FC  8F  DD 0003C          PUSHL   #7504380                        ;2525
                                            00FD  31 00042          BRW     14$
                                    0D      08  A7  E9 00045 2$:     BLBC    OPERATOR_PRESENT, 3$            ;2533
                                      0072A03B  8F  DD 00049          PUSHL   #7512123                        ;2535
                        00000000G     00      01  FB 0004F          CALLS   #1, LIB$SIGNAL
                                            08  A7  D4 00056 3$:     CLRL    OPERATOR_PRESENT                ;2536
                                            38  A7  DD 00059          PUSHL   REPLY_CHANNEL                   ;2541
                                          0180  C7  9F 0005C          PUSHAB  OP_MSG_DESC
                        00000000G     00          02  FB 00060          CALLS   #2, SYS$SNDOPR
                                      56          50  D0 00067          MOVL    R0, STATUS
                                      0D          56  E8 0006A          BLBS    STATUS, 4$
                                                  56  DD 0006D          PUSHL   STATUS                          ;2543
                                                  7E  D4 0006F          CLRL    -(SP)
                                         007281EC   8F  DD 00071          PUSHL   #7504364
                                             68      03  FB 00077          CALLS   #3, LIB$STOP
                                   00058061  8F      56  D1 0007A 4$:     CMPL    STATUS, #360545         ;2547
                                                     60  13 00081          BEQL    9$
                                       FACB  C9      00  FB 00083          CALLS   #0, POST_READ_TO_MBX    ;2550
                                             67      01  D0 00088          MOVL    #1, REPLY_PENDING       ;2551
                                                         04 0008B          RET                             ;2513
                                       8029  8F      52  B1 0008C 5$:     CMPW    R2, #32809              ;2556
                                                     03  13 00091          BEQL    6$
                                                   0082  31 00093          BRW     12$
                                             69      00  FB 00096 6$:     CALLS   #0, PRINT_REPLY         ;2560
                                                 18  A7      01  CE 00099          MNEGL   #1, PREVIOUS_STATUS     ;2561
                                                             67  D4 0009D          CLRL    REPLY_PENDING   ;2562
                                                 08  A7      01  D0 0009F          MOVL    #1, OPERATOR_PRESENT    ;2563
                                                     08  3E  A7  B1 000A3          CMPW    REPLY_IOSB+2, #8        ;2567
                                                         3A  13 000A7          BEQL    9$
                                                 00DC  C7  3E  A7  3C 000A9          MOVZWL  REPLY_IOSB+2, TPARSE_BLOCK+8    ;2573
                                                 00DC  C7      08  C2 000AF          SUBL2   #8, TPARSE_BLOCK+8
                                       00E0      C7  00D0      C7  08  C1 000B4          ADDL3   #8, REPLY_DESC+4, TPARSE_BLOCK+12   ;2574
                                                         54  0000'  CF  3C 000BC          MOVZWL  NEWLINE, R4     ;2582
                        00E0    D7       00DC      C7  0000'  DF      54  39 000C1          MATCHC  R4, @NEWLINE+4, TPARSE_BLOCK+8, -   ;2583
                                                                                                  @TPARSE_BLOCK+12
                                                             03  13 000CC          BEQL    7$
                                                         53  54  D0 000CE          MOVL    R4, R3
                                                         53  54  C2 000D1 7$:     SUBL2   R4, R3
                                                             08  13 000D4          BEQL    8$              ;2589
                                                 00DC  C7    53  C3 000D6          SUBL3   TPARSE_BLOCK+12, PTR, TPARSE_BLOCK+8    ;2591
                                                         50  00DC  C7  D0 000DE 8$:     MOVL    TPARSE_BLOCK+8, R0      ;2595
                                                             01  12 000E3 9$:     BNEQ    10$
                                                                 04 000E5          RET
                        0000'   CF      00       00E0      D7      50  2E 000E6 10$:     MOVTC   R0, @TPARSE_BLOCK+12, #0, TRANS_TABLE, R0, -    ;2606
                                                 00E0      D7      50      000EF                          @TPARSE_BLOCK+12
                                                             0000V CF  9F 000F3          PUSHAB  KEY_TABLE       ;2611
                                                             0000V CF  9F 000F7          PUSHAB  STATE_TABLE
                                                             00D4  C7  9F 000FB          PUSHAB  TPARSE_BLOCK
```

```
                00000000G  00              03  FB  000FF          CALLS   #3, LIB$TPARSE                                  ;
                           56              50  D0  00106          MOVL    R0, STATUS                                      ;
                           01              56  E9  00109          BLBC    STATUS, 11$                                     ;
                                           04  00010C           RET                                                     ;
                                     14    A7  DD  0010D  11$:    PUSHL   MOUNT_STATUS                                    ; 2613
                                           7E  D4  00110          CLRL    -(SP)                                           ;
                                           56  DD  00112          PUSHL   STATUS                                          ;
                           68              03  FB  00114          CALLS   #3, LIB$STOP                                    ;
                                           04  00117           RET                                                     ; 2513
                        8021   8F          52  B1  00118  12$:    CMPW    R2, #32801                                      ; 2616
                                           0D  12  0011D          BNEQ    13$                                             ;
                           69              00  FB  0011F          CALLS   #0, PRINT_REPLY                                 ; 2622
                          08   A7          01  D0  00122          MOVL    #1, OPERATOR_PRESENT                            ; 2623
                        FACB   C9          00  FB  00126          CALLS   #0, POST_READ_TO_MBX                            ; 2624
                                           04  0012B           RET                                                     ; 2513
                        801C   8F          52  B1  0012C  13$:    CMPW    R2, #32796                                      ; 2627
                                           13  12  00131          BNEQ    15$                                             ;
                           69              00  FB  00133          CALLS   #0, PRINT_REPLY                                 ; 2631
                                           67  D4  00136          CLRL    REPLY_PENDING                                   ; 2632
                          08   A7          01  D0  00138          MOVL    #1, OPERATOR_PRESENT                            ; 2633
                                 007281F4  8F  DD  0013C          PUSHL   #7504372                                        ; 2634
                           68              01  FB  00142  14$:    CALLS   #1, LIB$STOP                                    ;
                                           04  00145           RET                                                     ; 2513
                        8084   8F          52  B1  00146  15$:    CMPW    R2, #32900                                      ; 2637
                                           07  13  00148          BEQL    16$                                             ;
                        81DB   8F          52  B1  0014D          CMPW    R2, #33243                                      ; 2638
                                           0B  12  00152          BNEQ    17$                                             ;
                          18   A7          01  CE  00154  16$:    MNEGL   #1, PREVIOUS_STATUS                             ; 2643
                                           67  D4  00158          CLRL    REPLY_PENDING                                   ; 2644
                          08   A7          01  D0  0015A          MOVL    #1, OPERATOR_PRESENT                            ; 2645
                                           04  0015E           RET                                                     ; 2513
                        81D3   8F          52  B1  0015F  17$:    CMPW    R2, #33235                                      ; 2649
                                           07  13  00164          BEQL    18$                                             ;
                        81E3   8F          52  B1  00166          CMPW    R2, #33251                                      ; 2648
                                           10  12  0016B          BNEQ    19$                                             ;
                          18   A7          01  CE  0016D  18$:    MNEGL   #1, PREVIOUS_STATUS                             ; 2654
                                           67  D4  00171          CLRL    REPLY_PENDING                                   ; 2655
                          08   A7          01  D0  00173          MOVL    #1, OPERATOR_PRESENT                            ; 2656
                        0000V  CF          00  FB  00177          CALLS   #0, INVALID_COMMAND                             ; 2657
                                           04  0017C           RET                                                     ; 2513
                                           67  D4  0017D  19$:    CLRL    REPLY_PENDING                                   ; 2665
                          08   A7          01  D0  0017F          MOVL    #1, OPERATOR_PRESENT                            ; 2666
                    7E    00D0   C7          1A  C1  00183          ADDL3   #26, REPLY_DESC+4, -(SP)                        ; 2674
                                 00CC  C7      3C  00189          MOVZWL  REPLY_DESC, -(SP)                               ;
                                       1A      C2  0018E          SUBL2   #26, (SP)                                       ;
                                   48  A7      DD  00191          PUSHL   REPLY_BUFFER+4                                  ;
                                       46  A7  3C  00194          MOVZWL  REPLY_BUFFER+2, -(SP)                           ;
                                       44  A7  9A  00198          MOVZBL  REPLY_BUFFER, -(SP)                             ;
                                           05  DD  0019C          PUSHL   #5                                              ;
                                 007281E4  8F  DD  0019E          PUSHL   #7504356                                        ;
                           68              07  FB  001A4          CALLS   #7, LIB$STOP                                    ;
                                           04  001A7           RET                                                     ; 2678

; Routine Size:  424 bytes,    Routine Base:  $CODE$ + 071B
```

```
;  1791          2679  1 ROUTINE SAVE_DEVICE =
;  1792          2680  1
;  1793          2681  1 !++
;  1794          2682  1 ! Functional description:
;  1795          2683  1 !
;  1796          2684  1 !       This is a TPARSE action routine that is called
;  1797          2685  1 !       to create a string descriptor for the token
;  1798          2686  1 !       just parsed.  The token is a device name.
;  1799          2687  1 !
;  1800          2688  1 ! Input:
;  1801          2689  1 !
;  1802          2690  1 !       None.
;  1803          2691  1 !
;  1804          2692  1 ! Output:
;  1805          2693  1 !
;  1806          2694  1 !       None.
;  1807          2695  1 !
;  1808          2696  1 ! Implicit Inputs:
;  1809          2697  1 !
;  1810          2698  1 !       TPARSE_BLOCK = data structure defining TPARSE context.
;  1811          2699  1 !
;  1812          2700  1 ! Implicit outputs:
;  1813          2701  1 !
;  1814          2702  1 !       DEVICE_DESC = string descriptor of device name.
;  1815          2703  1 !
;  1816          2704  1 ! Routine Value:
;  1817          2705  1 !
;  1818          2706  1 !       1 If the device name length is within tolerance,
;  1819          2707  1 !       0 if not.
;  1820          2708  1 !
;  1821          2709  1 !--
;  1822          2710  1
;  1823          2711  2 BEGIN                                           ! Start of SAVE_DEVICE
;  1824          2712  2
;  1825          2713  2
;  1826          2714  2 EXTERNAL
;  1827          2715  2
;  1828          2716  2         DEVICE_DESC     : BBLOCK,               ! Device string descriptor
;  1829          2717  2         TPARSE_BLOCK    : BBLOCK;               ! TPARSE context data structure
;  1830          2718  2
;  1831          2719  2 IF .TPARSE_BLOCK[TPA$L_TOKENCNT] GTR MAX_DEV_LENGTH          ! Check for device name too long
;  1832          2720  2 THEN
;  1833          2721  2     0                                                       ! Return failure
;  1834          2722  2 ELSE
;  1835          2723  3     BEGIN
;  1836          2724  3     DEVICE_DESC[DSC$W_LENGTH]  = .TPARSE_BLOCK[TPA$L_TOKENCNT];
;  1837          2725  3     DEVICE_DESC[DSC$A_POINTER] = .TPARSE_BLOCK[TPA$L_TOKENPTR];
;  1838          2726  3     1                                                       ! Return success
;  1839          2727  3     END
;  1840          2728  3
;  1841          2729  1 END;                                            ! End of SAVE_DEVICE


                                0000 00000 SAVE_DEVICE:
```

```
                                                        .WORD   Save nothing                                    ; 2679
                        3F      0000G   CF      D1 00002        CMPL    TPARSE_BLOCK+16, #63                    ; 2719
                                        03      15 00007        BLEQ    1$                                      ;
                                        50      D4 00009        CLRL    R0                                      ;
                                                04 0000B        RET                                             ;
                0000G   CF      0000G   CF      B0 0000C 1$:    MOVW    TPARSE_BLOCK+16, DEVICE_DESC            ; 2724
                0000G   CF      0000G   CF      D0 00013        MOVL    TPARSE_BLOCK+20, DEVICE_DESC+4          ; 2725
                        50              01      D0 0001A        MOVL    #1, R0                                  ; 2723
                                                04 0001D        RET                                             ; 2729

; Routine Size:  30 bytes,    Routine Base:  $CODE$ + 08C3
```

```
;  1843     2730  1 ROUTINE DO_SUBSTITUTE =
;  1844     2731  1
;  1845     2732  1 !++
;  1846     2733  1 ! Funtional desctiption:
;  1847     2734  1 !
;  1848     2735  1 !       This routine is merely a shell so that $COPY_INFO may be
;  1849     2736  1 !       called during the TPARSE operation to copy the new device
;  1850     2737  1 !       name to the mount data base.
;  1851     2738  1 !
;  1852     2739  1 !       Note that the previous device must be deallocated before
;  1853     2740  1 !       we copy the new device name into the data base.
;  1854     2741  1 !
;  1855     2742  1 ! Input:
;  1856     2743  1 !
;  1857     2744  1 !       None.
;  1858     2745  1 !
;  1859     2746  1 ! Output:
;  1860     2747  1 !
;  1861     2748  1 !       None.
;  1862     2749  1 !
;  1863     2750  1 ! Implict input:
;  1864     2751  1 !
;  1865     2752  1 !       DEVICE_DESC     : a device name descriptor
;  1866     2753  1 !       DEVICE_INDEX    : the current device index into the DEVICE_STRING vector
;  1867     2754  1 !
;  1868     2755  1 ! Implict output:
;  1869     2756  1 !
;  1870     2757  1 !       The mount data base may be modified.
;  1871     2758  1 !
;  1872     2759  1 ! Routine value:
;  1873     2760  1 !
;  1874     2761  1 !       See the description of $COPY_INFO.
;  1875     2762  1 !--
;  1876     2763  1
;  1877     2764  2 BEGIN                                           ! Start of DO_SUBSTITUE
;  1878     2765  2
;  1879     2766  2 EXTERNAL
;  1880     2767  2         DEVICE_INDEX    : LONG,
;  1881     2768  2         DEVICE_DESC     : BBLOCK;
;  1882     2769  2
;  1883     2770  2 EXTERNAL ROUTINE
;  1884     2771  2         $DALLOC_DEVS$U  : ADDRESSING_MODE (GENERAL),    ! Address of the transfer vector
;  1885     2772  2         $COPY_INFO$U    : ADDRESSING_MODE (GENERAL);    ! Address of the transfer vector
;  1886     2773  2
;  1887     2774  2 $DALLOC_DEVS$U (1);                             ! Deallocate old device
;  1888     2775  2 $COPY_INFO$U (.DEVICE_INDEX, DEVICE_DESC)       ! Copy string and return status
;  1889     2776  2
;  1890     2777  1 END;                                           ! End of DO_SUBSTITUTE


                                                .EXTRN  $COPY_INFO$U

                                0000 00000 DO_SUBSTITUTE:
                                                .WORD   Save nothing                    ; 2730
                                01  DD 00002           PUSHL   #1                      ; 2774
                    00000000G   01  FB 00004           CALLS   #1, $DALLOC_DEVS$U      ;
```

```
                          0000G  CF  9F 0000B         PUSHAB  DEVICE_DESC                                    ; 2775
                          0000G  CF  DD 0000F         PUSHL   DEVICE_INDEX                                   ;
                00000000G  00        02  FB 00013    CALLS   #2, $COPY_INFO$U                               ;
                                     04  0001A       RET                                                    ; 2777

; Routine Size:  27 bytes,    Routine Base:  $CODE$ + 08E1
```

```
;  1892          2778  1 ROUTINE INVALID_COMMAND =
;  1893          2779  1
;  1894          2780  1 !++
;  1895          2781  1 ! Functional Description:
;  1896          2782  1 !
;  1897          2783  1 !       This routine is the TPARSE action routine that implements
;  1898          2784  1 !       invalid command handling and reporting.  If we get here,
;  1899          2785  1 !       it means that TPARSE has detected a bogus operator reply.
;  1900          2786  1 !       The user is notified that the operator response was invalid,
;  1901          2787  1 !       and the mount operation continues.  If the condition that
;  1902          2788  1 !       caused the initial error still exists, then MOUNT will issue
;  1903          2789  1 !       another request to the operator.  The reason the operator is
;  1904          2790  1 !       not notified of his mistake is that there is no way to target
;  1905          2791  1 !       a message to specific operator.
;  1906          2792  1 !
;  1907          2793  1 ! Input:
;  1908          2794  1 !
;  1909          2795  1 !       None.
;  1910          2796  1 !
;  1911          2797  1 ! Output:
;  1912          2798  1 !
;  1913          2799  1 !       None.
;  1914          2800  1 !
;  1915          2801  1 ! Implicit Inputs:
;  1916          2802  1 !
;  1917          2803  1 !       None.
;  1918          2804  1 !
;  1919          2805  1 ! Implicit Outputs:
;  1920          2806  1 !
;  1921          2807  1 !       The user is informed of the operator's mistake.
;  1922          2808  1 !
;  1923          2809  1 ! Routine value:
;  1924          2810  1 !
;  1925          2811  1 !       Always 1.
;  1926          2812  1 !--
;  1927          2813  1
;  1928          2814  2 BEGIN                                           ! Start of INVALID_COMMAND
;  1929          2815  2
;  1930          2816  2 SIGNAL (MOUN$_INVLDRESP);
;  1931          2817  2
;  1932          2818  2 1
;  1933          2819  1 END;                                           ! End of INVALID_COMMAND


                                        0000 00000 INVALID_COMMAND:
                                                   .WORD   Save nothing                                 ; 2778
                            0072A043    8F  DD 00002           PUSHL   #7512131                         ; 2816
                  00000000G   00        01  FB 00008           CALLS   #1, LIB$SIGNAL                   ;
                              50        01  D0 0000F           MOVL    #1, R0                           ; 2819
                                        04 00012               RET                                      ;

; Routine Size:  19 bytes,    Routine Base:  $CODE$ + 08FC
```

```
;  1935     2820  1 GLOBAL ROUTINE $COPY_INFO (DEV_INDEX, DEV_DESC) =
;  1936     2821  1
;  1937     2822  1 !++
;  1938     2823  1 ! Functional description:
;  1939     2824  1 !
;  1940     2825  1 !       This routine provides a secure way of copying a device name
;  1941     2826  1 !       string from the caller (in user mode) to MOUNT's protected
;  1942     2827  1 !       data base (in EXEC mode).
;  1943     2828  1 !
;  1944     2829  1 ! Input:
;  1945     2830  1 !
;  1946     2831  1 !       DEV_INDEX       : A number from 0 to .DEVICE_COUNT
;  1947     2832  1 !       DEV_DESC        : Address of a device name descriptor
;  1948     2833  1 !
;  1949     2834  1 ! Output:
;  1950     2835  1 !
;  1951     2836  1 !       None.
;  1952     2837  1 !
;  1953     2838  1 ! Implicit input:
;  1954     2839  1 !
;  1955     2840  1 !       DEVICE_STRING   : A vector of device name descriptors
;  1956     2841  1 !       DEVICE_COUNT    : The number of devices specified by the user.
;  1957     2842  1 !
;  1958     2843  1 ! Implicit output:
;  1959     2844  1 !
;  1960     2845  1 !       The DEVICE_STRING vector may be modified.
;  1961     2846  1 !
;  1962     2847  1 ! Routine value:
;  1963     2848  1 !
;  1964     2849  1 !       SS$_NORMAL      : Normal successful completion
;  1965     2850  1 !       SS$_ACCVIO      : The specified device name cannot be read.
;  1966     2851  1 !       SS$_BADPARAM    : The specified device name has a zero length,
;  1967     2852  1 !                         or is longer than LOG$C_NAMLENGTH bytes, or
;  1968     2853  1 !                         DEV_INDEX is not a reasonable value.
;  1969     2854  1 !--
;  1970     2855  1
;  1971     2856  2 BEGIN                                           ! Start of $COPY_INFO
;  1972     2857  2
;  1973     2858  2 EXTERNAL
;  1974     2859  2         DEVICE_COUNT    : LONG,                 ! # of drives
;  1975     2860  2         DEVICE_STRING   : VECTOR VOLATILE;      ! Descriptor list
;  1976     2861  2
;  1977     2862  2 BUILTIN
;  1978     2863  2         PROBER;                                 ! Probe for read access
;  1979     2864  2
;  1980     2865  2 LOCAL
;  1981     2866  2         DEV_NAME        : BBLOCK [DSC$K_S_BLN]; ! Local descriptor
;  1982     2867  2
;  1983     2868  2 !
;  1984     2869  2 ! Make sure DEV_INDEX is within a reasonable range.
;  1985     2870  2 !
;  1986     2871  2 IF (.DEV_INDEX LSS 0) OR (.DEV_INDEX GTR (.DEVICE_COUNT - 1))
;  1987     2872  2 THEN
;  1988     2873  2     RETURN (SS$_BADPARAM);
;  1989     2874  2
;  1990     2875  2 !
;  1991     2876  2 ! Probe the actual descriptor for read access.
```

```
;  1992          2877  2 !
;  1993          2878  2 IF NOT PROBER (%REF (0), %REF (DSC$K_S_BLN), .DEV_DESC)
;  1994          2879  2 THEN
;  1995          2880  2     RETURN (SS$_ACCVIO);
;  1996          2881  2
;  1997          2882  2 !
;  1998          2883  2 ! Copy the descriptor to internal storage and then probe the
;  1999          2884  2 ! device name for read access, and make sure that the device
;  2000          2885  2 ! name length is reasonable.
;  2001          2886  2 !
;  2002          2887  2 CH$MOVE (DSC$K_S_BLN, .DEV_DESC, DEV_NAME);
;  2003          2888  2 IF (.DEV_NAME [DSC$W_LENGTH] LEQ 0)
;  2004          2889  2 OR (.DEV_NAME [DSC$W_LENGTH] GTR 63)
;  2005          2890  2 THEN
;  2006          2891  2     RETURN (SS$_BADPARAM);
;  2007          2892  2 IF NOT PROBER (%REF (0), DEV_NAME [DSC$W_LENGTH], .DEV_NAME [DSC$A_POINTER])
;  2008          2893  2 THEN
;  2009          2894  2     RETURN (SS$_ACCVIO);
;  2010          2895  2
;  2011          2896  2 !
;  2012          2897  2 ! Copy the new device name to the mount data base,
;  2013          2898  2 ! and update the descriptor in DEVICE_STRING.
;  2014          2899  2 !
;  2015          2900  2 DEVICE_STRING [(.DEV_INDEX*2)] = .DEV_NAME [DSC$W_LENGTH];
;  2016          2901  2 CH$MOVE (.DEV_NAME [DSC$W_LENGTH],
;  2017          2902  2           .DEV_NAME [DSC$A_POINTER],
;  2018          2903  2           .DEVICE_STRING [(.DEV_INDEX*2)+1]
;  2019          2904  2          );
;  2020          2905  2
;  2021          2906  2 SS$_NORMAL
;  2022          2907  2
;  2023          2908  1 END;                                    ! End of $COPY_INFO


                                        .EXTRN  DEVICE_COUNT, DEVICE_STRING

                              007C 00000        .ENTRY  $COPY_INFO, Save R2,R3,R4,R5,R6      ;  2820
                           5E   08   C2 00002   SUBL2   #8, SP                               ;
                           56   04   AC D0 00005   MOVL    DEV_INDEX, R6                    ;  2871
                                21   19 00009   BLSS    1$                                 ;
                     50    0000G  CF   01   C3 0000B   SUBL3   #1, DEVICE_COUNT, R0         ;
                           50        56   D1 00011   CMPL    R6, R0                       ;
                                     16   14 00014   BGTR    1$                           ;
                08   BC    08        00   0C 00016   PROBER  #0, #8, @DEV_DESC             ;  2878
                                     1A   13 0001B   BEQL    3$                           ;
                     6E    08   BC   08   28 0001D   MOVC3   #8, @DEV_DESC, DEV_NAME      ;  2887
                           51        6E   3C 00022   MOVZWL  DEV_NAME, R1                 ;  2888
                                     05   15 00025   BLEQ    1$                           ;
                           3F        51   B1 00027   CMPW    R1, #63                      ;  2889
                                     04   1B 0002A   BLEQU   2$                           ;
                           50        14   D0 0002C 1$:  MOVL    #20, R0                  ;  2891
                                          04 0002F   RET                                  ;
                04   BE    6E        00   0C 00030 2$:  PROBER  #0, DEV_NAME, @DEV_NAME+4 ;  2892
                                     04   12 00035   BNEQ    4$                           ;
                           50        0C   D0 00037 3$:  MOVL    #12, R0                  ;  2894
                                          04 0003A   RET                                  ;
```

```
                50              56          01  78 0003B 4$:    ASHL    #1, R6, R0                              ; 2900
                          0000GCF40           51  D0 0003F      MOVL    R1, DEVICE_STRING[R0]                   ;
                                50      0000GCF40  D0 00045      MOVL    DEVICE_STRING+4[R0], R0                 ; 2903
                60        04    BE            51  28 0004B      MOVC3   R1, @DEV_NAME+4, (R0)                   ;
                                50          01  D0 00050      MOVL    #1, R0                                  ; 2908
                                                04 00053      RET                                             ;

; Routine Size:  84 bytes,    Routine Base:  $CODE$ + 090F
```

```
;  2025     2909  1 GLOBAL ROUTINE $CHANGE_PROT =
;  2026     2910  1
;  2027     2911  1 !++
;  2028     2912  1 ! Functional description:
;  2029     2913  1 !
;  2030     2914  1 !       This routine will change the page protection of this module's
;  2031     2915  1 !       OWN storage so that it may be written to in USER mode.
;  2032     2916  1 !
;  2033     2917  1 ! Input:
;  2034     2918  1 !
;  2035     2919  1 !       None.
;  2036     2920  1 !
;  2037     2921  1 ! Output:
;  2038     2922  1 !
;  2039     2923  1 !       None.
;  2040     2924  1 !
;  2041     2925  1 ! Implicit input:
;  2042     2926  1 !
;  2043     2927  1 !       1) The current access mode is EXEC or KERNEL.
;  2044     2928  1 !       2) VA_RANGE is a vector of two longword elements, containing the starting
;  2045     2929  1 !          and ending virtual addresses of the range of pages to work on.
;  2046     2930  1 !
;  2047     2931  1 ! Implicit output:
;  2048     2932  1 !
;  2049     2933  1 !       The pages are made USER readable.
;  2050     2934  1 !
;  2051     2935  1 ! Routine value:
;  2052     2936  1 !
;  2053     2937  1 !       Whatever status value is returned by $SETPRT.
;  2054     2938  1 !--
;  2055     2939  1
;  2056     2940  2 BEGIN                                           ! Start of $CHANGE_PROT
;  2057     2941  2
;  2058     2942  2 EXTERNAL
;  2059     2943  2         DEVICE_INDEX,                           ! Index into PHYS_NAME bblock
;  2060     2944  2         DATA_BASE_READY,                        ! Boolean
;  2061     2945  2         STORED_CONTEXT;                         ! Bit vector
;  2062     2946  2
;  2063     2947  2
;  2064     2948  2 !
;  2065     2949  2 ! Initialize three important variables referenced in VMOUNT.  This
;  2066     2950  2 ! must be done here as they are zeroed only once per $MOUNT call,
;  2067     2951  2 ! and must be written while in EXEC mode.
;  2068     2952  2 !
;  2069     2953  2 DEVICE_INDEX = 0;
;  2070     2954  2 DATA_BASE_READY = 0;
;  2071     2955  2 STORED_CONTEXT = 0;
;  2072     2956  2
;  2073     2957  2 !
;  2074     2958  2 ! Set the page protection of this module's data to allow user
;  2075     2959  2 ! mode read/write access.  This must be done here, in EXEC mode, since
;  2076     2960  2 ! this image is INSTALLed as a protected shareable image, which has
;  2077     2961  2 ! the effect of setting the protection to be USER read, EXEC write.
;  2078     2962  2 ! Note that the data sits in a special PSECT, to avoid changing
;  2079     2963  2 ! the page protection on adjacent pages.
;  2080     2964  2 !
;  2081     2965  3 $SETPRT (INADR=VA_RANGE, PROT=PRT$C_UW)
```

```
;  2082          2966  3
;  2083          2967  1 END;                                    ! End of $CHANGE_PROT


                                                                 .EXTRN  DATA_BASE_READY
                                                                 .EXTRN  STORED_CONTEXT, SYS$SETPRT

                                                                 .ENTRY  $CHANGE_PROT, Save nothing                      ;  2909
                                                 0000 00000      CLRL    DEVICE_INDEX                                    ;  2953
                                          0000G  CF   D4 00002   CLRL    DATA_BASE_READY                                 ;  2954
                                          0000G  CF   D4 00006   CLRL    STORED_CONTEXT                                  ;  2955
                                          0000G  CF   D4 0000A   MOVQ    #4, -(SP)                                       ;  2965
                                             7E       04 7D 0000E
                                                      7E 7C 00011   CLRQ    -(SP)
                                          0000'  CF   9F 00013   PUSHAB  VA_RANGE
                                 00000000G    00       05 FB 00017   CALLS   #5, SYS$SETPRT
                                                          04 0001E   RET                                                    ;  2967

;  Routine Size:  31 bytes,    Routine Base:  $CODE$ + 0963
```

```
;  2085          2968  1 GLOBAL ROUTINE $DALLOC_DEVS (SINGLE_DEVICE) =
;  2086          2969  1
;  2087          2970  1 !++
;  2088          2971  1 ! Functional description:
;  2089          2972  1 !
;  2090          2973  1 !       This routine will attempt to dealocate all devices that were
;  2091          2974  1 !       specified by the user that were not previously allocated.
;  2092          2975  1 !
;  2093          2976  1 ! Input:
;  2094          2977  1 !
;  2095          2978  1 !       SINGLE_DEVICE   : a longword boolean to  control whether all
;  2096          2979  1 !                         drives or just a single one is to be deallocated.
;  2097          2980  1 !                         If the latter, use DEVICE_INDEX to select the
;  2098          2981  1 !                         drive name from the PHYS_NAME vector.
;  2099          2982  1 !
;  2100          2983  1 ! Output:
;  2101          2984  1 !
;  2102          2985  1 !       None.
;  2103          2986  1 !
;  2104          2987  1 ! Implicit input:
;  2105          2988  1 !
;  2106          2989  1 !       CLEANUP_ALLOC   : a bit vector where each bit represents an
;  2107          2990  1 !                         an entry in PHYS_NAME that was not previously
;  2108          2991  1 !                         allocated by the user.
;  2109          2992  1 !       DEVICE_INDEX    : index into PHYS_NAME vector
;  2110          2993  1 !       PHYS_NAME       : a vector of device name descriptors for all
;  2111          2994  1 !                         devices specified by the user.
;  2112          2995  1 !       PHYS_COUNT      : a high-water mark that indicates the number
;  2113          2996  1 !                         of devices actually used in the mount.
;  2114          2997  1 !
;  2115          2998  1 ! Implicit output:
;  2116          2999  1 !
;  2117          3000  1 !       All devices not mounted or not previously allocated are deallocated.
;  2118          3001  1 !
;  2119          3002  1 ! Routine value:
;  2120          3003  1 !
;  2121          3004  1 !       SS$_NORMAL      : Normal successful completion
;  2122          3005  1 !--
;  2123          3006  1
;  2124          3007  2 BEGIN                                           ! Start of $DALLOC_DEVS
;  2125          3008  2
;  2126          3009  2 EXTERNAL
;  2127          3010  2         CLEANUP_ALLOC   : BITVECTOR VOLATILE,  ! cleanup bit vector
;  2128          3011  2         DEV_ALLOCATED   : BITVECTOR VOLATILE,  ! device allready allocated
;  2129          3012  2         DEV_ACQUIRED    : BITVECTOR VOLATILE,  ! device is interlocked
;  2130          3013  2         DEVICE_INDEX    : LONG,                ! current device
;  2131          3014  2         PHYS_COUNT      : LONG,                ! count of physical devices
;  2132          3015  2         PHYS_NAME       : VECTOR VOLATILE,     ! device descriptor array
;  2133          3016  2         MOUNT_OPTIONS   : BITVECTOR,           ! mount options and modifiers
;  2134          3017  2         STORED_CONTEXT  : BITVECTOR;           ! special mount context
;  2135          3018  2
;  2136          3019  2
;  2137          3020  2 IF .SINGLE_DEVICE
;  2138          3021  2 THEN
;  2139          3022  2     !
;  2140          3023  2     ! Deallocate a specific device.  This is used to deallocate a
;  2141          3024  2     ! previously allocated device when the operator instructs us to
```

```
2       ! substitute another device in its place.
2       !
3       BEGIN
3       IF .CLEANUP_ALLOC[.DEVICE_INDEX]
3       THEN
4           BEGIN
4           $DALLOC(DEVNAM = PHYS_NAME[.DEVICE_INDEX*2]);
4           CLEANUP_ALLOC[.DEVICE_INDEX] = 0;
3           END;
3       DEV_ALLOCATED[.DEVICE_INDEX] = 0;
3       DEV_ACQUIRED[.DEVICE_INDEX] = 0;
3       PHYS_COUNT = .DEVICE_INDEX;
3       END
2   ELSE
3       BEGIN
3       !
3       ! Deallocate every device listed in the PHYS_NAME device name descriptor
3       ! array, that was not previously allocated by the user.  If the device is
3       ! mounted, it will not be deallocated (this check is done in the $DALLOC
3       ! system service).
3       !
3       INCR I FROM 0 TO .PHYS_COUNT-1 DO
3           IF .CLEANUP_ALLOC[.I]
3           THEN
4               BEGIN
4               $DALLOC(DEVNAM = PHYS_NAME[.I*2]);
4               DEV_ALLOCATED[.I] = 0;
4               DEV_ACQUIRED[.I] = 0;
4               CLEANUP_ALLOC[.I] = 0;
3               END;
2       END;
2
2   SS$_NORMAL
2
1   END;                                        ! End of $DALLOC_DEVS


                                                .EXTRN  CLEANUP_ALLOC, DEV_ALLOCATED
                                                .EXTRN  DEV_ACQUIRED, PHYS_COUNT
                                                .EXTRN  SYS$DALLOC

                          007C 00000            .ENTRY  $DALLOC_DEVS, Save R2,R3,R4,R5,R6          ; 2968
         56      0000G  CF  9E 00002            MOVAB   DEVICE_INDEX, R6                           ;
         55  00000000G  00  9E 00007            MOVAB   SYS$DALLOC, R5                             ;
         54      0000G  CF  9E 0000E            MOVAB   CLEANUP_ALLOC, R4                          ;
         2C         04  AC  E9 00013            BLBC    SINGLE_DEVICE, 4$                          ; 3020
12       64             66  E1 00017            BBC     DEVICE_INDEX, CLEANUP_ALLOC, 1$            ; 3028
                        7E  D4 0001B            CLRL    -(SP)                                      ; 3031
50       66             01  78 0001D            ASHL    #1, DEVICE_INDEX, R0                       ;
              0000GCF40     DF 00021            PUSHAL  PHYS_NAME[R0]                              ;
         65             02  FB 00026            CALLS   #2, SYS$DALLOC                             ;
00       64             66  E5 00029            BBCC    DEVICE_INDEX, CLEANUP_ALLOC, 1$            ; 3032
         50             66  D0 0002D  1$:       MOVL    DEVICE_INDEX, R0                           ; 3034
00   0000G   CF         50  E5 00030            BBCC    R0, DEV_ALLOCATED, 2$                      ;
00   0000G   CF         50  E5 00036  2$:       BBCC    R0, DEV_ACQUIRED, 3$                       ; 3035
     0000G   CF         50  D0 0003C  3$:       MOVL    R0, PHYS_COUNT                             ; 3036
```

```
                                                30  11 00041                BRB     9$                                      ; 3020
                                          53    CF  D0 00043 4$:         MOVL    PHYS_COUNT, R3                          ; 3046
                                          52    01  CE 00048             MNEGL   #1, I                                   ;
                                                22  11 0004B             BRB     8$                                      ;
                                    1E          52  E1 0004D 5$:         BBC     I, CLEANUP_ALLOC, 8$                    ; 3047
                                          64    7E  D4 00051             CLRL    -(SP)                                   ; 3050
                                    50    52    01  78 00053             ASHL    #1, I, R0                               ;
                                          0000GCF 40  DF 00057           PUSHAL  PHYS_NAME[R0]                           ;
                                          65    02  FB 0005C             CALLS   #2, SYS$DALLOC                          ;
                                    00    0000G CF  52  E5 0005F         BBCC    I, DEV_ALLOCATED, 6$                    ; 3051
                                    00    0000G CF  52  E5 00065 6$:     BBCC    I, DEV_ACQUIRED, 7$                     ; 3052
                                    00          64  52  E5 0006B 7$:     BBCC    I, CLEANUP_ALLOC, 8$                    ; 3053
                                    DA          52  53  F2 0006F 8$:     AOBLSS  R3, I, 5$                               ; 3047
                                          50    01  D0 00073 9$:         MOVL    #1, R0                                  ; 3059
                                                04  00076               RET                                             ;

; Routine Size:  119 bytes,    Routine Base:  $CODE$ + 0982
```

```
;  2178     3060  1 ROUTINE EXIT_HANDLER : NOVALUE =
;  2179     3061  1
;  2180     3062  1 !++
;  2181     3063  1 ! Fucntional Description:
;  2182     3064  1 !
;  2183     3065  1 !       This routine is called by the OS on exit (for whatever reason) from
;  2184     3066  1 !       the MOUNT facility.  This routine will clean up any mess left by MOUNT.
;  2185     3067  1 !
;  2186     3068  1 ! Input Parameters:
;  2187     3069  1 !       none
;  2188     3070  1 !
;  2189     3071  1 ! Implicit Inputs:
;  2190     3072  1 !       none
;  2191     3073  1 !
;  2192     3074  1 ! Output Parameters:
;  2193     3075  1 !       none
;  2194     3076  1 !
;  2195     3077  1 ! Implicit Outputs:
;  2196     3078  1 !       none
;  2197     3079  1 !
;  2198     3080  1 !--
;  2199     3081  1
;  2200     3082  2 BEGIN                                           ! Start of EXIT_HANDLER
;  2201     3083  2
;  2202     3084  2 EXTERNAL ROUTINE
;  2203     3085  2         $DALLOC_DEVS$U  : ADDRESSING_MODE (GENERAL);    ! Address of transfer vector
;  2204     3086  2
;  2205     3087  2 !
;  2206     3088  2 ! Attempt to deallocate devices that are not mounted and
;  2207     3089  2 ! were not previously allocated.
;  2208     3090  2 !
;  2209     3091  2 $DALLOC_DEVS$U (0);                             ! Attempt to deallocate devices
;  2210     3092  2
;  2211     3093  2 IF .REPLY_PENDING
;  2212     3094  2 THEN
;  2213     3095  2     !
;  2214     3096  2     ! Cancel any outstanding operator requests.
;  2215     3097  2     !
;  2216     3098  2     CANCEL_REQUEST (REQUEST_NOT_SATISFIED);
;  2217     3099  2
;  2218     3100  2 $SETSFM (ENBFLG = .SS_FAIL_MODE);
;  2219     3101  2
;  2220     3102  1 END;                                           ! End of EXIT_HANDLER


                                0000 00000 EXIT_HANDLER:
                                           .WORD   Save nothing                    ;  3060
                                7E  D4 00002           CLRL    -(SP)                ;  3091
00000000G   00                  01  FB 00004           CALLS   #1, $DALLOC_DEVS$U   ;
                07      0000'   CF  E9 0000B           BLBC    REPLY_PENDING, 1$    ;  3093
                                7E  D4 00010           CLRL    -(SP)                ;  3098
    F9AA        CF              01  FB 00012           CALLS   #1, CANCEL_REQUEST   ;
                        0000'   CF  DD 00017 1$:       PUSHL   SS_FAIL_MODE         ;  3100
00000000G   00                  01  FB 0001B           CALLS   #1, SYS$SETSFM       ;
```

```
                        04 00022        RET                                     ; 3102

; Routine Size:  35 bytes,    Routine Base:  $CODE$ + 09F9
```

```
;  2222          3103  1 !
;  2223          3104  1 ! The TPARSE tables are here because they mangle
;  2224          3105  1 ! PSECT definitions.
;  2225          3106  1 !
;  2226          3107  1
;  2227          3108  1 !
;  2228          3109  1 ! Define the TPARSE grammar of the possible operator replies.
;  2229          3110  1 !
;  2230          3111  1 $INIT_STATE     (STATE_TABLE,KEY_TABLE);
;  2231          3112  1
;  2232          3113  1 !
;  2233          3114  1 ! Initial state
;  2234          3115  1 !
;  2235        P 3116  1 $STATE  (START,
;  2236        P 3117  1          ((SUBSTITUTE_COMMAND),  TPA$_EXIT,      DO_SUBSTITUTE),
;  2237        P 3118  1          (TPA$_LAMBDA,           TPA$_EXIT,      INVALID_COMMAND)
;  2238          3119  1          );
;  2239          3120  1
;  2240          3121  1 !
;  2241          3122  1 ! SUBSTITUTE command.  'SUBSTITUTE'<TPA$_BLANK><DEVICE><TEXT>
;  2242          3123  1 !
;  2243        P 3124  1 $STATE  (SUBSTITUTE_COMMAND,
;  2244        P 3125  1          ('SUBSTITUTE')
;  2245          3126  1          );
;  2246          3127  1
;  2247          3128  1 !$STATE (,
;  2248          3129  1 !          (TPA$_BLANK)
;  2249          3130  1 !          );
;  2250          3131  1
;  2251        P 3132  1 $STATE  (,
;  2252        P 3133  1          ((DEVICE),              TPA$_EXIT,      SAVE_DEVICE)
;  2253          3134  1          );
;  2254          3135  1
;  2255          3136  1 !$STATE (,
;  2256          3137  1 !          ((TEXT),                TPA$_EXIT)
;  2257          3138  1 !          );
;  2258          3139  1
;  2259          3140  1 !
;  2260          3141  1 ! Device name.  It may be a device spec or a logical name string.
;  2261          3142  1 !
;  2262        P 3143  1 $STATE  (DEVICE,
;  2263        P 3144  1          (TPA$_SYMBOL)
;  2264          3145  1          );
;  2265          3146  1
;  2266        P 3147  1 $STATE  (,
;  2267        P 3148  1          (':',                   TPA$_EXIT),
;  2268        P 3149  1          (TPA$_LAMBDA,           TPA$_EXIT)
;  2269          3150  1          );
;  2270          3151  1 !
;  2271          3152  1 ! Text.  The remainder of the operator response is treated
;  2272          3153  1 ! as a comment, and has no effect on the mount.  If there is
;  2273          3154  1 ! a comment, at least one blank must separate it from the
;  2274          3155  1 ! previous section of the operator response.
;  2275          3156  1 !
;  2276        P 3157  1 $STATE  (TEXT,
;  2277        P 3158  1          (TPA$_BLANK,            MORE_TEXT),
;  2278        P 3159  1          (TPA$_EOS,              TPA$_EXIT)
```

```
;  2279          3160  1          );
;  2280          3161  1
;  2281        P 3162  1 $STATE   (MORE_TEXT,
;  2282        P 3163  1          (TPA$_ANY,          MORE_TEXT),
;  2283        P 3164  1          (TPA$_EOS,          TPA$_EXIT)
;  2284          3165  1          );
;  2285          3166  1 END
;  2286          3167  0 ELUDOM


                                                    .PSECT  _LIB$KEY1$,NOWRT,  SHR,  PIC,1

                                                00000 ;TPA$KEYSTO
                                                      U.10:   .BLKB   0
                                    45  54  55  54  49  54  53  42  55  53  00000 ;TPA$KEYST
                                                      U.12:   .ASCII  \SUBSTITUTE\                    ;
                                                FF    0000A             .BYTE   -1                      ;
                                                FF    0000B ;TPA$KEYFILL
                                                      U.14:   .BYTE   -1                              ;

                                                            .PSECT  _LIB$STATE$,NOWRT,  SHR,  PIC,1

                                                00000 STATE_TABLE::
                                                            .BLKB   0
                                                00000 START:    .BLKB   0
                                            99F8  00000 ;TPA$TYPE
                                                      U.2:    .WORD   -26120                          ;
                                            0000* 00002 ;TPA$SUBEXP
                                                      U.4:    .WORD   <<U.3-U.4>-2>                   ;
                                        00000000* 00004 ;TPA$ACTION
                                                      U.5:    .LONG   <<DO_SUBSTITUTE-U.5>-4>         ;
                                            FFFF  00008 ;TPA$TARGET
                                                      U.6:    .WORD   -1                              ;
                                            95F6  0000A ;TPA$TYPE
                                                      U.7:    .WORD   -27146                          ;
                                        00000000* 0000C ;TPA$ACTION
                                                      U.8:    .LONG   <<INVALID_COMMAND-U.8>-4>       ;
                                            FFFF  00010 ;TPA$TARGET
                                                      U.9:    .WORD   -1                              ;
                                                  00012 ;SUBSTITUTE_COMMAND
                                                      U.3:    .BLKB   0
                                            0500  00012 ;TPA$TYPE
                                                      U.13:   .WORD   1280                            ;
                                            9DF8  00014 ;TPA$TYPE
                                                      U.15:   .WORD   -25096                          ;
                                            0000* 00016 ;TPA$SUBEXP
                                                      U.17:   .WORD   <<U.16-U.17>-2>                 ;
                                        00000000* 00018 ;TPA$ACTION
                                                      U.18:   .LONG   <<SAVE_DEVICE-U.18>-4>          ;
                                            FFFF  0001C ;TPA$TARGET
                                                      U.19:   .WORD   -1                              ;
                                                  0001E ;DEVICE
                                                      U.16:   .BLKB   0
                                            05F1  0001E ;TPA$TYPE
                                                      U.20:   .WORD   1521                            ;
                                            103A  00020 ;TPA$TYPE
```

```
                U.21:   .WORD   4154                          ;
FFFF   00022 ;TPA$TARGET
                U.22:   .WORD   -1                            ;
15F6   00024 ;TPA$TYPE
                U.23:   .WORD   5622                          ;
FFFF   00026 ;TPA$TARGET
                U.24:   .WORD   -1                            ;
       00028 TEXT:      .BLKB   0
11F2   00028 ;TPA$TYPE
                U.25:   .WORD   4594                          ;
0000*  0002A ;TPA$TARGET
                U.27:   .WORD   <<U.26-U.27>-2>               ;
15F7   0002C ;TPA$TYPE
                U.28:   .WORD   5623                          ;
FFFF   0002E ;TPA$TARGET
                U.29:   .WORD   -1                            ;
       00030 ;MORE_TEXT
                U.26:   .BLKB   0
11ED   00030 ;TPA$TYPE
                U.30:   .WORD   4589                          ;
0000*  00032 ;TPA$TARGET
                U.31:   .WORD   <<U.26-U.31>-2>               ;
15F7   00034 ;TPA$TYPE
                U.32:   .WORD   5623                          ;
FFFF   00036 ;TPA$TARGET
                U.33:   .WORD   -1                            ;

                        .PSECT  _LIB$KEY0$,NOWRT,  SHR,  PIC,1

       00000 KEY_TABLE::
                        .BLKB   0
       00000 ;TPA$KEY0
                U.1:    .BLKB   0
0000*  00000 ;TPA$KEY
                U.11:   .WORD   <U.10-U.1>                    ;

                        .EXTRN  LIB$SIGNAL, LIB$STOP
```

```
;                       PSECT SUMMARY
;
;       Name                    Bytes                   Attributes
;
;  $USER_DATA$                   1032  NOVEC,  WRT,  RD ,NOEXE,NOSHR,  LCL,  REL,  CON,NOPIC,ALIGN(9)
;  $PLIT$                         140  NOVEC,NOWRT,  RD ,NOEXE,NOSHR,  LCL,  REL,  CON,NOPIC,ALIGN(2)
;  $CODE$                        2588  NOVEC,NOWRT,  RD ,  EXE,NOSHR,  LCL,  REL,  CON,NOPIC,ALIGN(2)
;  .  ABS  .                        0  NOVEC,NOWRT,NORD ,NOEXE,NOSHR,  LCL,  ABS,  CON,NOPIC,ALIGN(0)
;  $GLOBAL$                         8  NOVEC,  WRT,  RD ,NOEXE,NOSHR,  LCL,  REL,  CON,NOPIC,ALIGN(2)
;  _LIB$KEY0$                       2  NOVEC,NOWRT,  RD ,  EXE,  SHR,  LCL,  REL,  CON,  PIC,ALIGN(1)
;  _LIB$STATE$                     56  NOVEC,NOWRT,  RD ,  EXE,  SHR,  LCL,  REL,  CON,  PIC,ALIGN(1)
;  _LIB$KEY1$                      12  NOVEC,NOWRT,  RD ,  EXE,  SHR,  LCL,  REL,  CON,  PIC,ALIGN(1)


;                       Library Statistics
;
```

```
;                                  --------- Symbols ---------      Pages      Processing
;       File                       Total    Loaded   Percent      Mapped      Time
;
;  _$255$DUA28:[SYSLIB]LIB.L32;1    18619       113         0        1000       00:02.0
;  _$255$DUA28:[SYSLIB]TPAMAC.L32;1    42        27        64          14       00:00.2




;                                  COMMAND QUALIFIERS

;       BLISS/CHECK=(FIELD,INITIAL,OPTIMIZE)/LIS=LIS$:ASSIST/OBJ=OBJ$:ASSIST MSRC$:ASSIST/UPDATE=(ENH$:ASSIST)

; Size:          2588 code + 1250 data bytes
; Run Time:         01:01.8
; Elapsed Time:     02:09.2
; Lines/CPU Min:     3077
; Lexemes/CPU-Min: 33437
; Memory Used:  233 pages
; Compilation Complete
```

0243 AH-BT13A-SE
VAX/VMS V4.0

DIGITAL EQUIPMENT CORPORATION
CONFIDENTIAL AND PROPRIETARY

BINDVL
LIS

MOUNT

SYSFAO
LIS

MOUNTSHR
MAP

TEMPLATE
LIS

VMOUNT
MAP

ASSIST
LIS

ALLOCM
LIS

MOUDEF
B32